



Document No.: KKM011712-187

Item No: 501927603











**Description:**

CBS CSK FLAT HD TX25 6NIBS SAW HALF THRD TYP17 WZP CR3 STL  
5x90

Material: C10B21

Certificate No.: [CPR-J-00891-20](#)

Report No.: [1015-CPR-30-14940/2/JZ](#)

	Nominal diameter	Inner thread diameter	Head diameter	Total length	Thread length	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre)	Head pull-through parameter	Yield moment $I_2 = 1d$	Tensile capacity
Description	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)	(N/mm <sup>2</sup> )	(N/mm <sup>2</sup> )	(Nmm)	(kN)
										
5.0x90	4.7 - 5.0	2.9 - 3.2	9.64 - 10.0	88.25 - 90.0	58.25 - 61.75	4.1	17.36 / 12.87	23.98	5844 (Thread section, 14 Deg)	9.22
Characteristic density of wood $\rho_k$ (kg/m <sup>3</sup> )						350	350	350	-	
Durability (i.e. corrosion protection)						Blue/yellow zinc plated Cr3, (3 - 10) $\mu$ m (Service Class 1 and 2 acc. To EN 1995-1-1)				

**The manufacturer declares for:**

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 29 Aug 2020



Hieu Trong Nguyen

# SWISSTEC Sourcing Ltd.



Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,  
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM011712-187

Item No: 501927603











**Description:**

CBS CSK FLAT HD TX25 6NIBS SAW HALF THRD TYP17 WZP CR3 STL  
5x90

Material: Carbon steel C1022

Certificate No.: [E-30-20652-17](#)

Report No.: [1015-CPR-30-11211/7](#)

	Nominal diameter	Inner thread diameter	Head diameter	Total length	Thread length	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre)	Head pull-through parameter	Yield moment (Ring / Smooth section) $I_2 = 1d$	Tensile capacity
Description	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)	(N/mm <sup>2</sup> )	(N/mm <sup>2</sup> )	(Nmm)	(kN)
										
5.0x90	4.7 - 5.0	2.9 - 3.2	9.64 - 10.0	88.25 - 90.0	58.25 - 61.75	2.58	17.41 / 13.73	20.26	7879 / 12283	9.95
Characteristic density of wood $\rho_k$ (kg/m <sup>3</sup> )						350	440	350	-	
Durability (i.e. corrosion protection)						Blue/yellow zinc plated Cr3, (3 - 10) $\mu$ m (Service Class 1 and 2 acc. To EN 1995-1-1)				

**The manufacturer declares for:**

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 17 Apr 2019



Hieu Trong Nguyen