

# Environmental product declaration

In accordance with ISO 14025 and EN 15804 +A2

weber outdoor repair Repair and levelling plaster (weber outdoor repair Korjaus- ja tasoituslaasti)



**Owner of the declaration:**

Saint-Gobain Finland Oy

**Declared unit:**

1 kg weber outdoor repair Repair and levelling plaster (weber outdoor repair Korjaus- ja tasoituslaasti)

**Product Category:**

Technical-chemical building materials products

**This declaration is based on Product Category Rules:**

CEN Standard EN 15804:2012+A2:2019 serves as core PCR  
NPCR 009:2018 Part B for Technical - Chemical products in the building and construction industry

**Program operator:**

The Norwegian EPD Foundation

**Declaration number:**

NEPD-3594-2259-EN

**Registration number:**

NEPD-3594-2259-EN

**Issue date:** 30.06.2022

**Valid to:** 30.06.2027

**EPD Software:**

LCA.no EPD generator

**System ID:** 50135

## General information

### Product

weber outdoor repair Repair and levelling plaster (weber outdoor repair Korjaus- ja tasoituslaasti)

### Program operator:

Post Box 5250 Majorstuen, 0303 Oslo, Norway  
The Norwegian EPD Foundation  
Phone: +47 23 08 80 00  
web: [post@epd-norge.no](mailto:post@epd-norge.no)

### Declaration number:

NEPD-3594-2259-EN

### This declaration is based on Product Category Rules:

CEN Standard EN 15804:2012+A2:2019 serves as core PCR  
NPCR 009:2018 Part B for Technical - Chemical products in the building and construction industry

### Statement of liability:

The owner of the declaration shall be liable for the underlying information and evidence. EPD Norway shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

### Declared unit:

1 kg weber outdoor repair Repair and levelling plaster (weber outdoor repair Korjaus- ja tasoituslaasti)

### Declared unit with option:

A1,A2,A3,A4,A5,C1,C2,C3,C4,D

### Functional Unit

Not relevant

### General information on verification of EPD from EPD tools:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4. Individual third party verification of each EPD is not required when the EPD tool is i) integrated into the company's environmental management system, ii) the procedures for use of the EPD tool are approved by EPD Norway, and iii) the process is reviewed annually. See Appendix G of EPD-Norway's General Programme Instructions for further information on EPD tools.

### Verification:

Independent verification of data, other environmental information and the declaration according to ISO 14025:2010, § 8.1.3 and § 8.1.4

Third party verifier:

Anne Rønning, Norsus AS

(Independent verifier approved by EPD Norway)

### Owner of the declaration:

Saint-Gobain Finland Oy  
Contact person: Anne Kaiser  
Phone: +358400289933  
e-mail: [anne.kaiser@saint-gobain.com](mailto:anne.kaiser@saint-gobain.com)

### Manufacturer:

Saint-Gobain Finland Oy  
P.O. Box 70, Fi-00381 Helsinki  
Finland

### Place of production:

Saint-Gobain Weber Parainen  
Parainen Premix plant, Kalkkitehtaantie, 21600 Parainen  
Finland

### Management system:

ISO 9001:2015, ISO 14001:2015 and OHSAS 18001:2007

### Organisation no:

FI09515553

### Issue date: 30.06.2022

### Valid to: 30.06.2027

### Year of study:

2021

### Comparability:

EPD of construction products may not be comparable if they not comply with EN 15804 and seen in a building context.

### The EPD has been worked out by:

The declaration is created using EPD tool lca.tools ver EPD2021.09, developed by LCA.no. The EPD tool is integrated in the company's management system, and has been approved by EPD Norway.


### Developer of EPD:

Päivi Pesu

### Reviewer of company-specific input data and EPD:

Helene Løvkvist Andersen

### Approved:



Håkon Hauan  
Managing Director of EPD-Norway

## Product

### Product description:

weber outdoor repair is cement based concrete repair plaster for wall and floor surfaces in indoor and outdoor areas. It is used in repair of small local surface damage or holes and patching both vertical and horizontal concrete surfaces. Examples of uses: concrete socles, stairs and columns. The product has an excellent adhesion and is frost resistant. It is easy to spread by hand. Delivered in 5 kg (6415910031770) and 15 kg bags (6415910031800).

### Product specification

The composition of the product is described in the following table:

Materials	%
Binder	20-40
Aggregate	50-80
Additives	1-3
Packaging, PE	0,01 kg
Packaging, pallet	0,037 kg
Packaging, cardboard	0,02 kg

### Reference service life, building

## LCA: Calculation rules

### Declared unit:

1 kg weber outdoor repair Repair and levelling plaster (weber outdoor repair Korjaus- ja tasoituslaasti)

### Cut-off criteria:

All major raw materials and all the essential energy is included. The production processes for raw materials and energy flows with very small amounts (less than 1%) are not included. These cut-off criteria do not apply for hazardous materials and substances.

### Data quality:

Specific data for the product composition are provided by the manufacturer. The data represent the production of the declared product and were collected for EPD development in the year of study. Background data is based on EPDs according to EN 15804 and different LCA databases. The data quality of the raw materials in A1 is presented in the table below.

Materials	Source	Data quality	Year
Additives	ecoinvent 3.6	Database	2019
Aggregate	ecoinvent 3.6	Database	2019
Binder	ecoinvent 3.6	Database	2019
Filler	ecoinvent 3.6	Database	2019
Packaging	ecoinvent 3.6	Database	2019
Additives	LCA.no	Database	2021
Cement	Supplier	EPD	2021

### Technical data:

weber outdoor repair is produced according to the requirements of R2 class according to SFS-EN 1504-3:2006 (Product intended for non-structural repair of concrete as polymermodified cementitious mortar for concrete repair according principles 3.1 and 3.3).

Material consumption: approx. 2 kg/m<sup>2</sup>/mm  
 Recommended layer thickness: 3-20 mm for plaster over and up to 50 mm for filling holes.  
 Recommended water content: approx. 0.8 l/5 kg  
 Mixed volume: approx. 3.4 l/5 kg

More information: [www.fi.weber/betonit/betonin-korjauslaasti/weber-outdoor-repair-korjaus-ja-tasoituslaasti](http://www.fi.weber/betonit/betonin-korjauslaasti/weber-outdoor-repair-korjaus-ja-tasoituslaasti)

### Market:

Nordic and Baltic countries

### Reference service life, product

The reference service life of the product is similar to the service life of the building.

60 years

### Allocation:

The allocation is made in accordance with the provisions of EN 15804. Incoming energy and water and waste production in-house is allocated equally among all products through mass allocation. Effects of primary production of recycled materials is allocated to the main product in which the material was used. The recycling process and transportation of the material is allocated to this analysis.

## System boundaries (X=included, MND=module not declared, MNR=module not relevant)

Product stage			Construction installation stage		User stage							End of life stage				Beyond the system boundaries
Raw materials	Transport	Manufacturing	Transport	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	MNR	MNR	MNR	MNR	MNR	MNR	MNR	X	X	X	X	X


### System boundary:

The analysis includes modules A1-A5, C1-C4, D (cradle-to-gate with options). Processes from raw materials extraction to product transportation to the building site, assembly, as well as end of life stage and phases beyond the system boundary are included.

The basic production process comprises of mixing raw materials together. Ready mixed product is then packed into small bags. At assembly phase, water is added according to the instructions and it is mixed.

When building is demolished at the end-of-life, the structure with mortar integrated into concrete slab are crushed. 90% of crushed concrete is recycled and used to replace natural gravel in soil construction, remaining 10% being disposed to landfill.

Packaging of most representative product package is selected for the study. System boundaries are illustrated in the picture below.



### Additional technical information:

The LCA calculation has been made taking into account the fact that during the manufacturing process 100% renewable electricity is used. This 100% renewable electricity bought is evidenced by Guarantee of Origin certificates (GOs) from LOS, valid for the study year (2021).

Unused product powder is classified as hazardous waste. Product hardens after adding water in 5 to 6 hours and can then be disposed as mixed construction waste.

## LCA: Scenarios and additional technical information

The following information describe the scenarios in the different modules of the EPD.

The results of stage A4 (transportation of product) in the table of this EPD refer to transportation in Finland (average distance 2021). This product may also be delivered to the countries in the table "Additional A4 information". In order to adapt the impact of transportation to these countries, A4 figures from this EPD shall be multiplied by the multiplication factors below. At installation stage, it is assumed that mixing is done by electric mixer. Electricity mix used is that of Finland. Material loss is considered to be 0. At end of life stage, it is assumed that all demolition waste is collected and 90% of crushed concrete is recycled and 10% is disposed into landfill. Transport distance to processing is estimated to be 30 km.

Transport from production place to user (A4)	Capacity Utilization	Distance (km)	Fuel/Energy Consumption	Unit	Value (L/t)
Truck, over 32 tonnes, EURO 5 (km)	53,3 %	206	0,023	l/tkm	4,74

Additional A4 information	Unit/Range	Value			
Tullinge, Sweden (truck / ferry 384 km)	Multiplication factor GWP/A4	2,20			
Lillestrøm, Norway (truck / ferry 871 km)	Multiplication factor GWP/A4	4,57			
Karlslunde, Denmark (truck / ferry 1033 km)	Multiplication factor GWP/A4	5,35			
Tallinn, Estonia (truck / ferry 271 km)	Multiplication factor GWP/A4	1,41			
Riga, Latvia (truck / ferry 579 km)	Multiplication factor GWP/A4	2,90			
Kaunas, Lithuania (truck / ferry 848 km)	Multiplication factor GWP/A4	4,21			

Assembly (A5)	Unit	Value			
Waste, cardboard and paper packaging, to average treatment (kg)	kg	0,02			
Waste, plastic packaging, mixture, to average treatment (kg)	kg	0,01			
Waste, wood packaging, average treatment (kg)	kg	0,04			
Water, tap water (L)	kg/DU	0,16			
Electricity, Finland (kWh)	kWh/DU	0,00			

C1 Deconstruction demolition	Unit	Value			
Demolition of building per kg product (kg)	kg/DU	1,00			

Transport to waste processing (C2)	Capacity Utilization	Distance (km)	Fuel/Energy Consumption	Unit	Value (L/t)
Truck, over 32 tonnes, EURO 5 (km)	53,3 %	30	0,023	l/tkm	0,69

<b>C3 Waste Processing</b>	<b>Unit</b>	<b>Value</b>			
Waste treatment of product after demolition (kg)	kg	0,90			









<b>C4 Disposal</b>	<b>Unit</b>	<b>Value</b>			
Disposal of product in landfill (kg)	kg	0,10			

<b>D Reuse-Recovery Recycling potential</b>	<b>Unit</b>	<b>Value</b>			
Substitution of primary aggregates with crushed recycled inert products (kg)	kg	0,89			

## LCA: Results

The LCA results are presented below for the declared unit defined on page 2 of the EPD document.

Environmental impact										
Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D	
 GWP-total	kg CO <sub>2</sub> -eq.	4,22E-01	1,87E-02	2,69E-03	4,00E-03	2,73E-03	6,35E-04	8,22E-04	-2,08E-03	
GWP-fossil	kg CO <sub>2</sub> -eq.	4,32E-01	1,87E-02	2,68E-03	4,00E-03	2,73E-03	6,27E-04	8,20E-04	-2,04E-03	
GWP-biogenic	kg CO <sub>2</sub> -eq.	-1,27E-02	7,68E-06	8,44E-06	7,50E-07	1,12E-06	5,41E-06	9,58E-07	-4,07E-05	
GWP-luluc	kg CO <sub>2</sub> -eq.	1,99E-03	5,47E-06	6,31E-06	3,15E-07	7,96E-07	8,67E-07	2,02E-07	-1,38E-06	
 ODP	kg CFC11-eq.	2,05E-08	4,33E-09	3,51E-10	8,64E-10	6,30E-10	1,25E-10	3,08E-10	-3,73E-10	
 AP	mol H <sup>+</sup> -eq.	1,71E-03	7,87E-05	1,31E-05	4,19E-05	1,15E-05	5,07E-06	7,30E-06	-1,84E-05	
 EP-FreshWater <sup>3</sup>	kg P-eq.	3,86E-05	1,43E-07	4,38E-08	1,46E-08	2,08E-08	3,96E-08	9,30E-09	-5,42E-08	
EP-Marine	kg N-eq.	2,82E-04	2,37E-05	5,24E-06	1,85E-05	3,45E-06	1,49E-06	2,71E-06	-6,37E-06	
EP-Terrestrial	mol N-eq.	3,81E-03	2,62E-04	5,09E-05	2,00E-04	3,81E-05	1,71E-05	2,99E-05	-7,48E-05	
 POCP	kg NMVOC-eq.	1,30E-03	8,41E-05	1,35E-05	5,57E-05	1,23E-05	4,58E-06	8,57E-06	-1,98E-05	
 ADPE <sup>1</sup>	kg Sb-eq.	3,39E-06	3,20E-07	3,39E-08	6,14E-09	4,66E-08	7,95E-09	7,39E-09	-1,81E-07	
 ADPF <sup>1</sup>	MJ	5,13E+00	2,91E-01	3,64E-02	5,51E-02	4,24E-02	1,95E-02	2,26E-02	-3,45E-02	
 WDP <sup>1</sup>	m <sup>3</sup>	7,98E+00	2,23E-01	9,41E-01	1,17E-02	3,25E-02	2,15E+00	1,39E-01	-1,62E+00	







GWP total Global Warming Potential total; GWP fossil Global Warming Potential fossil fuels ; GWP biogenic Global Warming Potential biogenic; GWP luluc Global W Potential land use change; ODP Ozone Depletion; AP Acidification; EP freshwater Eutrophication aquatic freshwater; EP marine Eutrophication aquatic marine; EP terrestrial Eutrophication terrestrial ;POCP Photochemical zone formation; ADPE Abiotic Depletion Potential minerals and metals; ADPF Abiotic Depletion Potential fossil fuels; WDP Water Depletion Potential

"Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009"

\*INA Indicator Not Assessed

- The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
- Eutrophication aquatic freshwater shall be in kg P-eq., there is a typo in EN 15804:2012+A2:2019 regarding this unit. Eutrophication calculated as PO<sub>4</sub>-eq is presented on page 11

## Additional environmental impact indicators

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
 PM	Disease incidence	1,48E-08	1,65E-09	1,51E-10	5,07E-09	2,40E-10	8,20E-11	1,55E-10	-3,90E-10
 IRP <sup>2</sup>	kgBq U235-eq.	5,33E+00	1,27E-03	4,77E-04	2,40E-04	1,85E-04	3,27E-04	1,03E-04	-3,17E-04
 ETP-fw <sup>1</sup>	CTUe	5,09E+00	2,13E-01	3,47E-02	3,01E-02	3,10E-02	1,38E-02	1,23E-02	-3,55E-02
 HTP-c <sup>1</sup>	CTUh	2,97E-10	0,00E+00	1,00E-12	1,00E-12	0,00E+00	0,00E+00	0,00E+00	-1,00E-12
 HTP-nc <sup>1</sup>	CTUh	6,53E-09	2,06E-10	9,20E-11	2,80E-11	3,00E-11	1,20E-11	8,00E-12	-4,30E-11
 SQP <sup>1</sup>	Pt	5,84E+00	3,34E-01	2,52E-02	6,69E-03	4,86E-02	1,10E-02	8,69E-02	7,83E-02

PM Particulate Matter emissions; IRP Ionizing radiation – human health; ETP-fw Eco toxicity – freshwater; HTP-c Human toxicity – cancer effects; HTP-nc Human toxicity – non cancer effects; SQP Soil Quality (dimensionless)

"Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009"

\*INA Indicator Not Assessed

1. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is limited experienced with the indicator
2. This impact category deals mainly with the eventual impact of low dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure nor due to radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, from radon and from some construction materials is also not measured by this indicator.



## Resource use




Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
 PERE	MJ	5,95E-01	3,67E-03	5,50E-03	3,00E-04	5,34E-04	1,00E-02	8,08E-04	-8,08E-03
 PERM	MJ	8,32E-01	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
 PERT	MJ	1,43E+00	3,67E-03	5,50E-03	3,00E-04	5,34E-04	1,00E-02	8,08E-04	-8,08E-03
 PENRE	MJ	3,51E+00	2,91E-01	3,69E-02	5,51E-02	4,24E-02	1,95E-02	2,26E-02	-3,64E-02
 PENRM	MJ	1,14E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
 PENRT	MJ	4,66E+00	2,91E-01	3,69E-02	5,51E-02	4,24E-02	1,95E-02	2,26E-02	-3,64E-02
 SM	kg	1,06E-02	0,00E+00	1,46E-05	2,70E-05	0,00E+00	1,67E-05	9,79E-06	-6,98E-05
 RSF	MJ	5,06E-02	1,28E-04	7,99E-05	7,33E-06	1,87E-05	2,03E-04	1,68E-05	-1,65E-04
 NRSF	MJ	6,64E-02	4,30E-04	2,91E-04	-1,10E-04	6,26E-05	-1,26E-05	3,62E-05	-1,70E-04
 FW	m <sup>3</sup>	2,92E-03	3,32E-05	1,89E-04	2,83E-06	4,83E-06	3,33E-05	2,78E-05	-1,27E-03

PERE Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM Use of renewable primary energy resources used as raw materials; PERT Total use of renewable primary energy resources; PENRE Use of non renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM Use of non renewable primary energy resources used as raw materials; PENRT Total use of non renewable primary energy resources; SM Use of secondary materials; RSF Use of renewable secondary fuels; NRSF Use of non renewable secondary fuels; FW Use of net fresh water

\*Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009"

\*INA Indicator Not Assessed

## End of life - Waste






Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
 HWD	kg	4,66E-03	1,59E-05	4,04E-04	1,62E-06	2,32E-06	1,94E-06	1,59E-06	-8,32E-06
 NHWD	kg	8,11E-02	2,53E-02	5,76E-03	6,52E-05	3,69E-03	6,14E-05	1,00E-01	-2,52E-04
 RWD	kg	8,86E-06	1,99E-06	3,01E-07	3,82E-07	2,90E-07	2,06E-07	1,47E-07	-2,74E-07

HWD Hazardous waste disposed; NHWD Non-hazardous waste disposed; RWD Radioactive waste disposed;

\*Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009"

\*INA Indicator Not Assessed

## End of life - Output flow

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
 CRU	kg	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
 MFR	kg	3,03E-03	0,00E+00	2,36E-02	2,66E-05	0,00E+00	8,82E-01	8,92E-06	-1,63E-06
 MER	kg	2,94E-04	0,00E+00	7,05E-07	8,23E-08	0,00E+00	2,03E-06	1,68E-07	-6,11E-05
 EEE	MJ	7,28E-03	0,00E+00	2,69E-02	2,82E-07	0,00E+00	3,48E-06	1,39E-05	-1,48E-05
 EET	MJ	1,18E-01	0,00E+00	4,07E-01	4,27E-06	0,00E+00	5,27E-05	2,10E-04	-2,23E-04

CRU Components for re-use; MFR Materials for recycling; MER Materials for energy recovery; EEE Exported electrical energy; EET Exported energy Thermal

\*Reading example: 9,0 E-03 = 9,0\*10<sup>-3</sup> = 0,009"

\*INA Indicator Not Assessed

## Biogenic Carbon Content

Indicator	Unit	At the factory gate
Biogenic carbon content in product	kg C	0,00E+00
Biogenic carbon content in accompanying packaging	kg C	2,46E-02

Note: 1 kg biogenic carbon is equivalent to 44/12 kg CO<sub>2</sub>

## Additional Norwegian requirements

### Greenhouse gas emissions from the use of electricity in the manufacturing phase

National production mix from import, low voltage (production of transmission lines, in addition to direct emissions and losses in grid) of applied electricity for the manufacturing process (A3).

Electricity mix	Data source	Amount	Unit
Renewable electricity Saint-Gobain, based on 100% hydro power, with Guarantee of Origin from LOS 2021 (kWh)	ecoinvent 3.6	4,26	g CO <sub>2</sub> -eq/kWh

### Dangerous substances

The product contains no substances given by the REACH Candidate list or the Norwegian priority list. The product is classified as hazardous waste (Avfallsforskriften, Annex III), see table.

Name	CASNo	Amount
Portland cement	65997-15-1	25-50%

### Indoor environment

## Additional Environmental Information

### Environmental impact indicators EN 15804+A1 and NPCR Part A v2.0

Parameter	Unit	A1-A3	A4	A5	C1	C2	C3	C4	D
GWP	kg CO <sub>2</sub> -eq.	4,61E-01	1,85E-02	2,70E-03	3,95E-03	2,70E-03	6,18E-04	8,04E-04	-2,18E-03
ODP	kg CFC11-eq.	1,87E-08	3,50E-09	3,38E-10	6,86E-10	5,10E-10	1,52E-10	2,50E-10	-3,37E-10
POCP	kg C <sub>2</sub> H <sub>4</sub> -eq.	1,03E-04	2,42E-06	4,57E-07	6,09E-07	3,52E-07	1,37E-07	1,89E-07	-4,55E-07
AP	kg SO <sub>2</sub> -eq.	1,35E-03	3,74E-05	8,38E-06	5,84E-06	5,44E-06	2,32E-06	2,23E-06	-5,34E-06
EP	kg PO <sub>4</sub> <sup>3-</sup> -eq.	2,35E-04	4,08E-06	2,20E-06	6,50E-07	5,94E-07	3,07E-07	2,64E-07	-6,26E-07
ADPM	kg Sb-eq.	1,03E-05	3,20E-07	3,39E-08	6,14E-09	4,66E-08	7,95E-09	7,39E-09	-1,81E-07
ADPE	MJ	5,34E+00	2,86E-01	3,63E-02	5,47E-02	4,16E-02	7,47E-03	2,16E-02	-3,45E-02
GWPIOBC	kg CO <sub>2</sub> -eq.	2,98E-01	1,87E-02	7,59E-04	5,37E+00	2,73E-03	0,00E+00	0,00E+00	-2,18E-03
GWIBC	kg CO <sub>2</sub> -eq.	3,07E-05	5,56E-07	2,45E-08	0,00E+00	8,09E-08	0,00E+00	0,00E+00	0,00E+00

## Bibliography

ISO 14025:2010 Environmental labels and declarations - Type III environmental declarations - Principles and procedures.  
 ISO 14044:2006 Environmental management - Life cycle assessment - Requirements and guidelines.  
 EN 15804:2012+A2:2019 Environmental product declaration - Core rules for the product category of construction products.  
 ISO 21930:2017 Sustainability in buildings and civil engineering works - Core rules for environmental product declarations of construction products.  
 ecoinvent v3, Allocation, cut-off by classification, Swiss Centre of Life Cycle Inventories.  
 Iversen et al., (2021) eEPD v2021.09 Background information for EPD generator tool system verification, LCA.no Report number: 07.21  
 Iversen et al., (2019) EPD generator for Saint-Gobain Weber and Scanspac - Background information and LCA data, LCA.no report number 05.18  
 Iversen et al., (2020) EPD generator for Saint-Gobain Weber Nordics and Scanspac Background information for customer application,

 <b>epd-norge</b> <small>The Norwegian EPD Foundation</small>	<b>Program operator and publisher</b> The Norwegian EPD Foundation Post Box 5250 Majorstuen, 0303 Oslo, Norway	Phone: +47 23 08 80 00 e-mail: post@epd-norge.no web: www.epd-norge.no
	<b>Owner of the declaration:</b> Saint-Gobain Finland Oy P.O. Box 70,FI-00381 Helsinki	Phone: +358400289933 e-mail: anne.kaiser@saint-gobain.com web: www.saint-gobain.fi
	<b>Author of the Life Cycle Assessment</b> LCA.no AS Dokka 6B,1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no
	<b>Developer of EPD generator</b> LCA.no AS Dokka 1C,1671 Kråkerøy	Phone: +47 916 50 916 e-mail: post@lca.no web: www.lca.no

# EPD for the best environmental decision

---



**Global  
Program  
Operator**

The Norwegian EPD Foundation

[www.epd-norge.no](http://www.epd-norge.no)

 **epd-norge**