

U-Clamp FUBD

The easy handling pipe and cable clamp for direct attachment of lines to FUS mounting rails



Supply lines fixed to FUS channel

2a

Applications

- Fast installation of metal and plastic pipes, flexible plastic pipes or cables without sound insulation requirements directly to FUS installation channels
- Fits to FUS channels FUS 21, FUS 41, FUS 62, FUS 21D, FUS 41D, FUS 62D


Advantages/benefits

- The FUBD without soundproofing is ideal for use in industrial applications, for example, for fixing lightweight flexible supply lines in the immediate area of production machines.
- Locking screw with hexagonal and slot drive.
- Quick adaptation to the desired outside pipe diameter by fastening the pressure pan.
- No loss of parts due to preassembled parts.
- Time- and cost-saving installation without the need of accessories like threaded rods or sliding nuts.


Properties

- Material U-Strap: steel S235JRC (Werkstoff-Nr.: 1.0122) acc. to EN 10025
- Zinc plating U-Strap: hot-dip galvanised min. 35 µm acc. to DIN EN ISO 1461
- Material Pressure pan: steel DX51D acc. to DIN EN 10346
- Zinc plating Pressure pan: electro zinc plated, min. 5 µm acc. to DIN EN ISO 4042
- Material Locking screw: steel 4.6 acc. to EN 20898-1
- Locking screw: with hexagonal SW10 and slot head

Installation FUBD



Technical data



FUDB

Item	Item No.	Clamping range	Height	Width x thickness clamp band	Locking screw	Sales unit
		D [mm]	H [mm]	b x s [mm]		
FUBD 40	539564 ¹⁾	36 - 40	71	25 x 1,75	M 6 x 24	100
FUBD 48	558148	44 - 48	85	25 x 2,0	M 8 x 30	50
FUBD 52	539566	48 - 52	90	25 x 2,0	M 8 x 30	50
FUBD 60	539567 ¹⁾	56 - 60	98	30 x 2,25	M 8 x 30	50
FUBD 76	539568 ¹⁾	70 - 76	113	30 x 2,75	M 8 x 30	25
FUBD 94	539569 ¹⁾	88 - 94	141	30 x 2,75	M 8 x 40	20
FUBD 100	539570 ¹⁾	94 - 100	147	30 x 2,75	M 8 x 40	10

1) Delivery time on request.