Technical Data Sheet

CRC LABEL OFF SUPER

1. General Description

Eliminates adhesive labels and rests of sticky substances and glues from most surfaces in 2-3 minutes. It does not attack most of the plastics (test on plastic substrates prior to use). It is recommended to scratch the surface if the label is plasticized.

Adapted for use in every industry, including food processing (NSF certified).

2.Characteristics

- FPS Label Off Super is a solvent mixture specially designed for the removal of self-adhesive paper labels. It penetrates the label paper and dissolves the underlying adhesive. Due to its high dissolving power of acrylate-based adhesives – the mostly used type of adhesives for adhering labels – labels can be removed easily in one go after only 2 minutes.
- The aerosol is equipped with an extension tube, allowing precise spot application on small labels.
- NSF registration : K3, registration number: 139426

3.Aplications

PAPER LABELS

- Address and production stickers from drums, cans and cardboard boxes.
- Identification labels on shelves, drawers or warehouse containers.
- Labels on spare parts and tools.
- Price indicating labels on glass, china, ceramics, furniture.
- Laboratory labels on flasks and bottles.
- Adhesive and label residues on labeling machines.

PLASTIFIED LABELS

- Label Off Super eliminates plastified labels. Before using Label off super, it is advised to scratch the label surface to allow label off Super penetration.

STICKY SUBSTANCES

- FPS Label Off Super dissolves many sticky substances making it ideal for removing tree resin, chewing gum and tar. Also adhesive remains following the removal of a label, can be dissolved and wiped off.

4.Instructions

- Soak the label with FPS Label Off Super. Most labels can be pulled off in one go after 2 minutes. In difficult cases waiting time can be extended to 15 minutes. If adhesive is still stuck to the substance after the label has been removed, spray FPS Label Off Super on a cloth and wipe off the adhesive residue.
- The aerosol can uses carbon dioxide as propellant and is filled for ± 97% with active product. The extension tube allows precise dosing when used on small labels or difficult to reach areas.
- If FPS Label Off Super is used on plastics or varnished surfaces it is essential to carry out a resistance test before use.

Technical Data Sheet

CRC LABEL OFF SUPER

- FPS Label Off Super is a powerful degreasing agent. If it is to be used in large quantities, appropriate protective gloves should be worn. Remove all close-by ignition sources.

5. TYPICAL PRODUCT DATA (without propellant)

Appearance:	Light amber
Smell:	Fresh fruit
Density at 20°C:	0.753 g/cm³
Inflammation point:	< 0 °C
VOC (g/L):	720
Water solubility:	Insoluble
Auto-ignition:	> 200 °C
Evaporation rate (ether = 1)	94
Compatible with most plastics *ac. to Bellcore stress cracking method*	Polycarbonate (PC), Polyurethane (PUR and PU), High Density Polyethylene (HDPE), Polyvinyl chloride (PVC), Acrylonitrile butadiene styrene (ABS) and Polysulfone (PSU).

6.PACKAGING

Aerosol: 12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.

Date: 03/11/2020