

ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A2

Owner of the Declaration	Knauf AQUAPANEL GmbH & Co. KG
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-USG-20210120-IBA2-EN
Issue date	08.06.2021
Valid to	07.06.2026

AQUAPANEL® Cement Board Rooftop 12,5 mm
Knauf AQUAPANEL GmbH & Co. KG

www.ibu-epd.com | <https://epd-online.com>



ECO PLATFORM

EPD
VERIFIED



1. General Information

Knauf AQUAPANEL GmbH & Co. KG

Programme holder

IBU – Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

Declaration number

EPD-USG-20210120-IBA2-EN

This declaration is based on the product category rules:

Fibre cement / Fibre concrete, 01.08.2021
(PCR checked and approved by the SVR)

Issue date

08.06.2021

Valid to

07.06.2026

Dipl.-Ing. Hans Peters
(Chairman of Institut Bauen und Umwelt e.V.)

Florian Pronold
(Managing Director Institut Bauen und Umwelt e.V.)

AQUAPANEL® Cement Board Rooftop 12,5 mm

Owner of the declaration

Knauf AQUAPANEL GmbH & Co. KG
Zur Helle 11
58638 Iserlohn
Germany

Declared product / declared unit

1 m² AQUAPANEL® Cement Board Rooftop with a thickness of 12,5 mm

Scope:

This environmental product declaration refers to AQUAPANEL® Cement Board Rooftop produced in Iserlohn, Germany.
The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A2. In the following, the standard will be simplified as *EN 15804*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally

Prof. Dr. Birgit Grahl,
(Independent verifier)

2. Product

2.1 Product description/Product definition

Cement-bonded, mineral building board with two-dimensional grid structures of glass layers arranged in longitudinal and transverse direction for use in flat roof construction. The AQUAPANEL® Cement Board Rooftop is certified according to EN 12467 and is therefore a product according to CPR with hEN. Regulation (EU) No. 305/2011 (CPR) applies to the placing of the product on the market in the EU/EFTA (with the exception of Switzerland).

The product requires a declaration of performance according to the CPR taking into account *DIN EN 12467:2018-12*, Fibre-cement boards - Product specification and test methods and the CE marking.

2.2 Application

AQUAPANEL® Cement Board Rooftop is a component of flat roof systems, especially commercial or industrial buildings. It improves the performance of the flat roof in several ways:

1. as a cover board between the insulation and the roof sealing:
 - protects the underlying thermal insulation
 - reduces the stress on the sealing membranes
 - adds structural strength to the entire roof system
 - provides a solid substrate for accessible roofs and roofs with ballast
2. as a support plate fixed directly to the profiled sheet, it serves as:
 - support for the vapour barrier
 - A work platform for the roofers

2.3 Technical Data

Technical Data

Name	Value	Unit
Thermal conductivity nach ISO 10456	0.35	W/(mK)
Water vapour diffusion resistance factor nach ISO 12572	66	-
Swelling (air-dry to water-saturated) nach EN 318	0.23	mm/m
Gross density nach EN 12467	1150	kg/m ³
Tensile strength nach EN 319	0.65	N/mm ²
Flexural strength nach EN 12467	>7	N/mm ²
Coefficient of thermal expansion	7	10 ⁻⁶ K ⁻¹
pH-value	12	

AQUAPANEL® Cement Board Rooftop (product according to CPR with hEN)

- Performance values of the product according to the declaration of performance *No KAGR_013* in relation to its essential characteristics in accordance with *DIN EN 12467:2018-12*, Fibre cement boards - Product specification and test methods.
- Voluntary information for the product: *Technical Data Sheet 04/19* (www.aquapanel.com).

2.4 Delivery status

The building panel is marketed in the dimensions 900 x 12000. The layer thickness is 12,5 mm.

2.5 Base materials/Ancillary materials

AQUAPANEL® Cement Board Rooftop

Name	Value	Unit
Limestone	35-45	Mass-%
Cement	15-30	Mass-%
Recyclate/Fuller	5-15	Mass-%
Perlite	5-10	Mass-%
Fiberglass scrim	<2	Mass-%
Hydrophobic agent	<1	Mass-%

The product contains substances on the ECHA Candidate List of Substances of Very High Concern (SVHC) (date 04.05.2021) above 0.1% by mass: no.

The product contains other CMR substances of category 1A or 1B, which are not on the candidate list, above 0.1% by mass in at least one sub-product: no.

Biocidal products have been added to the present construction product or it has been treated with biocidal products (it is therefore a treated product in the sense of the Biocidal Products Regulation (EU) No 528/2012): no.

2.6 Manufacture

The aggregates and binders are stored in silos outside the production hall. The raw materials for the slab core are dosed according to the recipe via belt weighers and differential feeders and transported to the weighing container via a central conveyor. The binder for the production of the top layer is transported directly via a screw conveyor to the production unit of the "slurry" (cement mixture). The glass fabrics required for production are stored in the basement of the production hall. The dry mixture in the weighing container is emptied into the compulsory mixer below and water is added according to the recipe. The core mixture is mixed homogeneously and soil-moist and conveyed to the moulding station by belt conveyor. At the same time, the slurry for the top layer is homogeneously premixed and conveyed to the moulding station via screw pumps and hoses. In the moulding station, the 3-layer element is produced continuously by extrusion and cut to the appropriate length in the subsequent cutter. The cut boards are hardened in the shelf storage.

The production process is certified according to *ISO 9001*.

2.7 Environment and health during manufacturing

According to Regulation (EC) No 1907/2006, cement and cement-containing mixtures may not be used or placed on the market if the content of soluble chromium(VI) in the dry mass of the cement after hydration is more than 2 mg/kg (0.0002 %). Only low-chromate cements are used in the production process. Apart from the legal requirements, no further special measures are necessary.

Further environmental protection measures in the production process:

a) Minimization of waste: Both manufactured slabs that do not meet the requirements as well as any edge trimmings produced during the final processing of the slabs are returned to the manufacturing process as raw material.

b) Optimization of energy consumption: A high degree of automation in production enables optimal process parameters to be maintained, thus minimizing unnecessary energy consumption. This applies in particular to the expansion of the perlite raw material.

2.8 Product processing/Installation

Knauf Aquapanel GmbH & Co. KG provides technical data sheets for the cement-bonded building boards. This information is available in printed form as well as at www.aquapanel.com.

The boards can be mechanically fastened or glued. The processing can be carried out with commercially available tools.

2.9 Packaging

The cement-bonded building board with glass grid reinforcement is delivered on a returnable Euro pallet secured with metal strapping.

2.10 Condition of use

No changes in material composition occur during service life.

2.11 Environment and health during use

During the service life, there are no environmental and health effects. The results of the Volatile Organic Compound (VOC) analysis all remained below the respective detection limit (see chapter 7.3). There is no release of chromium (VI)-containing substances.

There are no hazards to water, air or soil. In use, the ingredients of the products are firmly bound. Dust emissions are not possible.

2.12 Reference service life

From experience, a service life of approximately 50 years can be achieved when used as intended.

2.13 Extraordinary effects

Fire

Non-combustible building material of building material class A1 acc to *EN 13501-1*.

Fire protection

Name	Value
Building material class acc to EN 13501-1	A1

Water

Chromium elution is to be expected in case of unforeseen effects of water in non-relevant quantities (see chapter 7.4). Further elutions of other heavy metals are not expected.

Mechanical destruction

No sharp break edges are created upon mechanical destruction.

2.14 Re-use phase

Once used, the products are practically un-reusable, but are suitable for recycling as filling material if fully separated.

2.15 Disposal

According to AVV AQUAPANEL® Cement Board Rooftop, the waste code 170904 mixed construction and demolition waste other than those falling under 170901, 170902 and 170903 is recommended.

2.16 Further information

For further information visit: www.aquapanel.com.

3. LCA: Calculation rules

3.1 Declared Unit

The declared unit of the study is 1 m² AQUAPANEL® Cement Board Rooftop with a thickness of 12,5 mm.

Declared Unit

Name	Value	Unit
Declared Unit	1	m ²
Gross density	1150	kg/m ³
Grammage	16.5	kg/m ²
conversion factor [Mass/Declared Unit]	16.5	-

* The density according to *EN 12467* is the density after complete drying. Therefore, the data in the above table on surface weight at delivery and the bulk density do not correlate,

3.2 System boundary

Within the scope of the conducted LCA, the production or provision and transport of the preliminary products/raw materials as well as the production of the final product (A1-A3) are taken into account. Furthermore, the end-of-life phase (C1-C4) is considered using technical scenarios.

The data of the cement board production was determined at the production site. The recipe and the raw materials used, the electrical energy used and all direct production waste were taken into account in the balancing. Within phase A2, all specific transport routes of the educts were stored.

3.3 Estimates and assumptions

With the exception of the technical scenarios (Chapter 4), no estimates or assumptions were made in the study.

3.4 Cut-off criteria

In the LCA, the cut-off criteria for a release agent was applied in the area of production.

The material corresponds to <0.08 % of the mass input for the declared unit.

The use of the wooden pallets used for storage and transport is also cut off within the consideration. Due to the frequent reuse, the proportion to be taken into account for a declared unit is very low and does not have a significant share in the result. Furthermore, the section of metal strapping occurs during pallet loading. In relation to a declared unit, the share is <0.1% of the total mass input.

An application of the cut-off criteria beyond the above-mentioned processes was not necessary.

3.5 Background data

The background data used was completely obtained from the *GaBi-ts* software or can be traced back to it. *GaBi* version 10.0.0.71 (Content Version 2020.2, Service Pack 40) was used to calculate the LCA.

3.6 Data quality

All background data records relevant for the calculation were provided by the declaration holder and processed with the database of the accounting software *GaBi ts*. The manufacturer-specific data used is from 2019. All material and energy flows were recorded in full and were taken into account in the processes described in chapter 3.4.

3.7 Period under review

The review period for the data collection is 2019.

3.8 Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's

3.9 Allocation

During the production of cement-bound boards at the Iserlohn site, waste cuttings are produced, 100 % of which are returned to the production cycle. The offcuts are credited as a benefit, used input material was considered burdensome to the system.

The data for A3 at the site was recorded in relation to the actual output of the product under consideration.

3.10 Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to *EN 15804* and the building context, respectively the product-specific characteristics of performance, are taken into account. Die Hintergrunddaten wurden der *GaBi ts-Software* (Content Version 2020.2, Service Pack 40) entnommen.

4. LCA: Scenarios and additional technical information

Characteristic product properties of biogenic carbon

AQUAPANEL® Cement Board Rooftop is almost exclusively composed of inorganic materials. The proportion of biogenic carbon in the total mass of the product is less than 1 %.

Scenario information

Ende of Life (C1-C4)

Module C1 - Deconstruction and demolition

The deconstruction is carried out mechanically and unspecifically with an excavator (100 kW), related to the product under consideration. The scenario considers the impacts caused by the operation of the excavator (incl. diesel), depending on the mass to be moved (declared unit).

Module C2 – Transport for waste management

The transport of the deconstructed material is assumed to take place with one truck as a German fleet average to an inert

material landfill as mixed construction waste. The transport distance is assumed to be 100 km.

Module C3 - Waste management for reuse, recovery and/or recycling.

The product under consideration can be used as bulk and fill material if separated by type. In practice, the deconstructed roof structure is not separated by type, so that a pure inert material landfill is assumed in this scenario.

Module C4 - Disposal

The product under consideration is disposed of as part of mixed construction waste in an inert landfill. No consideration is given to energy credits from possible landfill gas use, as the product consists almost exclusively of inorganic materials.

Module D - Reuse, recovery and/or recycling potentials

Due to the assumed landfilling of inert materials, a consideration of credits is not possible.

5. LCA: Results

The results of the life cycle assessment of the AQUAPANEL® Cement Board Rooftop for the life cycle phases considered (A1-A3) are presented below. The characterisation factors of EK-JRC specified by EN 15804 were used.

Important notice:

EP-freshwater:

This indicator was calculated as "kg P-eq." in accordance with the characterisation model (EUTREND model, Struijs et al., 2009b, as implemented in ReCiPe; <http://eplca.jrc.ec.europa.eu/LCDN/developerEF.xhtml>)).

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; ND = MODULE OR INDICATOR NOT DECLARED; MNR = MODULE NOT RELEVANT)

Product stage			Construction process stage		Use stage							End of life stage				Benefits and loads beyond the system boundaries
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	MND	MND	MND	MND	MNR	MNR	MNR	MND	MND	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A2: 1 m² AQUAPANEL® Cement Board Rooftop 12,5 mm

Parameter	Unit	A1	A2	A3	C1	C2	C3	C4	D
GWP-total	kg CO ₂ eq	4.94	0.05	0.29	0.01	0.1	0	0.23	0
GWP-fossil	kg CO ₂ eq	4.91	0.05	0.28	0.01	0.1	0	0.25	0
GWP-biogenic	kg CO ₂ eq	2.76E-02	1.87E-05	1.86E-03	-4.42E-04	4E-05	0	-1.97E-02	ND
GWP-luluc	kg CO ₂ eq	2.37E-03	1.95E-04	7.21E-04	4.18E-05	4.16E-04	0	7.14E-04	0
ODP	kg CFC11 eq	2.17E-14	1.14E-17	8.73E-15	2.45E-18	2.44E-17	0	9.91E-16	0
AP	mol H ⁺ eq	8.03E-03	2.69E-04	4.33E-04	4.92E-05	5.73E-04	0	1.78E-03	0
EP-freshwater	kg P eq	4.05E-06	1.01E-07	1.18E-06	2.17E-08	2.16E-07	0	4.26E-07	0
EP-marine	kg N eq	2.17E-03	1.32E-04	1.33E-04	2.32E-05	2.81E-04	0	4.58E-04	0
EP-terrestrial	mol N eq	2.36E-02	1.46E-03	1.39E-03	2.57E-04	3.12E-03	0	5.03E-03	0
POCP	kg NMVOC eq	6.66E-03	2.52E-04	3.33E-04	6.49E-05	5.37E-04	0	1.39E-03	0
ADPE	kg Sb eq	3.97E-07	3.87E-09	1.07E-07	8.29E-10	8.25E-09	0	2.23E-08	0
ADPF	MJ	36.19	0.62	3.54	0.133	1.32	0	3.25	0
WDP	m ³ world eq deprived	2.36E-01	2.01E-04	6.29E-03	4.3E-05	4.28E-04	0	2.6E-02	0

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources; WDP = Water (user) deprivation potential

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A2: 1 m² AQUAPANEL® Cement Board Rooftop 12,5 mm

Parameter	Unit	A1	A2	A3	C1	C2	C3	C4	D
PERE	MJ	5.24	0.04	2.04	0.01	0.08	0	0.43	0
PERM	MJ	0	0	0	0	0	0	0	0
PERT	MJ	5.24	0.04	2.04	0.01	0.08	0	0.43	0
PENRE	MJ	36.44	0.62	3.55	0.13	1.32	0	3.26	0
PENRM	MJ	0	0	0	0	0	0	0	0
PENRT	MJ	36.44	0.62	3.55	0.13	1.32	0	3.26	0
SM	kg	0.06	0	0	0	0	0	0	0
RSF	MJ	2.4	0	0	0	0	0	0	0
NRSF	MJ	4.57	0	0	0	0	0	0	0
FW	m ³	8.17E-03	3.23E-05	1.1E-03	6.91E-06	6.88E-05	0	8.2E-04	0

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA - WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A2: 1 m² AQUAPANEL® Cement Board Rooftop 12,5 mm

Parameter	Unit	A1	A2	A3	C1	C2	C3	C4	D
-----------	------	----	----	----	----	----	----	----	---

HWD	kg	1.49E-05	2.31E-08	2.38E-09	4.95E-09	4.93E-08	0	4.96E-08	0
NHWD	kg	7.31E-02	1.09E-04	2.73E-03	2.33E-05	2.32E-04	0	1.64E+01	0
RWD	kg	7.72E-04	6.52E-07	2.96E-04	1.4E-07	1.39E-06	0	3.7E-05	0
CRU	kg	0.4	0	0	0	0	0	0	0
MFR	kg	0	0	0	0	0	0	0	0
MER	kg	0	0	0	0	0	0	0	0
EEE	MJ	0	0	0	0	0	0	0	0
EET	MJ	0	0	0	0	0	0	0	0

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

**RESULTS OF THE LCA – additional impact categories according to EN 15804+A2-optional:
1 m² AQUAPANEL® Cement Board Rooftop 12,5 mm**

Parameter	Unit	A1	A2	A3	C1	C2	C3	C4	D
PM	Disease incidence	ND	ND	ND	ND	ND	ND	ND	ND
IR	kBq U235 eq	ND	ND	ND	ND	ND	ND	ND	ND
ETP-fw	CTUe	ND	ND	ND	ND	ND	ND	ND	ND
HTP-c	CTUh	ND	ND	ND	ND	ND	ND	ND	ND
HTP-nc	CTUh	ND	ND	ND	ND	ND	ND	ND	ND
SQP	SQP	ND	ND	ND	ND	ND	ND	ND	ND

PM = Potential incidence of disease due to PM emissions; IR = Potential Human exposure efficiency relative to U235; ETP-fw = Potential comparative Toxic Unit for ecosystems; HTP-c = Potential comparative Toxic Unit for humans (cancerogenic); HTP-nc = Potential comparative Toxic Unit for humans (not cancerogenic); SQP = Potential soil quality index

Disclaimer 1 – for the indicator “Potential Human exposure efficiency relative to U235”. This impact category deals mainly with the eventual impact of low-dose ionizing radiation on human health of the nuclear fuel cycle. It does not consider effects due to possible nuclear accidents, occupational exposure or radioactive waste disposal in underground facilities. Potential ionizing radiation from the soil, radon and from some construction materials is also not measured by this indicator.


Disclaimer 2 – for the indicators “abiotic depletion potential for non-fossil resources”, “abiotic depletion potential for fossil resources”, “water (user) deprivation potential, deprivation-weighted water consumption”, “potential comparative toxic unit for ecosystems”, “potential comparative toxic unit for humans – cancerogenic”, “Potential comparative toxic unit for humans - not cancerogenic”, “potential soil quality index”. The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high as there is limited experience with the indicator.

6. LCA: Interpretation

Based on the dominance analysis of the use of resources, it can be seen that the most climate-effective impact in the case of AQUAPANEL® cement panels is the raw material procurement/raw material processing (module A1). The mineral raw materials used for this are extracted as a non-regenerative resource and in some cases also thermally treated (glass melting, blowing process, cement burning). The CEM I cement used in the product contributes approx. 60% to the Global Warming Potential (GWP) due to the energy-intensive burning process, whereas the electrical energy of the production process only contributes approx. 5% to the GWP (see figure).

procurement and raw material processing (A1), especially that of mineral raw materials, also stand out as relevant processes in the overall system, whereas the transport of raw materials and production at the Iserlohn plant have only minor impacts. The effects of the production process in the plant itself are rather subordinate in terms of life cycle assessment and are largely due to the electrical energy demand. The processes used here are largely mixing and moulding processes that have hardly any environmental impact. The drying process in the curing warehouse takes place without the use of additional thermal energy due to exothermic processes.

In the other impact categories considered, raw material



7. Requisite evidence

7.1 Quality Management System DIN EN ISO 9001

The location in Iserlohn is certified according to DIN EN ISO 9001 (2018).

7.2. Radioactivity

The Activity Concentration Index (ACI) was determined to be 0.18. The tested product meets the official guideline value of ACI <1 as well as the test condition ACI <0.75 of the Institut für Baubiologie Rosenheim (IBR).

Institute for Building Biology Rosenheim GmbH *Test Report No. 3018-1018* of August 2020.

7.3. VOC emissions

The analysis of emissions of volatile organic compounds (VOC) starting from the AQUAPANEL® Cement Board Rooftop was carried out in August 2020 by the Institut für Baubiologie Rosenheim (IBR) and the results were documented in *test report no. 3018-1018*.

AgBB result overview (28 days [µg/m³])

Name	Value	Unit
TVOC (C6 - C16)	600	µg/m ³
Sum SVOC (C16 - C22)	<5	µg/m ³
R (dimensionless)	0.1	-
VOC without NIK	<5	µg/m ³
Carcinogenic Substances	<1	µg/m ³

AgBB result overview (3 days [µg/m³])

Name	Value	Unit
TVOC (C6 - C16)	3100	µg/m ³
Sum SVOC (C16 - C22)	<5	µg/m ³
R (dimensionless)	0.5	-
VOC without NIK	20	µg/m ³
Carcinogenic Substances	<1	µg/m ³

Based on the measurement results and the comparison of the specifications of the AgBB scheme and the DIBt approval principles, no contamination of the tested product by emissions of volatile organic compounds and in particular by formaldehyde is to be expected; therefore, the use of the cement boards in interior rooms of buildings is harmless in terms of VOC emissions.

7.4 Heavy metal concentrations

A determination of the heavy metal concentration both in the original substance and in the eluate was carried out by the Institut für Baubiologie Rosenheim (IBR) in August 2020. The determination in the original substance was carried out according to ISO 17294-2, in the eluate according to DIN 38414-4.

Institut für Baubiologie Rosenheim GmbH *Test Report No. 3018-1018*.

Heavy metal concentrations in the original substance

Name	Value	Unit
Arsenic	1,6	mg/kg
Lead	6,0	mg/kg
Cadmium	<0.3	mg/kg
Chrome	22,1	mg/kg
Copper	35.1	mg/kg
Nickel	9,61	mg/kg
Mercury	<0,05	mg/kg
Zinc	<30	mg/kg

Heavy metal concentration in the eluate

Name	Value	Unit
Arsenic	<0,01	mg/l
Lead	<0,005	mg/l
Cadmium	<0,0005	mg/l
Chrome	0,0231	mg/l
Copper	<0,005	mg/l
Nickel	<0,005	mg/l
Mercury	<0,0001	mg/l
Zinc	0,072	mg/l

8. References

AVV

Ordinance on the European list of waste (Abfallverzeichnis-Verordnung - AVV)10.12.2001.

DIN 38414-4

DIN 38414-4:1984-10, German standard methods for the examination of water, wastewater and sludge; sludge and sediments (group S); determination of leachability by water (p 4).

EN 318

DIN EN 318:2002-06, Holzwerkstoffe - Bestimmung von Maßänderungen in Verbindung mit Änderungen der relativen Luftfeuchte; Deutsche Fassung EN 318:2002

EN 12467

Fibre-cement flat sheets - Product specification and test methods; German version EN 2467:2012+A2:2018

EN 13501-1

DIN EN 13501-1:2010-01 Fire classification of construction products and building elements - Part 1: Classification using data from reaction to fire tests

EN 15804

EN 15804:2012+A2:2019, Sustainability of construction works - Environmental product declarations - Core rules for the product category of construction products

GaBi ts

GaBi ts: Software und Datenbank zur Ganzheitlichen Bilanzierung, Professional Datenbank, Content Version 2020.2, Service Pack 40.
LBP, Universität Stuttgart und thinkstep, 2021.
Dokumentation der Datensätze unter <http://www.gabisoftware.com/deutsch/my-gabi/gabi-documentation/>.

IBU 2016

IBU (2016):General EPD programme guidance of the Institut Bauen und Umwelt e.V.. (IBU). Version 1.1, Institut Bauen und Umwelt e.V., Berlin. I

ISO 7783

ISO 7783:2018-10,Paints and varnishes - Determination of water-vapour transmission properties - Cup method

ISO 9001

DIN EN ISO 9001:2008, Quality management systems - Requirements (ISO 9001:2008).

ISO 10456

DIN EN ISO 10456:2010-05,Building materials and products - Hygrothermal properties - Tabulated design values and procedures for determining declared and design thermal values

(ISO 10456:2007 + Cor.1:2009).

ISO 12572

ISO 12572:2016-08,Hygrothermal performance of building materials and products - Determination of water vapour transmission properties - Cup method

ISO 14025

DIN EN ISO 14025:2011-10, Environmental labels and declarations - Type III environmental declarations - Principles and procedures

ISO 17294-2

DIN EN ISO 17294-2:2017-01, Water quality - Application of inductively coupled plasma mass spectrometry (ICP-MS) - Part 2: Determination of selected elements including uranium isotopes

No. KAGR_013

Declaration of performance no. KAGR_013 according to EN 12467:2012 dated 11.10.2017

Product Category Rules for Building-Related

Products and Services – Part A:

Product Category Rules for Building-Related Products and Services. Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report, V1.7, 03/2018.

PCR: Fibre Cement/Fibre Concrete

Product category rules for building-related products and services. Part B: Environmental Product Declaration Requirements for Fibre Cement/Fibre Concrete.
Berlin: Institut Bauen und Umwelt e.V. (ed.), 11/2017.

Test report No. 3018 - 1018/

Institute for Building Biology Rosenheim, Test report Nr. 3018-1018 for AQUAPANEL® Cement Board Indoor/Outdoor, 16.10.2018.

Technical datasheet 04/19

Technical datasheet AQUAPANEL® Cement Board Rooftop 6 mm, April 2019.

Regulation (EC) No 1907/2006

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Council Regulation (EC) No 1488/2006.



establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (OJ L396, 30.12.2006, p. 1. Corrected version in OJ L 136, 29.5.2007, p. 3).

Regulation (EU) No 305/2011

Regulation (EU) No 305/2011 of the European Parliament and

of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC Text with EEA relevance.

Regulation (EU) No 528/2012

Regulation (EU) No 528/2012 of the European Parliament and of the Council of 22 May 2012 concerning the making available on the market and use of biocidal products.



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

WESSLING GmbH
Oststraße 7
48341 Altenberge
Germany

02505 - 89-0
info@wessling.de
www.wessling.de



Owner of the Declaration

Knauf AQUAPANEL GmbH & Co. KG
Zur Helle 11
58638 Iserlohn
Germany

0231 880855-0
aquapanel.info@knauf.com
www.aquapanel.com