

MILLER® H700 SERIES

The Next Generation of Premium Full Body Harnesses

The new and exciting Honeywell Miller® H700 Premium Series full body harnesses are the result of Honeywell's hyper focus on ergonomic science and safety innovation. The latest in the H-Series, Miller H700 boasts technologically-advanced safety, comfort and modular features.



1. COMFORT

The Miller H700 harness features high-tech, multi-layered new-generation 3D movement-focused waist padding for prolonged work positioning, enhanced shock absorption, breathability and venting – helping to keep workers drier and cooler on the job. The webbing surface is water repellent and durable. Moreover, our new Pivot Strap Adjuster enables a variety of leg configurations for customizable comfort.



2. SAFETY

Harnesses help keep workers at height safe, but spending long hours in a restrictive, non-ergonomic heavy harness can lead to muscular fatigue and may even cause serious medical problems. Plus, when a worker falls and is suspended, time is of the essence. With the Miller H700, what's usually a complicated four-step process in providing trauma relief is now one easy step with the One-Pull Trauma Relief Step accessory, which provides a quick auto-release. Suspension trauma is alleviated, blood flow continues to circulate and the worker is safer until help arrives.



3. INTUITIVENESS

Intuitive and easy-to-use adjustability options provide customizable comfort. The low-profile textile accessory interface straps enable workers to conveniently attach and move pouches around onto the Miller H700 harness. Tool tether anchor attachments and lanyard keepers are also positioned in several convenient locations and the integrated Personal Fall Limiter (PFL) connector enables the attachment of Self Retracting Lifelines (SRLs) and carabiners. The dorsal wear protector accessory helps protect the dorsal webbing from damage.



Miller H700 IC2



Miller H700 CC3



Miller H700 CC5



Miller H700 CC7

H700 WAIST PAD FEATURES AND BENEFITS

Breathability (water vapor resistance)	Low water vapor resistance (114 RET value for shoulder and leg padding material, and 72,4 for waist padding material) ensures higher breathability when compared with the next best alternative that has more than 1000 RET value for the padding material with imperforate EVA
Pressure distribution	Offers even pressure distribution around the waist, helping to ensure superior comfort in working position situations

IC2

Technical Specifications

Shoulder strap

Color: Dark grey
Width: 44 mm
Type of webbing: Waterproof webbing
Breaking Strength: >27 kN

Other strap

Color: Black
Width: 44 mm
Type of webbing: Waterproof webbing
Breaking Strength: >27 kN

Back Anchorage D-Ring

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >23 kN

Sternal Anchorage V-Ring

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >23 kN

Automatic Quick-Release Buckles

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >9 kN

Adjuster Buckles

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >18 kN

Weight (kg)

Net weight: 1.85
Breaking Strength: >15 kN

Temperature

Temperature: -30°C to +50°C

CC3

Technical Specifications

Shoulder strap

Color: Dark grey
Width: 44 mm
Type of webbing: Waterproof webbing
Breaking Strength: >27 kN

Other strap

Color: Black
Width: 44 mm
Type of webbing: Waterproof webbing
Breaking Strength: >27 kN

Back Anchorage D-Ring

Material: Aluminum alloy

Finish: Anodized
Breaking Strength: >23 kN

Sternal Anchorage V-Ring

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >23 kN

Side Anchorage D-Rings

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >23 kN

Automatic Quick-Release Buckles

Material: Aluminum alloy

Finish: Anodized
Breaking Strength: >9 kN

Adjuster Buckles

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >18 kN

Weight (kg)

Net weight: 2.3
Breaking Strength: >15 kN

Temperature

Temperature: -30°C to +50°C

CC5

Technical Specifications

Shoulder strap

Color: Dark grey
Width: 44 mm
Type of webbing: Waterproof webbing
Breaking Strength: >27 kN

Other strap

Color: Black
Width: 44 mm
Type of webbing: Waterproof webbing
Breaking Strength: >27 kN

Back Anchorage D-Ring

Material: Aluminum alloy

Finish: Anodized
Breaking Strength: >23 kN

Sternal Anchorage V-Ring

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >23 kN

Side Anchorage D-Rings

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >23 kN

Automatic Quick-Release Buckles

Material: Aluminum alloy

Finish: Anodized
Breaking Strength: >9 kN

Adjuster Buckles

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >18 kN

Weight (kg)

Net weight: 2.6
Breaking Strength: >15 kN

Temperature

Temperature: -30°C to +50°C

CC7

Technical Specifications

Shoulder strap

Color: Dark grey
Width: 44 mm
Type of webbing: Waterproof webbing
Breaking Strength: >27 kN

Other strap

Color: Black
Width: 44 mm
Type of webbing: Waterproof webbing
Breaking Strength: >27 kN

Back Anchorage D-Ring

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >23 kN

Sternal Anchorage V-Ring

Material: Aluminum alloy

Finish: Anodized
Breaking Strength: >23 kN

Side Anchorage D-Rings

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >23 kN

Belly Anchorage D-Ring

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >23 kN

Shoulder Anchorage web loops

Material: Polyester
Breaking Strength: >15 kN

Automatic Quick-Release Buckles

Material: Aluminum alloy
Finish: Anodized

Breaking Strength: >9 kN

Adjuster Buckles

Material: Aluminum alloy
Finish: Anodized
Breaking Strength: >18 kN

Weight (kg)

Net weight: 2.75
Breaking Strength: >15 kN

Temperature

Temperature: -30°C to +50°C

HONEYWELL MILLER® MODEL GUIDE

MODEL	SKU	DESCRIPTION	SIZE	LEG BUCKLES ALUM	CHEST BUCKLE ALUM	D-RINGS			INTEGRATED SR ADAPTOR	ROTATIVE BELT	PIVOT LINK LEG STRAP ADJUSTER		
						VENTRAL D	SHOULDER	SIDE D					
IC2	1036760	H700 IC2 ALUM QC FD	1	QC	QC	Alum	Alum	0	0	yes	yes	no	
	1036781	H700 IC2 ALUM QC FD	2	QC	QC	Alum	Alum	0	0	0	yes	yes	no
	1036783	H700 IC2 ALUM QC FD	3	QC	QC	Alum	Alum	0	0	0	yes	yes	no
	1036784	H700 IC2 ALUM QC FD	4	QC	QC	Alum	Alum	0	0	0	yes	yes	no
CC3	1036789	H700 CC3 ALUM QC FD/SD	1	QC	QC	Alum	Alum	2	0	0	no	no	yes
	1036800	H700 CC3 ALUM QC FD/SD	2	QC	QC	Alum	Alum	2	0	0	no	no	yes
	1036771	H700 CC3 ALUM QC FD/SD	3	QC	QC	Alum	Alum	2	0	0	no	no	yes
	1036773	H700 CC3 ALUM QC FD/SD	4	QC	QC	Alum	Alum	2	0	0	no	no	yes
CC5	1036785	H700 CC5 ALUM QC FD/SD	1	QC	QC	Alum	Alum	2	0	0	yes	yes	no
	1036793	H700 CC5 ALUM QC FD/SD	2	QC	QC	Alum	Alum	2	0	0	yes	yes	no
	1036787	H700 CC5 ALUM QC FD/SD	3	QC	QC	Alum	Alum	2	0	0	yes	yes	no
	1036788	H700 CC5 ALUM QC FD/SD	4	QC	QC	Alum	Alum	2	0	0	yes	yes	no
CC7	1036774	H700 CC7 ALUM QC FD/SD VD SHD	1	QC	QC	Alum	Alum	2	2	1	yes	yes	no
	1036775	H700 CC7 ALUM QC FD/SD VD SHD	2	QC	QC	Alum	Alum	2	2	1	yes	yes	no
	1036776	H700 CC7 ALUM QC FD/SD VD SHD	3	QC	QC	Alum	Alum	2	2	1	yes	yes	no
	1036777	H700 CC7 ALUM QC FD/SD VD SHD	4	QC	QC	Alum	Alum	2	2	1	yes	yes	no
	1036778	ONE PULL SUSPENSION TRAUMA STEPS (PAIR)											
	1036779	REMOVABLE LUMBAR PROTECTOR (EACH)											
	1036780	Waterproof DUFFLE BAG (EACH)											

Standards: EN 361:2002, EN 358:2018, EN 1497:2007

Certified to 140 kg

QC= Quick-Connect

For More Information

sps.honeywell.com

**HONEYWELL SAFETY PRODUCTS
UNITED KINGDOM**

Honeywell Safety Products UK LTD
Honeywell House, Skimped Hill Lane,
Bracknell, Berkshire RG12 1EB
United Kingdom
Phone: +44 (0) 1256 274938
Email: info-uk.hsp@honeywell.com

**HONEYWELL SAFETY PRODUCTS
NORDICS**

Honeywell Safety Products Nordic AB
Strandbadsvägen 15
SE-252 29 Helsingborg – Sverige
Phone: +46 (0) 424480433
Email: info-nordic.hsp@honeywell.com

**HONEYWELL SAFETY PRODUCTS
BENELUX**

Honeywell Safety Products Benelux BV
Lange Amerikaweg 55
7332 BP Apeldoorn, Nederland
Tel: +31 (0) 20 5656 988
Email: info-benelux.hsp@honeywell.com