



Universalspiker til både  
utvendig og innvendig bruk,  
også i våte rom.



[NO-DoP-h19/0003](#)

### EGENSKAPER



### Fordeler:

- Flatt hode
- 40 graders diamant spids
- Firkantet stamme



### ANVENDELSE

#### Bruksområde:

- Tre til tre

TEKNISK DATA

Product dimensions



| Art. nr.       | Item code     | NOBB nr.            | Fastener dimensions [mm] |     |                |
|----------------|---------------|---------------------|--------------------------|-----|----------------|
|                |               |                     | d                        | l   | d <sub>h</sub> |
| FIRKSQG1.4x25  | 75572         | 55837252            | 1.4                      | 25  | 4              |
| FIRKSQG1.7x30  | 75573         | 55837214            | 1.7                      | 30  | 4.2            |
| FIRKSQG1.7x35  | 75574         | 55837263            | 1.7                      | 35  | 4.2            |
| FIRKSQG1.7x40  | 75575         | 55837233            | 1.7                      | 40  | 4.2            |
| FIRKSQG2.0x40  | 75576 - 75581 | 55837157 - 55837282 | 2                        | 40  | 4.9            |
| FIRKSQG2.0x50  | 75582 - 75577 | 55837161 - 55837176 | 2                        | 50  | 4.9            |
| FIRKSQG2.2x55  | 75583 - 75578 | 55837104 - 55837123 | 2.2                      | 55  | 5.3            |
| FIRKSQG2.5x65  | 75584 - 75579 | 55837093 - 55837142 | 2.5                      | 65  | 6              |
| FIRKSQG2.8x65  | 75585         | 55837244            | 2.8                      | 65  | 6.8            |
| FIRKSQG2.8x75  | 75586 - 75580 | 55837066 - 55837138 | 2.8                      | 75  | 6.8            |
| FIRKSQG2.8x90  | 75587 - 75594 | 55837074 - 55837225 | 2.8                      | 90  | 6.8            |
| FIRKSQG3.4x95  | 75588         | 55837085            | 3.4                      | 95  | 7.6            |
| FIRKSQG3.8x125 | 75589         | 55837112            | 3.8                      | 125 | 8              |
| FIRKSQG4.2x125 | 75590         | 55837195            | 4.2                      | 125 | 8.7            |
| FIRKSQG4.8x150 | 75591         | 55837206            | 4.8                      | 150 | 10             |
| FIRKSQG5.5x175 | 75592         | 55837180            | 5.5                      | 175 | 11.5           |
| FIRKSQG6.0x190 | 75593         | 55837278            | 6                        | 190 | 13             |

Product characteristic parameters



| Art. nr.       | Product characteristic properties                                       |   |  |
|----------------|---|---|--|
|                | Characteristic Yield Moment – M <sub>y,k</sub> [M <sub>y,k</sub> ] [Nm] | Characteristic withdrawal parameter - f <sub>ax,k,90°</sub> [f <sub>ax,k,90°</sub> ] [N/mm <sup>2</sup> ] | Characteristic head pull-through parameter - f <sub>head,k</sub> [f <sub>head,k</sub> ] [N/mm <sup>2</sup> ] |
| FIRKSQG1.4x25  | -   | -   | -  |
| FIRKSQG1.7x30  | -   | -   | -  |
| FIRKSQG1.7x35  | -   | -   | -  |
| FIRKSQG1.7x40  | -   | -   | -  |
| FIRKSQG2.0x40  | -   | -   | -  |
| FIRKSQG2.0x50  | -   | -   | -  |
| FIRKSQG2.2x55  | -   | -   | -  |
| FIRKSQG2.5x65  | 3.3   | 2.5   | 8.6  |
| FIRKSQG2.8x65  | 4.3   | 2.5   | 8.6  |
| FIRKSQG2.8x75  | 4.3   | 2.5   | 8.6  |
| FIRKSQG2.8x90  | 4.3   | 2.5   | 8.6  |
| FIRKSQG3.4x95  | 7   | 2.5   | 8.6  |
| FIRKSQG3.8x125 | 13.7  | 2.5   | 8.6  |
| FIRKSQG4.2x125 | 15.1  | 2.5   | 8.6  |
| FIRKSQG4.8x150 | 29.3  | 2.5   | 8.6  |
| FIRKSQG5.5x175 | 34  | 2.5   | 8.6  |

| Art. nr.       | Product characteristic properties                          |  |   |
|----------------|--|--|---|
|                | Characteristic Yield Moment – $M_{y,k}$ [ $M_{y,k}$ ] [Nm] | Characteristic withdrawal parameter - $f_{ax,k,90^\circ}$ [ $f_{ax,k,90^\circ}$ ] [ $N/mm^2$ ] | Characteristic head pull-through parameter - $f_{head,k}$ [ $f_{head,k}$ ] [ $N/mm^2$ ] |
| FIRKSQG6.0x190 | 35.1   | 2.5  | 8.6   |

