



Universalspiker til både
utvendig og innvendig bruk,
også i våte rom.



[NO-DoP-h19/0003](#)

EGENSKAPER



Fordeler:

- Flatt hode
- 40 graders diamant spids
- Firkantet stamme



ANVENDELSE

Bruksområde:

- Tre til tre

TEKNISK DATA

Product dimensions



| Art. nr. | Item code | NOBB nr. | Fastener dimensions [mm] | | |
|----------------|---------------|---------------------|--------------------------|-----|----------------|
| | | | d | l | d _h |
| FIRKSQG1.4x25 | 75572 | 55837252 | 1.4 | 25 | 4 |
| FIRKSQG1.7x30 | 75573 | 55837214 | 1.7 | 30 | 4.2 |
| FIRKSQG1.7x35 | 75574 | 55837263 | 1.7 | 35 | 4.2 |
| FIRKSQG1.7x40 | 75575 | 55837233 | 1.7 | 40 | 4.2 |
| FIRKSQG2.0x40 | 75576 - 75581 | 55837157 - 55837282 | 2 | 40 | 4.9 |
| FIRKSQG2.0x50 | 75582 - 75577 | 55837161 - 55837176 | 2 | 50 | 4.9 |
| FIRKSQG2.2x55 | 75583 - 75578 | 55837104 - 55837123 | 2.2 | 55 | 5.3 |
| FIRKSQG2.5x65 | 75584 - 75579 | 55837093 - 55837142 | 2.5 | 65 | 6 |
| FIRKSQG2.8x65 | 75585 | 55837244 | 2.8 | 65 | 6.8 |
| FIRKSQG2.8x75 | 75586 - 75580 | 55837066 - 55837138 | 2.8 | 75 | 6.8 |
| FIRKSQG2.8x90 | 75587 - 75594 | 55837074 - 55837225 | 2.8 | 90 | 6.8 |
| FIRKSQG3.4x95 | 75588 | 55837085 | 3.4 | 95 | 7.6 |
| FIRKSQG3.8x125 | 75589 | 55837112 | 3.8 | 125 | 8 |
| FIRKSQG4.2x125 | 75590 | 55837195 | 4.2 | 125 | 8.7 |
| FIRKSQG4.8x150 | 75591 | 55837206 | 4.8 | 150 | 10 |
| FIRKSQG5.5x175 | 75592 | 55837180 | 5.5 | 175 | 11.5 |
| FIRKSQG6.0x190 | 75593 | 55837278 | 6 | 190 | 13 |

Product characteristic parameters



| Art. nr. | Product characteristic properties | | |
|----------------|---|---|--|
| | Characteristic Yield Moment – M _{y,k} [M _{y,k}] [Nm] | Characteristic withdrawal parameter - f _{ax,k,90°} [f _{ax,k,90°}] [N/mm ²] | Characteristic head pull-through parameter - f _{head,k} [f _{head,k}] [N/mm ²] |
| FIRKSQG1.4x25 | - | - | - |
| FIRKSQG1.7x30 | - | - | - |
| FIRKSQG1.7x35 | - | - | - |
| FIRKSQG1.7x40 | - | - | - |
| FIRKSQG2.0x40 | - | - | - |
| FIRKSQG2.0x50 | - | - | - |
| FIRKSQG2.2x55 | - | - | - |
| FIRKSQG2.5x65 | 3.3 | 2.5 | 8.6 |
| FIRKSQG2.8x65 | 4.3 | 2.5 | 8.6 |
| FIRKSQG2.8x75 | 4.3 | 2.5 | 8.6 |
| FIRKSQG2.8x90 | 4.3 | 2.5 | 8.6 |
| FIRKSQG3.4x95 | 7 | 2.5 | 8.6 |
| FIRKSQG3.8x125 | 13.7 | 2.5 | 8.6 |
| FIRKSQG4.2x125 | 15.1 | 2.5 | 8.6 |
| FIRKSQG4.8x150 | 29.3 | 2.5 | 8.6 |
| FIRKSQG5.5x175 | 34 | 2.5 | 8.6 |

| Art. nr. | Product characteristic properties | | |
|----------------|--|--|---|
| | Characteristic Yield Moment – $M_{y,k}$ [$M_{y,k}$] [Nm] | Characteristic withdrawal parameter - $f_{ax,k,90^\circ}$ [$f_{ax,k,90^\circ}$] [N/mm^2] | Characteristic head pull-through parameter - $f_{head,k}$ [$f_{head,k}$] [N/mm^2] |
| FIRKSQG6.0x190 | 35.1 | 2.5 | 8.6 |

