

MOVE OAK WHITE SE19013

WOOD - PRODUCT DATASHEET 2024

TECHNICAL DATA (EN 13489)		13 mm
Reaction to fire	EN 14342 Table 1 (when applicable) / EN 13501	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	≥ 17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,104
Construction: softwood veneer and lamella core		3-layer

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Tarkoclean for lacquered floors Refresher for lacquered floors
See more alternatives and the complete range of accessories @ www.tarkett.com	

INSTALLATION	
Installation method	2-lock for floating or glue down
Installation instruction	Download from www.tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating underfloor heating system	Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²	

MAINTENANCE

These Tarkett wooden floors have a Proteco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or highlighted details. Please always refer to maintenance guidance available on websites.

See maintenance instructions @ www.tarkett.com

DIMENSIONS & PACKAGE	Wear layer thk (mm)	Board/ pack	m ² / pack	m ² / pallet	Net weight/ m ² (kg)
2 200 x 190 x 13	2,5	6	2,51	87,85	7,3
2 000 x 190 x 13	2,5	6	2,28	79,80	7,3

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side)	Character	Latin name	DoP no.
Move Oak White SE19013	7879920	2 200 x 190 x 13	1-strip	Proteco Natura	Brushed	Minibevel	Expressive	1	0190-0103
Move Oak White SE19013	7879921	2 000 x 190 x 13	1-strip	Proteco Natura	Brushed	Minibevel	Expressive	1	0190-0103

Due to the nature of the material this shows typical values.

1: Quercus Robur & Quercus Petraea



2-LOCK



93%
RENEWABLE
RESOURCES



www.realwood.eu