

FAST DRY DEGREASER

Technical Data Sheet

Product name: Fast Dry Degreaser	Creation date: 14/11/2017	Version: 4.0
		Replaces: 3.0

Section 1 : General description

Quick dry non-chlorinated cleaner.

A fast drying, powerful degreasing solvent blend free of 1,1,1-trichloroethane or other chlorinated solvents. Fast Dry Degreaser penetrates quickly and cuts through dirt, grime and contaminants for improved operation of mechanical equipment. Enhances overall performance. Designed for applications where flammable solvents can be used.

Section 2 : Features

- Quickly dissolves grease, oil, lubricants, tar and adhesives.
- Effective wash-away of contaminants.
- Fast evaporation to minimise downtime.
- Ensures rapid turnaround.
- Leaves no residue.
- Stable, non-staining and non-corrosive.
- Safe on most plastics, coatings and rubbers (test prior to use).
- Aerosol is equipped with the 360° (upside-down) spray valve.
- Aerosol is pressurised with non-flammable CO₂ propellant, giving an active product content of over 95%.

Section 3: Applications

Gear boxes	Pumps	Fork lifts
Chains & cables	Motors	Brakes and clutches
Dies & molds	Engines	Material handling equipment
Compressors	Pneumatic tools	Parts & tools

Section 4: Directions

Spray liberally and allow excess to run off. Air dry or dry with absorbent cloth. Repeat if necessary.

After application, re-lubricate moving parts with CRC 3-36.

Check plastics compatibility before use. Do not use on sensitive electronic equipment such as tape decks, VCR's, computers, etc. Use one of CRC's precision cleaners for these applications.

Use with adequate ventilation. Do not use on energized equipment. Allow to dry thoroughly and vent before reactivating system.



A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all KF products.

Section 5: Typical product data (without propellant)

Appearance	: colourless liquid, typical odour
Specific gravity (@ 20°C)	: 0,716
Boiling range	: 55 - 120°C
Vapour density (vs air = 1)	: 3
Freezing point	: < -30°C
Evaporation rate (vs ether = 1)	: 2,8
Flash point (closed cup)	: < 0°C
Dynamic viscosity (@ 20°C)	: 0,5 mPa.s
Surface tension (@ 20°C, est.)	: 21 mN/m
Plastics compatibility	: to be checked (*)
Non-volatiles	: none
Transversal resistivity	: $\geq 1.10^{14}$ _.cm

Section 6: Packaging

Aerosol 12x500 ML

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied.

This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

We recommend you to register on this website for this product so you will be able to receive any future updated version automatically.