



tesa[®] extra Power Universell

Product Information



BNR 56338, 56348, 56388, 56389, 56396, 56490

Produktbeskrivelse

tesa[®] extra Power Universal er en allsidig elektrikertape med ekstra vedheft. Ideell for håndverk, reparasjon, festing, bunting og merking og mer.

Funksjoner

- For håndverk, reparasjon, festing, bunting, forsterking, merking og mye mer
- For daglige, ukompliserte løsninger og raske og enkle reparasjoner
- Meget god vedheft til alle typer overflater
- Værbestandig for bruk både inne og ute
- Kan rives for hånd
- Løsemiddelfri

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|--------------------------|------------------|--------|
| • Bæremateriale | PE-film med PET filament | • Total tykkelse | 215 µm |
| • Klebetype | Syntetisk gummi | | |

Egenskaper / ytelsesverdier

- | | | | |
|--|-------------|------------------------|--|
| • Temperaturbestandighet | Ja | • Ozone resistance | Ja |
| • Bruddstyrke | 100 N/cm | • Rivebestandig | Ja |
| • Aldringsbestandighet (UV) | Ja | • Skrivbar | Nei |
| • Fjernes uten kleberester | Nei | • Spennbarhet | 19 % |
| • Fuktbestandighet | Ja | • UV-bestandig | Ja |
| • Hand tearability | Ja | • Vanntett | Ja |
| • Klebekraft | Høy vedheft | • Velegnede overflater | Jevnt tre, Fliser, De fleste plasttyper, Glass, Metall |
| • Løsemiddelfri | Ja | • Water resistance | Ja |
| • Motstandsdyktig overfor olje og fett | Ja | | |



tesa[®] extra Power Universell

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=56338>