

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,  
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-070

Item No: 502016261











Screw description:

CBS CSK FLAT HD TX20 FULL THRD SST A2/AISI 304 PASSIV. WAX 4X30

Material: SST A2

Certificate No.: [CPR-J-00128-21](#)

Report No.: [1015-CPR-30-15255/5/JZ](#)

Size	Nominal diameter (mm)	Inner thread diameter (mm)	Head diameter (mm)	Total length (mm)	Thread length (mm)	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre) ( $N/mm^2$ )	Head pull-through parameter ( $N/mm^2$ )	Yield moment $I_2 = 1d$ (Nmm)	Tensile capacity (kN)
										
4x30	3.75 - 4.0	2.3 - 2.6	7.64 - 8.0	28.95 - 30.0	Full	1.78	18.73 / 13.33	24.37	2083 (17 Deg)	3.67
Characteristic density of wood $\rho_k$ (kg/m <sup>3</sup> )						450	350	400	-	
Durability (i.e. corrosion protection)						Stainless steel A2 (Service Class 3 acc. To EN 1995-1-1)				

**The manufacturer declares for:**

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 12 May 2021



Hieu Trong Nguyen