

**SEALANTS**

Self-declaration that the named products comply with the requirements for sealants as per BREEAM-NOR's chapter HEA 02

This form must be filled out by the MANUFACTURER of sealants, elastic or plastic, based on polyurethane, silicone, MS, acrylic or other.

Approved emission certificates are M1<sup>1</sup>, EC 1 Plus<sup>2</sup>.

If the product has one of the approved emission certificates, it is not necessary to fill in this form. Connect the emission certificate to the product in goBIM.

<sup>1</sup> Approved performance standard NS-EN 15251:2007, Appendix C

<sup>2</sup> Approved performance standard GEV Emissioncode

---

It is important that the information given here is correct, and we strongly encourage thoroughness in researching the extent to which emission testing and/or test reports show that the product complies with the standards and emission limit values required by BREEAM-NOR 2016. If in doubt, the manufacturer should consult own internal and external experts. **Providing incorrect and misleading information can have legal consequences. Once filled-out, the form must be signed by a legally responsible person for the manufacturer, such as a technical director or a managing director.**

**MANUFACTURER:** Novatech int. V/Relekta AS

**PRODUCT TRADE NAME:** XealPro

**PRODUCT ID:**

The following is hereby confirmed by the manufacturer:

1. The product has undergone an emission test<sup>3</sup> which shows that its emissions are below the values<sup>4</sup> shown in table 15.

Table 15: Emission limits for all product categories – Conversion table

| Ref              | Wall                |                     | Floor/ceiling       |                     | Sealants            |                     |
|------------------|---------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
|                  | µg/m <sup>2</sup> h | µg/m <sup>3</sup> h | µg/m <sup>2</sup> h | µg/m <sup>3</sup> h | µg/m <sup>2</sup> h | µg/m <sup>3</sup> h |
| TVOC 28d         | 200                 | 417                 | 200                 | 160                 | 4260                | 60                  |
| Formaldehyde 3d  | 24                  | 50                  | 62,5                | 50                  | 3550                | 50                  |
| Formaldehyde 28d | 50                  | 104                 | 50                  | 40                  | 710                 | 10                  |
| Carcinogenic     | 5                   | 10                  | 5                   | 4                   | 71                  | 1                   |

<sup>3</sup>Documentation (test in acc. with approved standard) can be requested if required.

<sup>4</sup>Show accordance with units µg/m<sup>3</sup> or µg/m<sup>2</sup>h

3. The emission test has been performed in accordance with the following approved standards ISO 16000-9, ISO 16000-6 (volatile organic compounds), ISO 16000-3 (formaldehyde). Test and calculation shall be carried out according to EN 16516.

Legally responsible: Relekta AS

Position: Product Manager

Date: 28/10-22

Signature: \_\_\_\_\_

