



# BOSCH

# GSR 18V-90 FC Professional

GFA 18-M, GFA 18-H, Aux. Handle, Depth Gauge, L-BOXX

The Bosch Professional FlexiClick System – perfectly equipped for a professional job.



**1** The Bosch Professional FlexiClick System: a versatile system with easy-to-change attachments

**2** The GFA 18-H turns the GSR 18V-90 FC into a rotary hammer - the only 18V drill driver ready for effortless hammer drilling into concrete up to  $\varnothing$  10 mm

**3** With a head length of only 136 mm and a max. hard torque of 64 Nm, you have a highly compact and powerful tool at hand

### Marketing & Logistics

SKU	<b>0.601.9K6.204</b>
EAN code	4.059.952.617.435
Tool dimension (LxWxH)	136 x 77 x 210 mm
Packaging dimension (LxWxH)	442 x 357 x 151 mm
Weight (net / gross)	0.94 kg / 3.92 kg

### Technical information

Voltage	[V]	18
Speed (First / second gear)	[RPM]	0-630 / 0-2.100
Max. Torque (Hard / Soft)	[Nm]	64 / 36
Max. Drilling diam (Wood/Steel)	[mm]	68 / 13
Max. Screw diameter	[mm]	12
Tool Holder		6.35 (¼")
Sound pressure level	dB(A)	74.5
Vibration emission value ah (Drilling in metal)	(m/s <sup>2</sup> )	<2.5

### Scope of supply

Scope of supply	Part no.
Baretool	3601JK6200
GFA 18-M	1600A00ZS9
GFA 18-H	1600A003ND
Auxiliary Handle	16020250AB

### Target groups

### Applications

Target groups	Applications
Facility Manager	Repair and Maintenance
Electrician	Installation, Maintenance and Repair of electrical systems
Finish Carpenter/Joiner	Joiner / Cabinet Installation; Window & Door Installation
HVAC	Air conditioning, Refrigerator
Metal Installation / Locksmith Rough Carpenter / Framer	creation of steel and machinery parts, repair of machines Assembly of the major structural elements of a wood-framed building
Plumber	Repair of piping, fittings, fixtures, system equipment involved in water distribution