

tesa® Professional 53988 Soft PVC Insulation Tape



Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

•	Bæremateriale	Bløt PVC	•	lotal tykkelse	150 μm
•	Klebetype	Naturgummi			

Egenskaper / ytelsesverdier

•	Bruddforlengelse	240 %	•	Hand tearability	good
•	Bruddstyrke	25 N/cm	•	Klebeevne	very good
•	Aldringsbestandighet (UV)	good	•	Lett å fjerne	Nei
•	Bestandig over for bløtgjørere	good	•	Slitstyrkebestandighet	good
•	Fuktbestandighet	good	•	Temperaturbestandighet, kort	90 °C
•	Gjennomslagspenning	7000 V		varighet	
				Water resistance	medium

Klebekraft

Klebeevne på Stål
2.5 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

