

Product – and environmental Declaration for ANNUEL collection

Type: Wall covering viny on non-woven. Weight: +/- 230g/m²

Environmental mark

Fulfils the IGI's trade standards

(IGI = International Wall covering Manufacturers' Association)

Product contents

All wallcoverings produced by DECOPRINT NV are free from heavy metals and other environmental substances. All inks are waterbased.

Wall coverings components	Total weight percentage	Weight percentage	Specification of the components composition
Non – Woven	35%	40-85%	Cellulose (TCF)
		15-30%	Synthetic fibres film
		0-30%	Vac/Acrylic polymer
		15-25%	Filler
PVC	60%	98%	Pvc Filler
		2%	Thinner
Ink	5%	65-100%	Pigment
			Filler
		0-30%	Vac/Acrylic polymer

Formaldehyde in combined form exists naturally in wood being used in production of the substrate. Analysis of wallcoverings therefore have shown tracks of formaldehyde. The quantities though are essential lower than the valid limit.

Usage

The wallcovering can be used in all areas except wet areas such as bathrooms etc. Suitable adhesive is a machine adjusted adhesive.

Colour fastness to light

Good colour fastness to light 5.

Decoprint N.V. – Dommekensstraat 2 – 9240 ZELE – België

Tel: 0032 52 44 78 11

Fax: 0032 52 44 97 63

RPR Dendermonde

BTW BE0423 981 654

Packaging

The wallcovering rolls are wrapped into a thin recyclable polyethylene film before being packed into a corrugated cardboard carton.

In average 25gr packaging is being used per kg wallcovering.

The average transport volume (incl packaging) per kg wallcovering is about 4dm³

The corrugated cardboard carton packaging material is produced from recycled fibres.

Transport

The wallcoverings are transported via trucks from our central warehouse in Mölnlycke, Sweden.

Care instructions

The wallcoverings are extra washable. Stains are treated as follows.

- Wet the stain with a cloth or a sponge using soapy water or detergent
- Dab off the over amount of water and leave the wallcovering to selfdry.
- Avoid to get water in the joints where the wallcovering is unprotected.

Estimated lifetime

Estimated lifetime of the wallcoverings, when hanged, is 10-15 years.

Recycling and waste

The wallcovering can be recycled as energy at combustion.

Part of the excess inks are being reused in production.

No wallcovering waste is considered as hazardous waste.

Production

There is no solvent emission during the production.



Wim Lecluyse
Operations Manager

Decoprint N.V. – Dommekensstraat 2 – 9240 ZELE – België

Tel: 0032 52 44 78 11

Fax: 0032 52 44 97 63

RPR Dendermonde

BTW BE0423 981 654