## **DECLARATION of PERFORMANCE.**

Ref. no.: YT-18.

1. Product name: Forestia eliteX 12 mm

2. Product type: Particleboard type: NS-EN 312 P5.

3. Intended use: Boards for for use in humid conditions.

4. Manufacturer: Forestia AS, 2435 Braskereidfoss, Norway.

5. System of attestation of conformity: System 2+

6. Harmonized standard: NS-EN 13986:2004+A1:2015

Accredited laboratorium: Norsk Treteknisk Institutt, identification no. 1070.

**7.** Declared performance:

Essential characteristics:	Performance:	Harmonized technical specification:
	12mm P5	
Bending strength	18 MPa	
Modulus of elasticity	2550 MPa	
Internal bond	0,45 MPa	
Thickness swelling 24h	11 %	
Moisture resistance after cyclic test:		NS-EN
- Thickness swelling	12 %	13986:2004
- Internal bond	0,25 MPa	+A1:2015
Reaction to fire:	D-s1,d0	
Airborne sound insulation	NPD	
Sound absorption, frequency 250-500 Hz	0,10	
" " frequency 1000-2000 Hz	0,25	
Water vapor permeability μ, wet / dry cup	15 / 50	
Thermal conductivity, W/(m K)	0,15	
Biological durability	NPD	
Content of pentachlorophenol (PCP)	<5 ppm	
Formaldehyde potential	Class E1	

 $\overline{NPD} = No performance declared$ 

**8.** The performance of the product identified in points no. 1 and 2 are in conformity with the declared performance in point no. 7.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point no. 4.

Signed for and on behalf of Forestia AS by:

Vegard Grønnerud, Quality Manager

Name Function.

Braskereidfoss, 04.03.2022 .....

Signature

Vegal 6/3