


ENVIRONMENTAL-PRODUCT DECLARATION

as per ISO 14025 and EN 15804+A1

Owner of the Declaration	Grundfos Holding A/S
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-GRU-20180144-CCC2-EN
Issue date	20/11/2018
Valid to	19/05/2024

MAGNA3 25-40/60/80/100/120 (Cast Iron) Grundfos Holding A/S

www.ibu-epd.com | <https://epd-online.com>



General Information

Grundfos Holding A/S

Programme holder

IBU – Institut Bauen und Umwelt e.V.
 Hegelplatz 1
 10117 Berlin
 Germany

Declaration number

EPD-GRU-20180144-CCC2-EN

This declaration is based on the product category rules:

Pumps for liquids and liquids with solids, 01/08/2021
 (PCR checked and approved by the SVR)

Issue date

20/11/2018

Valid to

19/05/2024

[Unterschrift]

Dipl.-Ing Hans Peters
 (chairman of Institut Bauen und Umwelt e.V.)

[Unterschrift]

Florian Pronold
 (Managing Director Institut Bauen und Umwelt e.V.)

MAGNA3 25-40/60/80/100/120 (Cast Iron)

Owner of the declaration

Grundfos Holding A/S
 Poul Due Jensens Vej 7
 8850 Bjerringbro
 Denmark

Declared product / declared unit

1 PCS. of MAGNA3 25-40/60/80/100/120 (Cast Iron)

Scope:

The declared product is 1 piece of MAGNA3 25-40/60/80/100/120 (Cast Iron) pump. The product is produced in Wahlstedt, Germany, and the life cycle assessment is based on data collected at the production site. The declaration covers five different types of the MAGNA3 25- product (40/60/80/100/120). All life cycle sub-modules are identical for all five types, except module B6. The indicator results for module B6 in the results tables are declared for MAGNA3 25-40. B6 indicator results for 60, 80, 100 or 120 can be derived by multiplying the B6 indicator results with the factors given in the section LCA: Results.

The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life cycle assessment data and evidences.

The EPD was created according to the specifications of EN 15804+A1. In the following, the standard will be simplified as *EN 15804 bezeichnet*.

Verification

The standard EN 15804 serves as the core PCR	
Independent verification of the declaration and data according to ISO 14025:2011	
<input type="checkbox"/>	internally
<input checked="" type="checkbox"/>	externally

[Unterschrift]

Angela Schindler,
 (Independent verifier)

Product

Product description/Product definition

The Grundfos MAGNA3 circulator pumps are designed for circulating liquids in heating systems, air-conditioning and cooling systems and domestic hot-water systems. However, the pump range can also be used in ground source heat pump systems and solar-heating systems.

The MAGNA3 pump is a centrifugal pump powered by an electrical motor. It has a high-performance neodymium magnet rotor which increases motor efficiency and an insulation shell to reduce heat loss from the cast iron pump housing with threaded connections.

This EPD covers five types of the MAGNA3 pump. These are all the same physical products and 100 % identical in terms of design, dimensions and materials as well as supply chain and manufacturing processes, i.e. all cradle to gate processes (A1-A3). The products are also identical in terms of packaging, distribution, reference service life and end-of-life treatment. The only thing that differentiates the products from each other is the software which controls how the pump operates in the system in which it is installed, making them fit for different applications. Hence, all life cycle modules are identical, except use stage module B6, which will change, as the applied scenarios for electricity consumption changes.

Each type covers 4 different product numbers: PN10 (Int.), PN10 (Germany), PN16 (Int.), PN16 (Germany). They are grouped as shown below. The group reference in the technical data and scenarios refers also to these.

GROUP 1 - MAGNA3 25-40 180 PN10/16:
97924244, 97924623, 97924249, 97924628

GROUP 2 - MAGNA3 25-60 180 PN10/16:
97924245, 97924624, 97924250, 97924629

GROUP 3 - MAGNA3 25-80 180 PN10/16:
97924246, 97924625, 97924251, 97924630

GROUP 4 - MAGNA3 25-100 180 PN10/16:
97924247, 97924626, 97924252, 97924631

GROUP 5 - MAGNA3 25-120 180 PN10/16:
97924248, 97924627, 97924253, 97924632 For the placing on the market in the EU/EFTA (with the exception of Switzerland) the following legal provisions as well as the corresponding harmonised norms based on these provisions apply:

Machinery Directive (2006/42/EC)
Standard used: EN 809:1998 + A1:2009.

Radio Equipment Directive (2014/53/EU)
Standards used: EN 60335-1:2012/AC:2014 + A11:2014, EN 60335-2-51:2003 + A1:2008 + A2:2012, EN 62233:2008, EN 55014-1:2006 + A1:2009 + A2:2011, EN 55014-1:2017, EN 61000-6-2:2005, EN 61000-3-2:2014, EN 61000-3-3:2013, ETSI EN 301 489-1 V2.2.0, ETSI EN 301 489-17 V3.2.0, ETSI EN 300 328 V2.1.1

Ecodesign Directive (2009/125/EC)
Commission Regulation (EC) No: 641/2009 and Commission Regulation (EU) 622/2012.
Standards used: EN 16297-1:2012, EN 16297-2:2012.

The CE-marking takes into

account the proof of conformity with the respective harmonized norms based on the legal provisions above.

MAGNA3 pumps are not covered by a harmonized standard under the /Regulation EU No. 305/2011/ (CPR).

Application

For the application and use the respective national provisions apply. The pump is designed for circulating liquids in the following systems:

- heating systems
- domestic hot-water systems
- air-conditioning and cooling systems
- ground-source heat-pump systems
- solar-heating systems

The pump is suitable for thin, clean, non-aggressive and non-explosive liquids, not containing solid particles or fibres that may attack the pump mechanically or chemically. In heating systems, the water must meet the requirements of accepted standards on water quality in heating systems, for example the German standard VDI 2035. The pumps are also suitable for domestic hot-water systems.

Technical Data

The performance data of the product according to the harmonised norms, based on the harmonisation provisions above apply.

The relevant technical specifications according to the PCR Part B is given in the table below. Characteristics that are the same for all five product groups are only given once. Others are given individually for all five groups.

Note:

Electrical pumps usually falls under the scope of several internal market directives and regulations, such as the Machinery directive, Ecodesign Directive, Radio Equipment Directive etc. The relevant technical data given in the EPD will vary depending on the type of product and areas of application, and the table below should be adjusted accordingly.

Name	Value	Unit
Frequency	50	Hz
Voltage	230	V
Pumped liquid (e.g. water)	Clean water	-
Energy Efficiency Index	0,18	
Flow range, Gr. 1 (max)	6,1	m3/h
Flow range, Gr. 2 (max)	7,5	m3/h
Flow range, Gr. 3 (max)	8,5	m3/h
Flow range, Gr. 4 (max)	9,4	m3/h
Flow range, Gr. 5 (max)	9,7	m3/h
Head max., Gr. 1	4	m
Head max., Gr. 2	6	m
Head max., Gr. 3	8	m
Head max., Gr. 4	10	m
Head max., Gr. 5	12	m
Power input, Gr. 1 Average (from load profile describing use)	0,0238	kW
Power input, Gr. 2 Average (from load profile describing use)	0,0363	kW
Power input, Gr. 3 Average (from load profile describing use)	0,0498	kW
Power input, Gr. 4 Average (from load profile describing use)	0,0643	kW
Power input, Gr. 5 Average (from load profile describing use)	0,0739	kW
Nominal capacity, Gr. 1	0,05	kW
Nominal capacity, Gr. 2	0,084	kW
Nominal capacity, Gr. 3	0,116	kW
Nominal capacity, Gr. 4	0,153	kW
Nominal capacity, Gr. 5	0,185	kW

Please select one of the following options and delete the header of the selected [alternative]:

[Alternative 1a: Product according to the CPR, based on a hEN]:

- Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to *EN xyz:date, title*.
- Voluntary data: *source, date, title* (not part of CE-marking).

[Alternative 1b: Product according to the CPR, based on an ETA]:

- Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to *ETA no. xyz, date, title*.
- Voluntary data: *source, date, title* (not part of CE-marking).

[Alternative 2a: Product not harmonised in accordance with the CPR but in accordance with other provisions for harmonisation of the EU]:

Performance data of the product according to the harmonised standards, based on provisions for harmonization.

Voluntary data: *source, date, title* (not part of CE-marking).

[Alternative 2b: Product harmonized as well in accordance with the CPR as with other legal provisions of the EU]:

- Performance data of the product in accordance with the declaration of performance with respect to its essential characteristics according to *EN xyz: date, title* or *ETA*

no. xyz, date, title respectively.

- Performance data of the product, based on the harmonised standards, in accordance with the other provisions for harmonization.
- Voluntary data: *source, date, title* (not part of CE-marking)

[Alternative 3: Product for which no legal provisions for harmonisation of the EU exist]:

Performance data of the product with respect to its characteristics in accordance with the relevant technical provision (no CE-marking).

Base materials/Ancillary materials

Name	Value	Unit
Aluminium	5,4	%
Cardboard	6,4	%
Cast iron	36	%
Ceramics	0,8	%
Copper	3,2	%
Electronics	6,1	%
Magnet	1,9	%
Paper	3,0	%
Plastic film	0,2	%
Plastics	15,6	%
Rubber	0,6	%
Stainless steel	6,5	%
Steel	6,6	%
Wood pallet	7,7	%
TOTAL	100	%

REACH

The product does not contain substances listed in the Candidate List of Substances of Very High Concern for Authorisation (15.01.2018) exceeding 0.1 percentage by mass.

ISO 14001

The Wahlstedt production has been assessed and certified as meeting the requirements in ISO 14001:2015 (Certificate DE11/81829052.07)

Environment and health during use

Reference service life

No use stage scenario which refers to the lifetime of the product is declared. However, to facilitate building calculations, an estimated RSL of 10 years can be used. This is an EU consensus-based estimation, referenced on page 37 in Appendix 7: Lot 11 – Circulators in Buildings, prepared by AEA Energy & Environment for the European Commission in the context of the Eco Design Directive:

There is no definitive information on average circulator life available, there is consensus within industry that it is at least 12 years. However, this is complicated by many factors, including many being scrapped prematurely when e.g. the boiler they are connected to is replaced.

From the estimated stock (140Mpa) and annual sales (14Mpa), the average lifetime of the circulator is taken as being 10 years for the purposes of this study.

The RSL of the declared product is not directly influencing the results in this study, as no declared use stage scenario is dependent on the RSL; The use stage sub-module B6 is

declared per year as required by the PCR Part B.

LCA: Calculation rules

Declared Unit

The declared unit is 1 piece (pce) of product.

Name	Value	Unit
Declared unit	1	pce.
Mass reference	6,41	kg/pce
Conversion factor to 1 kg	0,156	-

For IBU core EPDs (where clause 3.6 is part of the EPD): for average EPDs, an estimate of the robustness of the LCA values must be made, e.g. concerning variability of the production process, geographical representativeness and the influence of background data and preliminary products compared to the environmental impacts caused by actual production.

System boundary

This EPD is Cradle-To-Grave.

The system boundaries of the EPD follow the modular approach in EN 15804.

By decision no. 20170712-n of the SVR, the modules B3, B4 and B5 are by default declared as "MNR" (module not relevant).

The product stage (A1-A3) comprises raw material extraction and processing, transport processes as well as the manufacturing process. The product stage is included in the study, and according to EN 15804 the system boundary with nature is set to include those processes that provide the material and energy inputs into the system and the following manufacturing, transport up to the factory gate as well as the processing of any waste arising from those processes.

Wastes and losses are included in the modules where they occur according to the polluter pays principle and the modular approach of EN 15804.

The product stage includes:

- A1 Extraction and processing of raw materials
- A1 Reuse of products or materials from a previous product system
- A1 Processing of secondary materials
- A1 Generation of electricity, steam and heat from primary energy resources, also including their extraction, refining and transport
- A1 Energy recovery and other recovery processes from secondary fuels
- A2 Transportation up to the factory gate and internal transport
- A3 Production of ancillary materials or pre-products
- A3 Manufacturing of products and co-products
- A3 Manufacturing of packaging
- A1-A3 processing up to the end-of-waste state or disposal of final residues

For secondary material inputs, the system boundary to the previous system (providing the secondary material) is set where

outputs reach the end-of-waste state. The recycling of secondary material into new raw materials is included in the system boundary of this study.

Waste materials from production processes that is recycled without any modification of the material-inherent characteristics are modelled as closed loop within A1-A3. This is done up to the input mass flow that was used during production.

Waste for incineration arising in the product stage is accounted for in the module where the waste is produced. The environmental loads from the incineration process are declared in the module where it occurs and the electricity and heat which is produced from the incineration is considered as closed-loop within A1-A3, as described in PCR Part A, 5.5.1.

Input of biogenic carbon from the production of packaging material is inventoried in A3. As required by PCR Part A, the corresponding end-of-life module of the packaging material, A5, is also declared and the emissions of biogenic carbon inventoried.

The construction process stage (A4-A5) includes:

A4:

- Transportation from factory gate to distribution center
- Consumption of electricity, thermal energy and water at distribution center
- Transportation from distribution center to construction site
- Wastage during distribution

A5:

- Installation process
- Transport of packaging waste to treatment site
- Waste treatment of packaging

The packaging material does not reach the end of waste state but is incinerated as waste. According to European statistics, the average R1 value of incineration plants is > 0.6. Therefore, it is assumed that packaging material are treated thermally in an incineration plant with R1 > 0.6. The loads from the combustion process of packaging are declared in module A5 and the resulting energy benefits in module D, as required by the PCR Part A, 5.5.2.

Use stage (B1-B7):

The use stage, related to the building fabric includes:

- B1, use or application of the installed product
- B2, maintenance

The use stage related to the operation of the building includes:

- B6, operational energy use
- B7, operational water use

In this study, all use stage modules are assessed, though B1, B2 and B7 are assessed to be zero. By decision no. 20170712-n of the SVR, the modules B3, B4 and B5 are by default declared as "MNR" (module not relevant). The modules include the provision and transport of all materials, products and related energy and water use, as well as waste processing up to the end-of-waste state or disposal of final residues during the use stage. They also include all impacts and aspects related to the losses during the use stage (i.e. production, transport, and waste processing and disposal of the lost products and materials).

Contributions to operational energy use during the use stage (B6) comes from the electricity consumption of the product. The annual electricity consumption is calculated by multiplying the average power input, which is based on a defined load profile, with the annual running hours. These values are declared in the scenarios section.

The End-of-Life stage (C1-C4) includes all activities from when the product reaches the end of its service life and no longer provides any functionality and until all materials and components are processed for reuse/recycling or disposed of.

According to EN 15804 and the PCR Part A, the end of life stage includes:

- C1 deconstruction of the product from the building, including initial on-site sorting of the materials
- C2 transportation of the discarded product to a recycling site and transportation of waste to final disposal
- C3 waste processing, collection of waste fractions from the deconstruction and waste processing of material flows intended for reuse, recycling and energy recovery
- C4 waste disposal including physical pre-treatment and management of the disposal site

At end of life, the MAGNA3 pump is manually disassembled from the piping system in which it has been installed. The definition of the applied end-of-life scenario in this EPD follows the requirements in the PCR Part A, 6.2 regarding complex products, with a combination of recycling, thermal waste treatment and landfilling. 100 % of the material is considered in the end of life scenario as required by the PCR. An overall collection rate of 90 % have been assumed. Materials from which energy is recovered in an incineration process with a R1-value above 0.60 are in this study included with the environmental burdens from the incineration process inventoried in C3, the recovered energy is declared as exported energy in C3 and the energy benefits is declared in D. This procedure is according to the PCR Part A, 5.5.6.

C3 includes the mechanical separation of the product followed by a series of sorting steps. Metal fractions are recycled and plastics, paper (manuals) and electronics are assumed incinerated with energy recovery. The residual fractions are landfilled and declared in C4. The specific amounts are shown in the scenarios section.

Beyond system boundary (D): According to EN 15804 module D includes the reuse, recovery and/or recycling potentials, expressed as net impacts and benefits. Any declared benefits and loads from net flows leaving the product system that have not been allocated as co-products and that have passed the end-of-waste state are included in module D.

Contributions to module D comes from waste incineration processes in A5 and C3 as well as material recycling in C3. The specific fractions and net flows are shown in the scenarios section.

Geographic Representativeness

Land or region, in which the declared product system is manufactured, used or handled at the end of the product's lifespan: Europe

Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to EN 15804 and the building context, respectively the product-specific characteristics of performance, are taken into account.

LCA: Scenarios and additional technical information

The following technical information forms the basis for the declared gate-to-grave modules and can be used for developing specific scenarios in the context of a building assessment.

Transport from the gate to the site (A4)

Name	Value	Unit
Litres of fuel	0,0129	l/100km
Transport distance	2003	km
Capacity utilisation (including empty runs)	85	%
Gross density of products transported	428	kg/m ³
Wastage during distribution	0,01	%

Assembly (A5)

Name	Value	Unit
Packaging waste for incineration (PE-film)	0,0093	kg
Packaging waste for incineration (Wood pallet)	0,49	kg
Packaging waste for incineration (Cardboard)	0,411	kg

An estimated RSL of 10 years can be used to facilitate building calculations. This is an EU consensus-based estimation, referenced in Appendix 7: Lot 11 – Circulators in Buildings, prepared by AEA Energy & Environment for the European Commission in the context of the Eco Design Directive.

Reference service life

Name	Value	Unit
Life Span according to the manufacturer	10	a

Operational energy use (B6)

Name	Value	Unit
Electricity consumption, Group 1	119	kWh/a
Electricity consumption, Group 2	181,5	kWh/a
Electricity consumption, Group 3	249	kWh/a
Electricity consumption, Group 4	321,5	kWh/a
Electricity consumption, Group 5	369,5	kWh/a
Average power input, Group 1	0,0238	kW
Average power input, Group 2	0,0363	kW
Average power input, Group 3	0,0498	kW
Average power input, Group 4	0,0643	kW
Average power input, Group 5	0,0739	kW
Running hours (all groups)	5000	h/a

End of life (C1-C4)

Name	Value	Unit
Collected as mixed construction waste	5,5	kg
Transportation distance (C2)	500	km
Aluminium for recycling	0,3	kg
Steel for recycling	2,42	kg
Copper for recycling	0,19	kg
Stainless steel for recycling	0,36	kg
Paper for incineration w/energy recovery	0,17	kg
Plastics for incineration w/energy recovery	0,93	kg
Electronics for incineration w/energy recovery	0,35	kg
Landfilling	0,79	kg

Reuse, recovery and/or recycling potentials (D), relevant scenario information

The values in the table are flow amounts which contributes to module D.

Name	Value	Unit
A5, incineration w/energy recov. (PE-foil)	0,0093	kg
A5, incineration w/energy recov. (Wood pallet)	0,49	kg
A5, incineration w/energy recov. (Cardboard)	0,411	kg
C3, steel for recycling (net amounts)	-0,158	kg
C3, stainless steel for recycling (net amounts)	0,224	kg
C3, aluminium for recycling (net amounts)	-0,047	kg
C3, copper for recycling (net amounts)	0,061	kg
C3, paper for incineration, w/ energy recov.	0,17	kg
C3, plastics for incineration, w/ energy recov.	0,93	kg
C3, electronics for incineration, w/ energy recov.	0,35	kg

LCA: Results

Characterization model: CML 2001 – Apr. 2013. By Decision no. 20170712-n of the IBU SVR, the modules B3, B4, B5 are marked as MNR (module not relevant) as default. The LCA results in B6 refers to a period of one year, as required by the PCR Part B. To quantify B6 over the total life cycle, the LCA results of module B6 is multiplied by 10 (estimated service life). The indicator results for module B6 are declared for MAGNA3 25-40. B6 indicator results for 60/80/100/120 can be derived by multiplying the B6 indicator results with the following factors:

MAGNA3 25-40: **1,00**
MAGNA3 25-60: **1,53**
MAGNA3 25-80: **2,09**
MAGNA3 25-100: **2,70**
MAGNA3 25-120: **3,11**

DESCRIPTION OF THE SYSTEM BOUNDARY (X = INCLUDED IN LCA; MND = MODULE NOT DECLARED; MNR = MODULE NOT RELEVANT)

PRODUCT STAGE			CONSTRUCTION PROCESS STAGE		USE STAGE							END OF LIFE STAGE				BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARIES
Raw material supply	Transport	Manufacturing	Transport from the gate to the site	Assembly	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
X	X	X	X	X	X	X	MNR	MNR	MNR	X	X	X	X	X	X	X

RESULTS OF THE LCA - ENVIRONMENTAL IMPACT according to EN 15804+A1: 1 PCS of MAGNA3 25-40 (Cast Iron)

Parameter	Unit	A1-A3	A4	A5	B1	B2	B6	B7	C1	C2	C3	C4	D
GWP	kg CO ₂ eq	5.13E+01	7.72E-01	1.51E+00	0	0	4.94E+01	0	0	1.41E-01	3.33E+00	1.26E-02	-1.8E+00
ODP	kg CFC11 eq	7.17E-08	7.2E-12	3.44E-14	0	0	2.2E-10	0	0	5.91E-15	1.28E-12	2.85E-15	-7.08E-09
AP	kg SO ₂ eq	4.72E-01	3.19E-03	2.33E-04	0	0	1.4E-01	0	0	5.83E-04	1.11E-03	7.46E-05	-8.84E-03
EP	kg PO ₄ ³⁻ eq	2.52E-02	8.01E-04	4.72E-05	0	0	1.31E-02	0	0	1.48E-04	1.45E-04	1.03E-05	-4.45E-04
POCP	kg Ethen eq	2.45E-02	-1.28E-03	5.98E-06	0	0	8.78E-03	0	0	-2.39E-04	7.5E-05	5.8E-06	-5.39E-04
ADPE	kg Sb eq	3.01E-03	3.7E-07	2.13E-08	0	0	2.62E-05	0	0	1.26E-08	2.06E-07	4.84E-09	-2.06E-04
ADPF	MJ	6.53E+02	1.06E+01	3.85E-01	0	0	5.26E+02	0	0	1.93E+00	3.46E+00	1.63E-01	-2.35E+01

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

RESULTS OF THE LCA - INDICATORS TO DESCRIBE RESOURCE USE according to EN 15804+A1: 1 PCS of MAGNA3 25-40 (Cast Iron)

Parameter	Unit	A1-A3	A4	A5	B1	B2	B6	B7	C1	C2	C3	C4	D
PERE	MJ	1.5E+02	5.76E-01	1.52E+01	0	0	3.39E+02	0	0	1.01E-01	4.38E+00	2.09E-02	-3.45E+00
PERM	MJ	1.79E+01	0	-1.52E+01	0	0	0	0	0	0	-2.39E+00	0	0
PERT	MJ	1.68E+02	5.76E-01	6.28E-02	0	0	3.39E+02	0	0	1.01E-01	1.99E+00	2.09E-02	-3.45E+00
PENRE	MJ	6.89E+02	1.06E+01	8.4E-01	0	0	9.02E+02	0	0	1.94E+00	3.11E+01	1.69E-01	-2.87E+01
PENRM	MJ	3.12E+01	0	-4E-01	0	0	0	0	0	0	-2.54E+01	0	0
PENRT	MJ	7.2E+02	1.06E+01	4.45E-01	0	0	9.02E+02	0	0	1.94E+00	5.66E+00	1.69E-01	-2.87E+01
SM	kg	3.18E+00	3.18E-04	0	0	0	0	0	0	0	0	0	0
RSF	MJ	0	0	0	0	0	0	0	0	0	0	0	0
NRSF	MJ	0	0	0	0	0	0	0	0	0	0	0	0
FW	m ³	8.55E-01	1.11E-03	3.93E-03	0	0	4.62E-01	0	0	1.87E-04	9.69E-03	3.23E-05	-6.63E-03

PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

RESULTS OF THE LCA – WASTE CATEGORIES AND OUTPUT FLOWS according to EN 15804+A1: 1 PCS of MAGNA3 25-40 (Cast Iron)

Parameter	Unit	A1-A3	A4	A5	B1	B2	B6	B7	C1	C2	C3	C4	D
HWD	kg	9.64E-05	5.6E-07	4.32E-09	0	0	4.23E-07	0	0	1.02E-07	4.01E-09	2.91E-09	-2.18E-08

NHWD	kg	3.05E+00	1.23E-03	1.67E-02	0	0	6.35E-01	0	0	1.56E-04	9.89E-02	7.93E-01	2.33E-01
RWD	kg	2.58E-02	2.71E-05	2.39E-05	0	0	1.49E-01	0	0	4.06E-06	8.74E-04	2.44E-06	-2.03E-03
CRU	kg	0	0	0	0	0	0	0	0	0	0	0	0
MFR	kg	0	0	0	0	0	0	0	0	0	3.26E+00	0	0
MER	kg	0	0	0	0	0	0	0	0	0	0	0	0
EEE	MJ	0	0	2.23E+00	0	0	0	0	0	0	5.03E+00	0	0
EET	MJ	0	0	4.01E+00	0	0	0	0	0	0	9.05E+00	0	0

NHWD = Hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EEE = Exported electrical energy; EET = Exported thermal energy

Note: The use of secondary material (SM) in A4 comes from product wastage during distribution.

References

Standards

EN 15804

EN 15804:2012+A1 2013, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

EN 15804

EN 15804:2012+A2:2019+AC:2021, Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products.

ISO 14025

EN ISO 14025:2011, Environmental labels and declarations — Type III environmental declarations — Principles and procedures.

Further References

Title of the software/database

Title of the software/database. Addition to the title, version. Place: Publisher, Date of publication [Access on access date].

IBU 2021

Institut Bauen und Umwelt e.V.: General Instructions for the EPD programme of Institut Bauen und Umwelt e.V., Version 2.0, Berlin: Institut Bauen und Umwelt e.V., 2021
www.ibu-epd.com

/IBU 2018/

Product Category Rules for Building-Related Products and Services, Part A: Calculation Rules for the Life Cycle Assessment and Requirements on the Project Report, Version 1.7

/IBU 2018/

PCR Guidance-Text for Building-Related Products and Services, Part B: Requirements on the EPD for Pumps for liquids and liquids with solids, Version 1.0

/Machinery Directive/

DIRECTIVE 2006/42/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 17 May 2006 on machinery

/EN 809/

EN 809:1998-10 + A1:2009 Pumps and pump units for liquids - Common safety requirements

/Radio Equipment Directive/

DIRECTIVE 2014/53/EU OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 April 2014 on the harmonisation of the laws of the Member States relating to the making

available on the market of radio equipment

/EN 60335-1/

EN 60335-1:2012-01/AC:2014 + A11:2014 Household and similar electrical appliances - Safety - Part 1: General requirements

/EN 60335-2-51/

EN 60335-2-51:2003-03 + A1:2008 + A2:2012 Household and similar electrical appliances – Safety – Part 2-51: Particular requirements for stationary circulation pumps for heating and service water installations

/EN 62233/

EN 62233:2008-04 Measurement methods for electromagnetic fields of household appliances and similar apparatus with regard to human exposure

/EN 55014-1/

EN 55014-1:2017-04 Electromagnetic compatibility – Requirements for household appliances, electric tools and similar apparatus – Part 1: Emission

/EN 61000-6-2/

EN 61000-6-2:2005-08 Electromagnetic compatibility (EMC) – Part 6-2: Generic standards – Immunity for industrial environments

/EN 61000-3-2/

EN 61000-3-2:2014-08 Electromagnetic compatibility (EMC) – Part 3-2: Limits – Limits for harmonic current emissions (equipment input current = 16 A per phase)

/61000-3-3:2013/

61000-3-3:2013-08 Electromagnetic compatibility (EMC) – Part 3-3: Limits – Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection

/ETSI EN 301 489-1/

ETSI EN 301 489-1 V2.2.0 ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 1: Common technical requirements

/ETSI EN 301 489-17/

ETSI EN 301 489-17 V3.2.0 ElectroMagnetic Compatibility (EMC) standard for radio equipment and services; Part 17: Specific conditions for Broadband Data Transmission Systems

/ETSI EN 300 328 V2.1.1/

ETSI EN 300 328 V2.1.1 Wideband transmission systems; Data transmission equipment operating in the 2,4 GHz ISM band and using wide band modulation techniques

/Ecodesign Directive/

DIRECTIVE 2009/125/EC OF THE EUROPEAN PARLIAMENT

AND OF THE COUNCIL of 21 October 2009 establishing a framework for the setting of ecodesign requirements for energy-related products

/EC 641/2009/

COMMISSION REGULATION (EC) No 641/2009 of 22 July 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for glandless standalone circulators and glandless circulators integrated in products

/EC 622/2012/

COMMISSION REGULATION (EU) No 622/2012 of 11 July 2012 amending Regulation (EC) No 641/2009 with regard to ecodesign requirements for glandless standalone circulators and glandless circulators integrated in products

/EN 16297-1/

EN 16297-1:2012-10 Pumps – Rotodynamic pumps – Glandless circulators – Part 1: General requirements and procedures for testing and calculation of energy efficiency index (EEI)

/EN 16297-2/

EN 16297-2:2012-10 Pumps – Rotodynamic pumps – Glandless circulators – Part 2: Calculation of energy efficiency index (EEI) for standalone circulators

/VDI 2035/

VDI 2035:2005-12 "Vermeidung von Schäden in Warmwasser-Heizungsanlagen"

/ISO 14001/

EN ISO 14001:2015-09 Environmental management systems - Requirements with guidance for use

/CPR/

REGULATION (EU) No 305/2011 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

/GaBi/

GaBi ts 8.7.0.18 (database schema 8007)

/Ecoinvent/

Ecoinvent v3.4



Publisher

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Programme holder

Institut Bauen und Umwelt e.V.
Hegelplatz 1
10117 Berlin
Germany

+49 (0)30 3087748- 0
info@ibu-epd.com
www.ibu-epd.com



Author of the Life Cycle Assessment

Grundfos Holding A/S
Poul Due Jensens Vej 7
8850 Bjerringbro
Denmark

+45 87501400
mhoeeg@grundfos.com
www.grundfos.com



Owner of the Declaration

Grundfos Holding A/S
Poul Due Jensens Vej 7
8850 Bjerringbro
Denmark

+45 87501400
mhoeeg@grundfos.com
www.grundfos.com