



# tesa® Maskeringstape Professional

## Product Information

BNR 56212, 56270, 56271, 56299

### Produktbeskrivelse

tesa® Maskeringstape Professional, vår beste maskeringstape til dags dato. Washipapirets kvalitet garanterer presisjon og gir knivskarpe og rette malingskanter hver gang. Takket være allsidigheten og rivefastheten kleber den seg godt til en rekke overflater og er lett å fjerne.

Med restfri fjerning i opptil 6 måneder etter innendørs påføring og i opptil 2 måneder etter utendørs påføring, etterlater den ingen spor. Oppnå profesjonelle resultater med tesa® Maskeringstape Professional.

### Funksjoner

- For maskering i høy kvalitet til malingsoppgaver – oppnå resultater i ekspertkvalitet \* Originalt washipapir – gir fantastiske og presise, skarpe malingskanter \* Restfri fjerning i opptil 6 måneder innendørs og 2 måneder utendørs
- \* Fleksibel: Tilpasser seg en rekke overflater – laget for innendørs og utendørs maleprosjekter \* Passer til alle typer maling, lakk og glasur \* Enkel å bruke: tesa® Maskeringstape Professional er ekstra rivefast \*\* Unngå bruk av malertape direkte på tregulv

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Produktinnhold

- |                 |               |                  |       |
|-----------------|---------------|------------------|-------|
| • Bæremateriale | Papir (Glatt) | • Total tykkelse | 90 µm |
| • Klebetype     | Akryl         |                  |       |

### Egenskaper / ytelsesverdier

- |                    |         |                 |    |
|--------------------|---------|-----------------|----|
| • Bruddstyrke      | 30 N/cm | • Rivebestandig | Ja |
| • Hand tearability | Ja      |                 |    |

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=56212>