



tesa® Professional 4663 Heavy Duty Duct Tape



Product Information

Kraftig lerretstape

Produktbeskrivelse

tesa® 4663 er en førsteklasses lerretstape med ekstra klebestyrke som er populær blant håndverkere, mest på grunn av sin imponerende rivestyrke og klebestyrke – selv på grove eller møkkete overflater. Lerretstapen består av et PE-belagt tekstillag i kombinasjon med en klebemasse av naturgummi. På grunn av sin bestandighet mot vann, damp og temperaturer kan den multifunksjonelle tapen også brukes til utfordrende oppgaver både innen- og utendørs. Lerretstapen er også enkel å håndtere ettersom den kan rives langs en rett kant for hånd.

Funksjoner

- Innen- og utendørs bruk
- Forsegling av rør og kanaler
- Feste av kraftige konstruksjoner som murarbeid, betong, puss og tre
- Feste av bygge- og beskyttelsesfilm
- Lukking og pakking

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Produktinnhold

- | | | | |
|-----------------|---|------------------|--------|
| • Bæremateriale | PE-belagt tekstil, PE-extrudert tekstil | • Total tykkelse | 300 µm |
| • Klebetype | Naturgummi | | |

Egenskaper / ytelsesverdier

- | | | | |
|-----------------------------|--------------|--------------------|--------------|
| • Slitstyrkebestandighet | medium, good | • Fuktbestandighet | good |
| • Bruddforlengelse | 15 % | • Hand tearability | good |
| • Bruddstyrke | 50 N/cm | • Water resistance | medium, good |
| • Aldringsbestandighet (UV) | good | | |



tesa[®] Professional 4663 Heavy Duty Duct Tape

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?mp=04663>