



### DECLARATION OF PERFORMANCE

In according to Annex III of the Regulation (EU) No 305/2011

No. **P0856** version 1

1. Unique identification code of the product-type:

**P0856 BOSTIK ACRYL POWER FLEX**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

**Batch number: see product packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Sealant for facade for interior and exterior application**

**EN 15651-1: F EXT-INT**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**Bostik AB, Box 903, 251 09 Helsingborg, Sverige**

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not relevant**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3  
System 3 for reaction to fire**

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

A notified testing laboratory SP Technical Research Institute of Sweden (0402), has performed the determination of the product-type on the basis of ITT under system 3 and performed fire tests according to systems 3 and issued corresponding test report.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not relevant**

9. Declared performance

9.a. according to EN 15651-1:2012 F EXT –INT

Conditioning: procedure A  
Substrates: Concrete

Reaction to fire (EN 13501-1)	class E
Release of dangerous substances	NPD
Resistance to flow (EN ISO 7390)	≤ 3 mm
Loss of volume (EN ISO 10563)	≤ 25 %
Adhesion/elongation under pretension and after immersion in water (EN ISO 10590)	Passed (NF)
Resilience (EN ISO 7389)	≥ 70 %
Tensile properties at -30 °C (EN ISO 8340)	≤ 0,9 MPa
Tensile properties under pretension at -30 °C (EN ISO 8340)	NPD
Durability	passed (NF)

NPD = No Performance Determined

Where pursuant to Article 37 or 38 the Specific Technical Documentation has been used, the requirements with which the product complies:

**Not relevant**

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:  
Helsingborg 2017-05-05



.....  
Robert Massey, CEO