

Technical data – Verdo

Combustion chamber type	Open
External air supply	NO
Notified body	1450
CO Emission (%)	0,14
Nominal output (kW)	7
Efficiency (%)	70
Net weight (kg)	66
Fumes outlet diameter (mm)	120
Width (cm)	41
Height (cm)	82,5
Depth (cm)	40
Burning chamber width (cm)	31,0
Burning chamber depth (cm)	28,5
Glass dimension (cm)	17,5x19,0x0,4
Seasonal efficiency (%)	60
PM (mg/m ³)	41
OGC (mg/m ³)	118
CO (mg/m ³)	1750
Nox (mg/m ³)	130
Chimney draft (Pa)	12
Batch size	2x20 cm
Fuel usage (kg/h)	2,5
EEl	92
Energy class	A
Water circuit output	0,0
Comply with regulation	EN 13240:2001/A2:2004 EN 13240:2001/AC:2006 EN 13240:2001/A2:2004/AC:2007
Comply with regulation 1185/2015 and 1186/2015 (ECODESIGN 2022)	Yes
Max. fuel batch (kg)	2,5
Distance from flammable element FRONT (cm)	80
Distance from flammable elements side (cm)	40
Distance from flammable elements back (cm)	40
Distance from flammable elements top (cm)	80