

YTELSESERKLÆRING

Nr. 2040-CPR-171011

1. Varetypens unike identifikasjonskode: **22150403 KRYSSFINER BB/X**
2. Tilsiktet bruksområde: **Kryssfinerplate for innvendig og utvendig bruk, komponent i ikke bærende element. Dimensjoner fra 4 mm til 30 mm.**
3. Produsent: **Sklejka – EKO S.A. str. Reymonta 35, 63-400 Ostrów Wielkopolski - Poland**
4. Autorisert representant (hvis relevant): **ikke relevant.**
5. System eller systemer for vurdering og verifikasjon av byggevarers ytelser: **System 4**
6. Harmonisert produktstandard: **Produktstandard EN 13986:2006, - EN 636:2005**
Teknisk kontrollorgan: **MPA Eberswald - 22150403**

7. Angitte ytelser:

Densitet	550 -750 kg/m³
Bøyefasthet	Langsgående 50-100 N/mm²– Tverrgående 30-70 N/mm², jfr. NS-EN 13986:2006
Bøyeelastisitetmodul	Langsgående 5000-11000 N/mm² – Tverrgående 3500-8000N/mm², jfr. NS-EN 13986:2006
Formaldehyd klasse	E1 CARB ≤0,5 mg/m²h
Brannteknisk klasse	D-s2, d0 (EN 13986 Tab. 8 for density ≥400kg/m³ and thickness ≥9mm)
Bindemiddel kvalitet	Klasse 3, jfr. NS-EN 335
Fuktmotstand	Innvendig og utvendig bruksområde*. Bruksklasse 3, jfr. NS-EN 335:2013 <small>* Produktet er i klimaklasse 3 iht. EN 335 og må behandles før utvendigbruk</small>

8. Ytelser for denne byggevaren, som er anført ovenfor, er i overensstemmelse med de angitte ytelsene. Denne ytelseserklæringen er utarbeidet i overensstemmelse med forordning (EU) nr. 305/2011 under eneansvar til produsenten, som er anført ovenfor.

Underskrevet for produsenten og på dennes vegne av:

Larvik,
11.10.17

Jarle Anholt
Teknisk sjef



DECLARATION OF PERFORMANCE

No. 2/2014

1. Product-type:

**Plywood for use as non-structural components in interior and exterior conditions,
technical classes EN 636-1 G; -2 G; -3 G, from hard- and soft-wood, thickness from 4 mm to 30 mm**

2. Identification of product:

Interior plywood and exterior plywood

3. Intended use or uses of the construction product:

Interior plywood can be used in construction as non-structural components in interior and humid conditions

Exterior plywood can be used in construction as non-structural components in exterior conditions

4. Name and address of the manufacturer:

FRITZ SKLEJKA – EKO S.A.
str. Reymonta 35
63-400 Ostrów Wielkopolski
POLAND
ENGROS

5. Name and contact address of the authorised representative:

Not applicable

6. System of assessment and verification of constancy of performance of the construction product (AVCP):

System 4

7. Notified Body's task(s), if applicable:

Not applicable

performed:

Not applicable

under system:

System 4

and issued:

Factory Production Control and Internal tests reports

8. Declared performance

Essential characteristics	Performance	Harmonized technical specification	
Density	550 ÷ 750 kg/m ³	EN 13986:2006 Wood based panels for use in construction Characteristics, evaluation of conformity and marking	
Humidity	5 ÷ 12 %		
Bending strength along / across fibers	50 ÷ 100 MPa / 30 ÷ 70 MPa		
Modulus of elasticity along / across fibers	5000 ÷ 11000 MPa / 3500 ÷ 8000 MPa		
Release of formaldehyde	Class E1 CARB ≤ 0,5 mg/m ² h		
Reaction to fire	D-s2,d0 (EN 13986 Tab. 8 for density ≥ 400 kg/m ³ and thickness ≥ 9 mm)		
Water vapour permeability	Interpolated from EN 13986 tab 9 for density 600 kg/m ³		
	wet cup		80 dry cup 210
Airborne sound insulation	Calculated per EN13986 section 5.10 using the formula (t = thickness in mm) $R=13 \times \lg(0,600 \times t)+14$		
	EN 13986 tab. 10		
Sound absorption coefficient	250 – 500 Hz: 0,10 1000 – 2000 Hz: 0,30		
	Interpolated from EN 13986 tab 11 for density 600 kg/m ³ $\lambda=0,15 \text{ W}/(\text{m}\cdot\text{K})$		
Thermal conductivity	λ=0,15 W/(m·K)		
Biological durability	Hazard class 1; 2; 3*		
Content of pentachlorophenol (PCP)	EN 13986 section 5.18	< 5 ppm	

* The conditions of Service Class 3 may correspond to the biological Hazard Class 3 to EN 335, for which this product cannot be used without further treatment and/or appropriate design.

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.
22150403

Signed for and on behalf of the manufacturer by:

Błażej Kidoń / spec. Technologist

(name and function)

17.09.2014 Ostrów Wielkopolski

(place and date of issue)

Specjalista
technolog
Błażej Kidoń
Błażej Kidoń

(signature)