




## FSN-TPG (fermacell)



- Material: Steel
- Coating: phosphated
- Drive: Cross drive PH
- Thread: HiLo thread
- Screw head: Small countersunk head 60°
- Suitability: For gypsum fibreboard (fermacell boards) on metal profiles up to 0,7 mm in thickness without pre-drilling
- Specially: collated, belt system for strip screws




Diameter	Length	Full thread length	Head-Ø	Drive	Art. No.	Sales unit	Outer carton			GTIN (EAN Code)
d	l	lg	dk			[pcs]	[pcs]			
[mm]	[mm]	[mm]	[mm]							
<b>3.9</b>	19	13	6.8	PH 2	<b>665095</b>	1.000	8.000			40 4896 2055 184
	22	16	6.8	PH 2	<b>665081</b>	1.000	8.000			40 4896 2052 831
	30	24	6.8	PH 2	<b>665098</b>	1.000	6.000			40 4896 2055 214
	35	29	6.8	PH 2	<b>665084</b>	1.000	4.000			40 4896 2052 862
	45	39	6.8	PH 2	<b>665101</b>	1.000	4.000			40 4896 2055 245
	55	49	6.8	PH 2	<b>665087</b>	600	2.400			40 4896 2052 893

## FSN-TPGM (fermacell)

- Material: Steel
- Coating: phosphated
- Drive: Cross drive PH
- Thread: HiLo thread
- Screw head: Small countersunk head 60°
- Suitability: For gypsum fibreboard (fermacell boards) on metal profiles up to 0,7 mm in thickness without pre-drilling
- Specially: collated, belt system for strip screws



Diameter	Length	Full thread length	Head-Ø	Drive	Art. No.	Sales unit	Outer carton			GTIN (EAN Code)
d	l	lg	dk			[pcs]	[pcs]			
[mm]	[mm]	[mm]	[mm]							
<b>3.9</b>	30	24	6.8	PH 2	<b>665103</b>	1.000	4.000			40 4896 2196 665
	45	39	6.8	PH 2	<b>665104</b>	1.000	4.000			40 4896 2196 672