






**NeoFlow trykkreduksjonsventil POM-C  
DN200 - DN300 / Trykkområde < 13.5 bar**

- Nominelt trykk: PN16
- Tilkoblingsmåte: Wafer design
- Pakningsmateriale: EPDM
- Materiale i huset: POM-C
- Komponenter: Rustfritt stål
- Medie: Vann
- Utviklet i samarbeid med OFUI

DN	PN	Set pressure range (bar)	Kode	Vekt (kg)	D (mm)	Lmax (mm)	L1 (mm)	L2 (mm)	Hmax (mm)	Wmax (mm)
200	16	1,0 - 13,5	<b>193 173 420</b>	22,3	275	298	149,0	149,0	398	346
250	16	1,0 - 13,5	<b>193 173 422</b>	34,8	328	348	174,0	174,0	451	399
300	16	1,0 - 13,5	<b>193 173 423</b>	71,0	378	398	199,0	199,0	501	449



De tekniske data er uforpliktende. De er hverken uttrykk for garanterte egenskaper, funksjoner eller for garantert holdbarhet. Rett til endringer forbeholdes. Våre generelle salgsbetingelser er gjeldene.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>