ENVIRONMENTAL PRODUCT DECLARATION

as per ISO 14025 and EN 15804

Owner of the Declaration	Knauf Gips KG
Programme holder	Institut Bauen und Umwelt e.V. (IBU)
Publisher	Institut Bauen und Umwelt e.V. (IBU)
Declaration number	EPD-KNA-20160111-IBA1-EN
ECO EPD Ref. No.	ECO-00000419
Issue date	21.02.2017
Valid to	20.02.2022

Knauf Safeboard GKF **Knauf Gips KG**

Too



www.bau-umwelt.com / https://epd-online.com







1. General Information

Knauf Gips KG	Knauf Safeboard GKF	
Programme holder IBU - Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Germany	Owner of the Declaration Knauf Gips KG Am Bahnhof 7 97346 Iphofen Germany	
Declaration number EPD-KNA-20160111-IBA1-EN	Declared product / Declared unit Plasterboard Knauf Safeboard Type GKF according to /DIN 18180:2014/ respectively DF according to /EN 520:2009/, 1 m ² , board thickness 12.5 mm, weight of board ca. 17.8 kg	
This Declaration is based on the Product Category Rules: Plasterboard, 07.2014 (PCR tested and approved by the SVR) Issue date	Scope: This EPD is valid for the plasterboard Knauf Safeboard GKF. This plasterboard is manufactured in Germany. The owner of the declaration shall be liable for the underlying information and evidence; the IBU shall not be liable with respect to manufacturer information, life	
21.02.2017 Valid to 20.02.2022	cycle assessment data and evidences.	
/	Verification	
Wiemanes	The CEN Norm /EN 15804/ serves as the core PCR Independent verification of the declaration according to /ISO 14025/	
Prof. DrIng. Horst J. Bossenmayer (President of Institut Bauen und Umwelt e.V.)	internally x externally	
Lelmann	C. Bacher	
Dr. Burkhart Lehmann (Managing Director IBU)	Christina Bocher (Independent verifier appointed by SVR)	

Product 2.

2.1 Product description Plasterboards Knauf Safeboard GKF are lead-free Xray shielding boards for X-ray facilities.

Application 2.2

Knauf Safeboard X-ray shielding boards are used for room-enclosing constructions of X-ray facilities for radiation shielding for the following systems:

- X-Ray shield ceilings •
- X-Ray shield partitions •
- X-Ray shield furrings ٠

2.3 **Technical Data**

The following technical data in condition on delivery is relevant for the declared product:

Constructional data

Name	Value	Unit
Gross density	≥ 1400	kg/m ³
Flexural breaking load (longitudinal) according to /DIN 18180:2014/ as per Gips- Datenbuch	≥ 610	N

Flexural breaking load (transversal) according to /DIN 18180:2014/ as per Gips- Datenbuch	≥ 210	Ν
Modulus of elasticity longitudinal, according to /DIN 18180:2014/, as per Gips-Datenbuch	≥ 2800	N/mm²
Modulus of elasticity transversal, according to /DIN 18180:2014/, as per Gips-Datenbuch	≥ 2200	N/mm²
Thermal conductivity according to /EN ISO 10456:2010/	0.26	W/(mK)
Specific heat capacity at 20 °C	0.73	kJ/kgK
Water vapour diffusion resistance factor (dry), according to /EN ISO 10456:2010/	10	-
Water vapour diffusion resistance factor (wet), according to /EN ISO 10456:2010/	4	-
Moisture content at 20 °C, 65% humidity according to Gips- Datenbuch	0.6 - 1	M%
Elongation/Vibration when humidity changes by 30% (20°C) according to /EN 318:2002/, per 1 % change of relative humidity	0.005 - 0.008	mm/m



Eurther information is available in the technical		
Datenbuch		
saturated) according to Gips-	0.35	%
Swelling (air-dry to water-		

Further information is available in the technical data sheet K762.de_ENG under www.knauf.de.

2.4 Application rules

Plasterboards Knauf Safeboard GKF require a declaration of performance as well as a CE marking in the EU/EFTA region according to EU Construction Products Regulation /CPR2011/. Further national application rules are to be observed.

In Germany, the following standards apply:

- /DIN 18180:2014/ Gypsum plasterboards Types and requirements
- /EN 520:2009/ Gypsum plasterboards -Definitions, requirements and test methods;
- /DIN 18181:2008/ Gypsum plasterboards for building construction Application
- /DIN 4103-1:2014/ Internal non-loadbearing partitions – Part 1: Requirements and verification
- /DIN 4103-4:1988/ Internal non-loadbearing partitions; partitions with timber framing
- /DIN 18183-1:2009/ Partitions and wall linings with gypsum boards on metal framing Part 1: Cladding with gypsum plasterboards
- /DIN 18168-1:2007/ Ceiling linings and suspended ceilings with gypsum plasterboards Part 1: Requirements for construction
- /DIN18168-2:2008/ Ceiling linings and suspended ceilings with gypsum plasterboards - Part 2: Verification of the loadcarrying capacity of metal sub-constructions and metal suspending rods

Plasterboards Knauf Safeboard GKF are processed in accordance with the relevant standards and the Knauf brochure ST01 "Knauf Sicherheitstechnik", which is available under www.knauf.de.

2.5 Delivery status

Plasterboards Knauf Safeboard GKF are delivered with a board thickness of 12.5 mm as well as a size of 2500 mm x 625 mm.

2.6 Base materials / Ancillary materials

Plasterboards Knauf Safeboard GFK consist to more than 90 % of set gypsum and baryte, covered with a board liner (< 3 %). Furthermore, the plasterboards contain small amounts (< 5 %) of starch, tensides, fiber additives as well as non-organic color pigments.

No substances classified according to the candidate list of Substances of Very High Concern (SVHC) /ECHA 2016/ are used in the product with an amount of more than 0.1 w/w%.

2.7 Manufacture

The components of plasterboards Knauf Safeboard GKF are suspended in water and spread on a continuous sheet of board liner (visible face, lower layer). Beforehand, the board liner is cut on the sides for edge shaping. The slurry is covered with a second sheet of board liner (back surface) in the forming station and the edges of the visible face board liner are flipped upwards. On the subsequent board line the gypsum is setting continuously and is dried in a multi-level drier to the permitted residual moisture level. Drying is followed by the cutting of the boards to the desired lengths.

All processes within the company are certified according to /ISO 9001:2008/.

2.8 Environment and health during manufacturing

The production of Knauf Safeboard GKF is subject to the German immission control regulations /BImSchG/. CO2 emissions are measured due to CO2 emissions trading. The German manufacturing sites of Knauf Gips KG are certified according to /ISO 50001:2011/ as well as certified with the occupational safety standard "Sicher mit System" (Systematic Safety) from the German trade association /BG RCI/.

Gypsum from the flue-gas desulphurization plants of coal-fired power stations is used in addition to natural gypsum. Production waste as well as dust from the filtration plants are recycled internally and fed back into the production of plasterboards.

2.9 Product processing/Installation

Storage

Plasterboards Knauf Safeboard GKF should be stored in closed rooms under dust-free and dry conditions in a horizontal position.

Application

During application, dust thresholds are to be observed according to /TRGS 900:2006/ and /TRGS 559:2010/. The application and installation should follow the instruction sheets provided under www.knauf.de (e.g., W11, D11) respectively the Knauf brochure ST01 "Knauf Sicherheitstechnik".

Like in other fire protection boards (compare /EPD-BVG20140076-IAG1-DE/), endless filament glass fibres are used in the manufacturing of plasterboards Knauf Safeboard GKF. These fibres do not fan out during application and therefore no fibre dusts according to /TRGS 521:2008/ emerge.

2.10 Packaging

Plasterboards Knauf Safeboard GKF are piled up on reusable pallets, and are protected against damage by sheets of cardboard, steel angles, and by stretch film. Pallets are re-used whereas all other packing materials are externally recycled/disposed of.

2.11 Condition of use

Plasterboards Knauf Safeboard GKF are used for room-enclosing constructions of X-ray facilities for radiation shielding. They feature high levels of robustness against mechanical impacts and serve increased demands on fire protection.



There is no change in the chemical composition during use.

2.12 Environment and health during use

Plasterboards Knauf Safeboard GKF are able to shield effectively against X-rays. The respective values of lead equivalence according to /DIN 6812:2013/ are available in the technical data sheet under www.knauf.de.

According to emission test of the Fraunhofer Institute for Wood Research Wilhelm-Klauditz-Institut WKI following the AgBB test scheme /WKI2011/, no hazardous substances are emitted above permissible thresholds during use.

2.13 Reference service life

There was no reference service life determined according to /ISO 15686-1:2011/. However, a reference service life of 50 years can be considered for gypsum plasterboards according to the Guideline for Sustainable Building /BBSR2011/ . There are no influences on ageing of plasterboards Knauf Safeboard GKF during use following the established engineering practice.

2.14 Extraordinary effects

Fire

The reaction to fire of plasterboards Knauf Safeboard GKF is classified as follows according to /EN 520:2009/ in conjunction with /EN 13501-1:2010/:

Fire safety regulations

Name	Value
Building material class	A2
Burning droplets	d0
Smoke gas development	s1

Water

Plasterboards Knauf Safeboard GKF show a small tendency to swell or shrink within changes of the climatic conditions. However, a permanent exposure to wet conditions or relative humidities may lead to a decrease in strength. An instruction sheet about restoration of flood damage is available under www.knauf.de /BSDH2013/. Information about the removal of flood damage can be downloaded from www.gypsum.org.

Mechanical destruction

Minor damages on plasterboards Knauf Safeboard GKF can be mended with suitable gypsum based filling materials, *e.g.*, Knauf Safeboard Filler. The installation with screws and brackets allows an easy exchange of

3. LCA: Calculation rules

3.1 Declared Unit

The declared unit is 1 m^2 of plasterboard Knauf Safeboard GKF with a thickness of 12.5 mm, weight approx. 17.8 kg/m².

Declared Unit

Name Val	ue Unit

heavily damaged boards. In this case, the substructure should be examined, too, and replaced if necessary.

2.15 Re-use phase

Re-use

Once plasterboards Knauf Safeboard GKF are installed, they are not suited for re-use in an unchanged way. Prior to collection, plasterboards Knauf Safeboard GKF should be separated from other used building materials and pruned of foreign matter, *e.g.*, metals from the substructure already on site for easier recycling or disposal.

Further use

Residual materials from new plasterboards Knauf Safeboard GKF, *e.g.*, from cut waste at the building site, can be further used after processing, *e.g.*, crushing and if necessary, removal of board liner. They are suited for reclamation of mining sites, as soil conditioner, fertilizer component or as setting and hardening regulating agent for cement. However, this procedure requires agreement with the purchaser and consideration of national regulations.

Recycling

Due to the reversible absorption and dehydration of water of crystallization, gypsum products can be recycled by suitable processes. Therefore, gypsum waste should be collected as mono-fraction and processed in gypsum recycling plants. For recycling, the adherent board liner is peeled from the gypsum core and returned to the paper recycling system or thermally utilized. Remaining metallic components are removed with magnetic separators and recycled as scrap. Afterwards, the gypsum core is fed into the recycling plant and crushed. The resulting recycled gypsum can be re-used for the production of gypsum based building materials.

2.16 Disposal

X-ray shielding boards Knauf Safeboard GKF have to be disposed of in compliance with the following waste codes of the European Waste Catalogue /EWC/:

17 09 04 mixed construction and demolition wastes other than those mentioned in 17 09 01, 17 09 02 and 17 09 03.

National disposal guidelines have to be observed. In Germany, plasterboards Knauf Safeboard GKF are to be disposed of at landfills of landfill category 1 or higher according to the regulation of landfills /DepV2009/.

2.17 Further information

Further information about plasterboards Knauf Safeboard GKF, *e.g.*, technical data sheets or material safety data sheets are available at www.knauf.de or from the Technical Advisory Service Knauf Direct (knauf-direkt@knauf.de).

Declared unit	1	m²
Conversion factor to 1 kg	0.056	-

3.2 System boundary

This Environmental Product Declaration contains the manufacturing (modules A1-A3), the transport from manufacturing to the building site (A4), the transport of



plasterboards Knauf Safeboard GKF to the landfill site or the recycling plant (module C2) as well as two scenarios for the End of Life (scenario 1: landfilling – module C4/1 scenario 2: recycling – modules C3/2 and C4/2, credits for the recycled gypsum core in module D/2). Accordingly, the EPD is a cradle-to-gate declaration with options.

During manufacturing, the provision and transport of raw materials, the manufacturing of the board including the provision of energy, emissions as well as the provision of packaging materials are considered. The modelling of recycling (scenario 2) includes the separation of materials, the feedback of board liner to the waste paper recycling system, and the processing of the gypsum core. Residual non-recyclable components are disposed of.

3.3 Estimates and assumptions

Baryte is substituted by an own model in the life cycle assessment of the manufacturing of Knauf Safeboard GKF since the respective GaBi dataset not only includes the extraction of the raw material but also the beneficiation to a highly purified barium sulphate which can be used as a white pigment. Therefore, the environmental impacts resulting from this upstream process in the GaBi dataset would be significantly higher than in reality.

For transport, a general payload of 50 % is assumed. Transport to the buildings site (module A4) as well as transport from the building site to the collecting site or landfill (module C4) is calculated with a standard distance of 100 km. This way, the user of the Environmental Product Declaration can convert the distances of the modules A4 and C2 to the specific distance by extrapolation.

Further assumptions are made for the modelling of the recycling of plasterboards Knauf Safeboard GKF. These are described in more detail in section 4.

3.4 Cut-off criteria

All raw materials for the manufacturing of plasterboards Knauf Safeboard GKF, the required energy, water and the resulting emissions are considered in the life cycle assessment. That way, recipe components with a share even smaller than 1 % are included. All neglected processes contribute less than 5 % to the total mass or less than 5 % to the total energy consumption.

3.5 Background data

For modelling the LCA the software GaBi 7 from thinkstep/GaBi2016/ is used. The LCA is based on production data. Datasets for Germany are used for the life cycle inventory as much as possible. This is especially true for the provision of electricity and thermal energy.

3.6 Data quality

The LCA of plasterboards Knauf Safeboard GKF is modelled by using GaBi datasets, exclusively. Besides two exceptions with only minor influence on the overall life cycle impacts of Knauf Safeboard GKF, background data are no older than 6 years. Therefore, the data quality is considered to be good.

3.7 Period under review

The modelling is based on the annual production of Knauf Safeboard GKF in 2015.

3.8 Allocation

Allocations are avoided in the modelling. Beyond that, allocations are only applied in the background data.

3.9 Comparability

Basically, a comparison or an evaluation of EPD data is only possible if all the data sets to be compared were created according to /EN 15804/ and the building context, respectively the product-specific characteristics of performance, are taken into account.

4. LCA: Scenarios and additional technical information

Product Stage (A1-A3)

Supply of raw materials

Plasterboards Knauf Safeboard GKF consist of a gypsum core and barytes which is reinforced with mineral fillers and covered with board liner. For its identification the core of Knauf Safeboard GKF is coloured in yellow. The natural gypsum is mainly extracted from open-cast mining in close vicinity to the manufacturing site. Furthermore, gypsum from the flue-gas desulphurization of coal-fired power stations (FGD gypsum) is used as a raw material. Board liner for the covering of gypsum core is produced from recycled waste paper which is partly certified by FSC.

Additives are added for an easier processing and a fine adjustment of properties of plasterboards Knauf Safeboard GKF. These additives add up to less than 5 % of the overall mass of the product.

Transport of raw materials

Natural gypsum is extracted from mines close to the manufacturing sites of plasterboard Knauf Safeboard GKF. Accordingly, transport distances are short and

trucks can be used. FGD gypsum is transported by freight train from coal-fired power plants. The heavy spar is produced predominantly in Germany and also delivered by truck. In parts, baryte can also be delivered from overseas by container ship. Further raw materials are supplied by truck from manufacturers within Germany or from neighbouring countries.

Manufacturing

Natural gypsum as well as gypsum from the flue-gas desulphurization is calcinated prior to the mixing with other components. FGD gypsum is usually delivered as damp material and, thus, must be dried before calcination.

Stucco, mineral fillers and additives are mixed with water and processed as described in section 2.7. The addition of water allows the incorporation of water of crystallization into the molecules of calcium sulphate. By the addition of water, gypsum becomes settled and hardened. Redundant surface water is removed in a multi-level dryer.

Transport to building site (A4)

For transport, a standard distance of 100 km by truck



is assumed. This declaration facilitates the extrapolation of the results in A4 to the real distance.

End of Life (C1-C4, D)

In the LCA, two scenarios for end of life were calculated: disposal (landfilling) and recycling, respectively. The de-construction (module C1) is not declared in this EPD. Analogous to A4, the results of a transport over 100 km by truck are calculated.

Both scenarios are calculated as 100 %-scenarios, to facilitate the individual calculations of disposal- and recovery-scenarios by the user of this Environmental Product Declaration. In scenario 1 a 100 % landfilling of Knauf Safeboard GKF was assumed without further processing. The related module C3 is characterised with "/1".

Recycling with a complete separation of both components, gypsum core and board liner, is modelled in scenario 2. The related modules C3, C4 and D are labelled with "/2".

Transport to building site (A4)

Name	Value	Unit	
Litres of fuel (Diesel, density: 0.83 kg/L)	0.0342	l/100km	
Transport distance	100	km	
Capacity utilisation (including empty runs)	50	%	
Gross density of products transported	≥ 1400	kg/m³	
Capacity utilisation volume factor	0.215	-	

Transport (C2)

Name	Value	Unit
Litres of fuel (Diesel, density: 0.83 kg/L)	0.0340	l/100 km
Transport distance	100	km
Capacity utilisation (including empty runs)	50	%
Gross density of products transported	≥ 1400	kg/m³
Capacity utilisation volume factor	0.215	-

Scenario 1: Landfilling (C4/1)

Name	Value	Unit
Collected separately	17.8	kg
Collected as mixed construction waste	-	kg
Reuse	-	kg
Recycling	-	kg
Energy recovery	-	kg
Landfilling	17.8	kg

Scenario 2: Recycling (C3/2, C4/2)

Name	Value	Unit
Collected separately	17.8	kg
Collected as mixed construction waste	-	kg
Reuse	-	kg
Recycling	16.9	kg
Energy recovery	-	kg
Landfilling	0.9	kg

Reuse-, recover- and recycling potential (D/2), only Scenario 2

Name	Value	Unit
Re-utilisation recycling gypsum	100	%
(assumption: substitution of 50 %		

natural gypsum and 50 % FGD	
gypsum)	



5. LCA: Results

Note: Two scenarios for the end of life stage were considered as 100 % scenario, each.

Scenario 1: Landfilling (module C4/1)

Scenario 2: Recycling und landfilling of non-recyclable fractions as well as the credit for recycled materials (modules C3/2, C4/2, D/2).

DESC	RIPT	ION C	F THE	SYS1	STEM BOUNDARY (X = INCLUDED IN LCA;					MND = MODULE NOT DECLARED)						
							BENEFITS AND									
	0013	TAGL	STA	AGE			0.	SE STA	JL							SYSTEM
														В		BOUNDARIES
			e							gy	er			b		
a		ng	ite -			e		t I	ent	Jer	/ate	lio		Sin		
∠ teri	Б	üni	e S	ply		and	. 	ne	Ĕ	e	>	ior l	Б Б	l So	sal 3	- and a lai
ppl	dsu	act	무무	E E	lse	ená	ba	Cel	ish	se	se	olit	ds	ĕ	ğ	use ove ent
su r	rar	Juf	p D	SS		int	Re	pla	l dr	n tio	atic I		rar	0 0	Disl	octo Ce
Ra	F	Jar	ate			Ма		Re	(sefi	era	er:	d d		ast		
		2								ð	ð			l Š		
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
х	Х	Х	Х	MND	MND	MND	MND	MND	MND	MND	MNE	MND	Х	X	Х	Х
RESU	JLTS	OF TH	IE LCA	- EN'	VIRON	MENT	AL IM	PACT	: 1 m²	Plaste	erboa	rd Knau	uf Safe	eboarc	I GKF	
Param	U	nit	A	1-A3		A4		C2		C3/2		C4/1		C4/2	2	D/2
eter	Ika CC		46	25+0	1	21 - 1		1 20 - 1		1 00E 1		2 00E	1	1 445	2	6 70E 2
ODP	Ika CFC	<u>2-⊏q.j</u> 211-Ea.1	1.0	2E+0 3E-10	2.4	46E-13		2.44E-13	_	6.53E-12	2	2.89E-1	2	1.44E	-13	-6.76E-13
AP	[kg SC	D ₂ -Eq.]	3.0	4E-2	3.	17E-4		3.15E-4		1.57E-4		1.73E-3	3	8.66E	-5	-1.59E-4
EP	[kg (PO	₀₄) ³ -Eq.]	3.6	2E-3	7	97E-5		7.91E-5		2.49E-5		2.36E-4	4	1.18E	-5	-3.42E-5
	[kg etne	h-Eq.]	1.5	02E-3	-1	.08E-4		-1.07E-4 8 93E-9		1.16E-5		1.66E-4	.66E-4		-0 -0	-1.//E-5 -3.07E-4
ADPF	[N	<u>u Lq.j</u> 1J]	6.3	6E+1	1.	62E+0	-	1.61E+0		1.07E+0)	3.76E+	0) <u>4.96E-9</u>) 1.88E-1		-7.11E-1
	GWF	P = Glob	al warmir	ng potent	ial; ODP	= Deplet	ion poter	ntial of th	e stratos	pheric oz	one lay	er; AP = A	cidificatio	on potenti	al of land	and water; EP =
Captio	n Eutro	ophicatic	on potenti	ial; POCI	P = Form	ation pot	ential of	troposph	eric ozor	e photoc	hemica	l oxidants;	ADPE =	Abiotic d	epletion	potential for non-
DEGI							E 1 m	² Dias	torbo	ard Kn		afohoa	rd CK	F		
								00								52
Parame	eter (Jnit	A1-4	43	P	4		62		63/2		C4/1		64/2		D/2
PER		MJ	6.72E	+0	1.10)E-1)E+0	1.	.09E-1	_	5.50E-1		4.43E-1		2.21E-2		-5.27E-2
PER	T I	MJ]	9.77E	+0	1.10)E-1	1.	.09E-1		5.50E-1		4.43E-1		2.21E-2		-5.27E-2
PENF	RE [MJ]	6.65E	+1	1.62	2E+0	1.	61E+0		1.41E+0		3.89E+0) 1.95E-1		-1	-7.39E-1
PENR	M [MJ]	4.17E	-1	0.00	E+0	1					IND	0 1 05E 1		1	
SM		ivij [ka]	0.09E	+0	1.02 IN	<u>E+0</u>	1.	IND	_	I.4 IE+0		3.69E+0	,	1.95E-1		-7.39E-1 1.65E+1
RSF		MJ]	IND)	IN	ID		IND		IND		IND	IND IND			IND
NRS	F [MJ]	INE)	<u>IN</u>	ID		IND		IND		IND	IND IND		-	IND
FVV			2.04E	2	1.0t	0E-4	1.	.65E-4		4.13E-4		7.93E-4		3.96E	-5	-1.34E-4
	renev	vable pr	rimary er	nergy res	sources	used as	raw mat	erials; P	ERT = T	otal use	of ren	ewable pri	mary en	ergy res	ources;	PENRE = Use of
Captio	n n	on-rene	wable pr	imary er	nergy ex	cluding r	non-rene	wable p	rimary e	nergy re	source	s used as	raw ma	terials; P	ENRM :	= Use of non-
	of se	condary	rimary ei / materia	nergy re I RSF =	sources	used as renewah	raw ma le secor	terials; F ndary fue	'ENRT =	F = Use	of non	on-renewa -renewabl	bie prim e secon	lary ener dary fuel	s [.] FW =	Urces; SM = Use
		oonaary	matoria	.,	000 01	Chevras			wate	r			000001		0,111	
RESU	JLTS		IE LCA	A – OU	TPUT	FLOW	IS AN	D WA	STE C	ATEG	ORIE	S:				
1 m² l	Plaste	erboar	'd Kna	ut Saf	eboar	d GKF	1									
Parame	eter l	Jnit	A1-4	43	4	4		C2		C3/2		C4/1		C4/2	2	D/2
	ו מ	kg] kal	1.10E	<u>6</u> -+1	2.09)E-7 3E-2	2.	07E-7		1.66E-9 1.55E+0		8.91E-8		4.45E	-9	-1.65E-8 -1.37E-1
RWD		kg]	1.32E	-3	2.20)E-6	2	.18E-6		1.32E-4		5.38E-5		2.69E	-6	-1.12E-5
CRL	ı İ	[kg]	INE)	IN	ID		IND		IND		IND		IND		IND
MFF	2 1	[kg]	INE)	IN IN			IND		1.69E+1		IND		IND		IND
	< : n	KGJ M.II))		חו חו	+				—			IND NN		
EET		MJ])		ID	L	IND		IND		IND		IND		IND
	HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components															
Captio	n fo	r re-use	; MFR =	Material	s for rec	ycling; N	1ER = M	laterials	for ener	gy recov	ery; EE	E = Expo	rted elec	ctrical en	ergy; EE	E = Exported
L								u	ionnai e	nergy						

6. LCA: Interpretation

In **scenario 1: landfilling** the environmental impact potentials and LCI contributions result to more than 90 % from the manufacturing (A1-A3) of plasterboard

Knauf Safeboard GKF (exceptions: POCP 80 %, HWD 69 %, NHWD 38 %). During manufacturing (A1-A3), the provision of raw materials significantly influences



indicators ODP (52 %), ADPE (100 %), PERT (51 %), FW (54 %), as well as NHWD (65 %) and RWD (63 %) significantly. The transport of raw materials dominates the indicators AP (78 %), EP (72 %), POCP (55 %), and HWD (86 %). In addition, the manufacturing of the board contributes to the indicators GWP, ODP, ADPF, PERT, PENRT, and FW by 41-50 %, as well as to the indicators NHWD and RWD to approx. 35 %, each. Transports in A4 and C2 contribute to a maximum of 3 % each to the results due the assumed transport distance of 100 km (exceptions: HWD 13 %, credit in POCP of 6 %). However, landfilling of plasterboards contributes a maximum of 9 % to the environmental impact potentials and LCI parameters (exception: NHWD 63 %). Similar results are obtained for **scenario 2: recycling.** In this scenario environmental impacts and LCI contributions result mainly from the manufacturing of Knauf Safeboard GKF, too. However, a credit of 43 % is obtained for ADPE due to the recycling of the gypsum core. Due to the small contributions of natural and FGD gypsum to LCI and LCA indicators, only marginal credits result from module D/2 in further indicators. Recycling and disposal of non-recyclable fractions (C3/2, C4/2) contribute to a maximum of 6 % to the overall results. Exceptions in comparison to scenario 1 are the significantly smaller contribution to the indicator NHWD of 12 % (NHWD in scenario 1: 63 %) and the increased contribution to the indicator RWD of 9 % (RWD in scenario 1: 4 %).

7. Requisite evidence

7.1 Leaching (sulphates and heavy metals)

Plasterboards Knauf Safeboard GKF show a leaching behaviour typical for gypsum based building products /Dre2006/. Thus, sulphates are leached in the saturation region (complexometric titration according to /DIN 38405-5:1985/). That is why disposal is only allowed in landfills from landfill category 1 in Germany /DepV2009/.

Heavy metal concentrations were verified (by ICP-OES according to /ISO 11885:2007/) significantly below the assignment criteria according to landfill category 1 complying with /DepV2009/. Plasterboards Knauf Safeboard GKF are classified in water hazard class 1 (slightly water-hazardous).

7.2 Radioactivity

According to /Geh2012/ and RP 112 dose values and radon concentrations of gypsum based building products are below 0.3 mSv/a. Thus, they can be used without restrictions.

8. References

DIN 4103-1

DIN 4103-1:2014-03, Internal non-loadbearing partitions; requirements, testing

DIN 4103-4

DIN 4103-4:1988-11, Internal non-loadbearing partitions; partitions with timber framing

DIN 18168-1

DIN 18168-1:2007-04, Ceiling linings and suspended ceilings with gypsum plasterboards - Part 1: Requirements for construction

DIN 18168-2

DIN 18168-2:2008-05, Ceiling linings and suspended ceilings with gypsum plasterboards - Part 2: Verification of the load-carrying capacity of metal sub-constructions and metal suspending rods

DIN 18180

DIN 18180:2014-09, Gypsum plasterboards - Types and requirements

DIN 18181

7.3 VOC emissions

Plasterboards Knauf Safeboard GKF were tested randomly by the Fraunhofer Institute for Wood Research Wilhelm-Klauditz-Institute WKI, Braunschweig (D), according to the AgBB test scheme /WKI2011/. The requirements of the AgBB protocol /AgBB2015/ are fully met.

3 days

Name	Value	Unit
TVOC (C6 - C16)	< 10000	µg/m³
Carcinogenic Substances	< 10	µg/m³

28 days

Name	Value	Unit
TVOC (C6 - C16)	< 1000	µg/m³
Sum SVOC (C16 - C22)	< 100	µg/m³
R (dimensionless)	< 1	-
VOC without LCI	< 100	µg/m³
Carcinogenic Substances	< 1	µg/m³

DIN 18181:2008-10, Gypsum plasterboards for building construction - Application

DIN 18183-1

DIN 18183-1:2009-05, Partitions and wall linings with gypsum boards on metal framing - Part 1: Cladding with gypsum plasterboards

DIN 38405-5

DIN 38405-5:1985-01, German standard methods for the examination of water, waste water and sludge; anions (group D); determination of sulphate ions (D 5)

EN 318

EN 318:2002-06, Wood-based panels - Determination of dimensional changes associated with changes in relative humidity

EN 520

EN 520:2009-12, Gypsum plasterboards - Definitions, requirements and test methods

DIN 6812

DIN 6812:2013-06, Medical X-ray equipment up to



300 kV - Rules of construction for structural radiation protection

EN 13501-1

EN13501-1:2010-01: Fire classification of construction products and building elements-Part 1: Classification using data from reaction to fire tests

EN ISO 10456

EN ISO 10456-1:2010-05: Building materials and products - Hygrothermal properties – Tabulated design values and procedures for determining declared and design thermal values - Technical Corrigendum 1 (ISO 10456:2007/Cor 1:2009)

EWC

European Waste Catalogue, established by Decision 2000/532/EC of European Commission

CPR2011

Regulation (EU) No 305/2011 for construction products (CPR), Regulation (EU) No 305/2011of the European Parliament and of the Council of 9 March 2011 laying down harmonised conditions for the marketing of construction products and repealing Council Directive 89/106/EEC

ISO 9001

ISO 9001:2008-11, Quality management systems - Requirements

ISO 11885

ISO 11885:2007-08, Water quality - Determination of selected elements by inductively coupled plasma optical emission spectrometry (ICP-OES)

ISO 50001

ISO 50001:2011-06, Energy management systems – Requirements with guidance for use

ISO 15686-1:2011

ISO 15686-1:2011: Buildings and constructed assets --Service life planning -- Part 1: General principles and framework

AgBB2015

Health-related Evaluation Procedure for Volatile Organic Compounds Emissions (VOC and SVOC) from Building Products. Ausschuss zur gesundheitlichen Bewertung von Bauprodukten (Committee for Health-Related Evaluation of Building Products). 2015.

http://www.umweltbundesamt.de/bauprodukte/agbb.ht m

BBSR2011

Nutzungsdauern von Bauteilen für Lebenszyklusanalysen nach Bewertungssystem Nachhaltiges Bauen (BNB), Herausgeber: Bundesinstitut für Bau-, Stadt- und Raumforschung (BBSR), Stand: 03.11.2011 (Service life of building components for life cycle analyses according to the Assessment System for Sustainable Building, editor: Federal Ministry for Environment, Nature Conservation, Building and Nuclear Safety, 2011)

BDSH2013

Bauschäden durch Hochwasser – Tipps für die Sanierung (Flood damage - tips for recovery), instruction sheet, Knauf Gips KG (editor), Iphofen, 2013, www.knauf.de

BG RCI

Arbeitsschutzmanagement: Mit System zum Erfolg (Occupational health management: Systematic Safety), editor: Berufsgenossenschaft Rohstoffe und chemische Industrie (German trade association of natural ressources and the chemical industry), Heidelberg, http://www.bgrci.de/fachwissenportal/start/arbeitsschutzmanagement/

BlmSchG

Act on the Prevention of Harmful Effects on the Environment Caused by Air Pollution, Noise, Vibration and Similar Phenomena (Federal Immission Control Act - BImSchG), Publication 2013-05-2017 (BGBI. I p. 1274), last amended 2015-08-31 (BGBI. I p. 1474)

DepV2009

Verordnung über Deponien und Langzeitlager (Deponieverordnung – DepV), German regulation on landfills, last amended and supplemented: 2013-04-15)

Dre2006

H. Drexler, Test report no. 1080556 AU-23572, Dorfner Analysenzentrum und Anlagenplanungsgesellschaft mbH, Hirschau, 11.01.2006 (originator: Bundesverband Gips e. V., Dr. H.-J. Kersten, Berlin)

ECHA 2016

Candidate List of substances of very high concern for Authorisation, editor: European Chemicals Agency (ECHA), Helsinki (FI), last update: 2016-06-20, http://echa.europa.eu/candidate-list-table

EPD-BVG20140076-IAG1-DE

Environmental Product Declaration "Gipsplatte – Feuerschutz", EPD-BVG20140076-IAG1-DE, owner of Declaration: Bundesverband Gips e. V. (German association of gypsum manufacturers), publisher: Institut Bauen und Umwelt e. V., Berlin, August 2014

Geh2012

K. Gehrcke, B. Hoffmann, U. Schkade, V. Schmidt, K. Wichterey: Natürliche Radioaktivität in Baumaterialien und die daraus resultierende Strahlenexposition, Report BfS-SW-14/12, Bundesamt für Strahlenschutz (editor), urn:nbn:de:0221-201210099810, Salzgitter, 2012

GaBi2016

GaBi (v7): Software-System and Databases for Life Cycle Engineering, Think Step AG, Leinfelden-Echterdingen, 2016

Gips-Datenbuch

Gips-Datenbuch, editor: Bundesverband Gips e. V. (German association of gypsum manufacturers), Berlin, 2013

RP112

Radiation Protection 112: Radiological protection principles concerning the natural radioactivity of building materials, European Commission, Luxembourg, 2000

TRGS 521

Technical Rules for Hazardous Substances TRGS 521: Demolition, reconstruction and maintenance work with biopersistent mineral wools, Edition: February



2008, Federal Institute for Occupational Safety and Health (editor)

TRGS 559

Technical Rules for Hazardous Substances TRGS 559: Mineral Dust, Edition: February 2010, Federal Institute for Occupational Safety and Health (editor), last amended and supplemented: GMBI 2011

TRGS 900

Technical Rules for Hazardous Substances TRGS 900: Occupational Exposure Limits, Edition: January 2006, Federal Institute for Occupational Safety and Health (editor), last amended and supplemented: GMBI 2015

WKI2011

Fraunhofer Institute for Wood Research Wilhelm-Klauditz-Institute WKI, test report MAIC-2011-1634, investigation of plasterboard "Knauf Safeboard GKF", Braunschweig, 2011-06-27

Institut Bauen und Umwelt

Institut Bauen und Umwelt e.V., Berlin(pub.): Generation of Environmental Product Declarations (EPDs);

General principles

for the EPD range of Institut Bauen und Umwelt e.V. (IBU), 2013/04 www.bau-umwelt.de

ISO 14025

DIN EN ISO 14025:2011-10: Environmental labels and declarations — Type III environmental declarations — Principles and procedures

EN 15804

EN 15804:2012-04+A1 2013: Sustainability of construction works — Environmental Product Declarations — Core rules for the product category of construction products

Institut Bauen und Umwelt e.V.	Publisher Institut Bauen und Umwelt e.V. Panoramastr. 1 10178 Berlin Germany	Tel Fax Mail Web	+49 (0)30 3087748- 0 +49 (0)30 3087748- 29 info@bau-umwelt.com www.bau-umwelt.com
Institut Bauen und Umwelt e.V.	Programme holder Institut Bauen und Umwelt e.V. Panoramastr 1 10178 Berlin Germany	Tel Fax Mail Web	+49 (0)30 - 3087748- 0 +49 (0)30 - 3087748 - 29 info@bau-umwelt.com www.bau-umwelt.com
knauf	Author of the Life Cycle Assessment Knauf Gips KG Am Bahnhof 7 97346 Iphofen Germany	Tel Fax Mail Web	0049 9001 31-1000 0049 1805 31-4000 knauf-direkt@knauf.de www.knauf.de
KNAUF	Owner of the Declaration Knauf Gips KG Am Bahnhof 7 97346 Iphofen Germany	Tel Fax Mail Web	0049 9001 31-1000 0049 1805 31-4000 knauf-direkt@knauf.de www.knauf.de