EVO3® MID PEAK - SLIP RATCHET - NON-VENTILATED

PRODUCT CODE: AJE160-00_-_00

EVO3® IS A TRUE EVOLUTION OF THE LONG ESTABLISHED MK2 & MK3 HELMETS

TECHNICAL SPECIFICATION

HEAD PROTECTION

INSTRUCTIONS FOR USE

- Fit helmet on head and fasten strap to ensure fit
- For adequate protection this helmet must be worn with peak facing forward
- Ensure the helmet is adjusted to the size of the user's head

SHELL:
UV Stabilised High Density Polyethylene (HDPE)

CHAMLON™ SWEATBAND:
Egyptian cotton core with porous PU coating for maximum sweat absorption. PH neutral, dermatologically tested



WEBBING HARNESS:
HDPE Strap & Webbing Clips with Polyester Webbing Straps



SLIP RATCHET:
One Touch™ Slip Ratchet version of the EVO3® is so simple to fit that it can be adjusted with just one finger.

DESIGN RIGHTS RESERVED • JSP • DESIGN RIGHTS RESERVED

evo3® Mk3 evolution

CONFORMITY

- Conforms to EN397, EN50365, ANSIZ89 & ГОСТ Р 50460-92
- EN 50365 for Helmets for use in low voltage installations
- EC Certificate Number 00279, issued by BSi Product Certification
- Meets the retro reflective performance requirements of EN12899 when fitted with CR2 Reflective kit
- Meets optional Molten Metal Splash performance
- Meets optional Electrical Insulation requirements
- Wide size range. Slip or wheel ratchet - High comfort fit
- Available vented or unvented. Available with mid or micro peak
- Company personalisation available by printing

CLEANING & MAINTENANCE

- The unit may be cleaned with soap and warm water and dried with a soft cloth
- The helmet should not be cleaned with chemical or abrasive cleaners
- The helmet should be stored out of direct sunlight
- The helmet should be stored away from chemicals and extremes of temperature

JSP® OXFORD, ENGLAND
MANUFACTURING FOR SAFETY
WWW.JSP.CO.UK
UKSALES@JSP.CO.UK
TEL: +44 (0)1993 826050

Issued 25/01/16, V7

EVO3® MID PEAK - SLIP RATCHET - NON-VENTILATED

PRODUCT CODE: AJE160-00_-_00

EVO3® IS A TRUE EVOLUTION OF THE LONG ESTABLISHED MK2 & MK3 HELMETS

TECHNICAL SPECIFICATION

HEAD PROTECTION

DIMENSIONS OF OUTER PACKAGING

Quantity: 10

Weight: 3.8kg (Approx.)

HEIGHT: 450mm

LENGTH: 580mm

WIDTH: 240mm

HELMET FEATURES

EN STANDARD	EN397 EN50365	Yes Yes
PERFORMANCE	Impact Resistance Electrial Insulation	Yes 50 Joules Yes: EN397 440V EN50365 1000V
TEMPERATURE RESISTANCE	Molten Metal (MM) Low Temperature	Yes Yes: EN397 -40°C ГОСТ P 50460-92 -50°C
SHELL MATERIAL	HDPE Recyclable UV Stabilised	Yes Yes Yes
HARNESS MATERIAL	HDPE LDPE Textile	Yes Yes Yes
OPTIONS	Universal Accessories Reflective CR2 option Integrated Eyewear	Yes Yes Yes
HARNESS SYSTEM OPTIONS	JSP 3D Slip Ratchet 6 pts	Yes Yes Yes
CHINSTRAP	4 pts	Yes
LOGO OPTIONS	Front Rear Side MOQ Logo Individual Name	Yes Yes Yes 10 Yes

DIMENSIONS OF HELMET

Size: 530 - 640mm

Weight: 375g (Approx.)

LOGOEXPRESS™
ADD YOUR LOGO TO OUR PRODUCTS

HELMET COLOURS

Insert the following two digit number in place of the dashes in the product code of your desired helmet

01 White 02 Yellow 05 Blue 06 Red

LIMITATIONS OF USE

Protection will only be offered if the helmet is fitted correctly

Any helmet subjected to severe impact should be replaced immediately. Do not apply paint, solvents or adhesive labels except in accordance with instructions from the manufacturer

The harness, when in contact with the skin may cause allergic reactions to susceptible individuals. If this occurs leave the hazard area, remove the helmet and seek medical advice

The attention of users is also drawn to the dangers of modifying or removing any of the original component parts, other than as recommended by the manufacturer