

**FLOORING
PRODUCTS**

Self-declaration that the named products comply with the requirements for flooring products as per BREEAM-NOR's chapter HEA 02

This form must be filled out by the MANUFACTURER of flooring products according to NS-EN 13813. The requirements apply to the following types of flooring products:

- Screed material
- Floor screeds

Approved emission certificates are M1¹, EC1² or SINTEF Technical Approval.

If the product has one of the approved emission certificates, it is not necessary to fill in this form. Connect the emission certificate to the product in goBIM.

¹ Approved performance standard NS-EN 15251:2007, Annex C

² Approved performance standard GEV Emissioncode

It is important that the information given here is correct, and we strongly encourage thoroughness in researching the extent to which emission testing and/or test reports show that the product complies with the standards and emission limit values required by BREEAM-NOR 2016. If in doubt, the manufacturer should consult own internal and external experts. **Providing incorrect and misleading information can have legal consequences. Once filled-out, the form must be signed by a legally responsible person for the manufacturer, such as a technical director or a managing director.**

MANUFACTURER:

BerryAlloc NV

PRODUCT TRADE NAME:

Pure

PRODUCT ID:

DOP 450-PU3220-2

The following is hereby confirmed by the manufacturer:

1. The product is in accordance with product standard: NS-EN 13813.
2. The product has undergone an emission test³ which shows that its emissions are below the values⁴ shown in BREEAM-NOR 2016 "Table 15" according to the intended use of the product.

Table 15: Emission limits for all product categories – Conversion table

Emission	Wall		Floor/ceiling		Sealants	
	$\mu\text{g}/\text{m}^2\text{h}$	$\mu\text{g}/\text{m}^3$	$\mu\text{g}/\text{m}^2\text{h}$	$\mu\text{g}/\text{m}^3$	$\mu\text{g}/\text{m}^2\text{h}$	$\mu\text{g}/\text{m}^3$
TVOC 28d	200	417	200	160	4260	60
Formaldehyde 3d*	24	50	62.5	50	3550	50
Formaldehyde 28d*	50	104	50	40	710	10
Carcinogenic	5	10	5	4	71	1

³Documentation (test in acc. with approved standard) can be requested if required.

⁴Show accordance with units $\mu\text{g}/\text{m}^3$ or $\mu\text{g}/\text{m}^2\text{h}$

*Emission levels for 3 or 28 days can be used as a basis for documenting compliance.

3. The emission test has been performed in accordance with the following approved standards ISO 16000-9 together with ISO 16000-6 (volatile organic compounds) and ISO 16000-3 (formaldehyde). Test and calculation shall be carried out according to EN 16516.

Legally responsible:

*Philippe
Schedin*

Position:

General Mgr.

Date:

26/11/2021

Signature:

