



PRODUCT DESCRIPTION

Dimensions	1288mm x 190mm
Thickness	8mm + 2mm Silent System underlay
Bevels	4
Loc System	5G Loc under licence of Välinge Innovation AB
Classification of use	Class 23/32 According to European Standard EN13329

	Contains	m ²	ft ²	Weight
1 pack	7 planks	1,71 m ²	18,41 ft ²	12,8 kg
1 pallet	56 packs	95,9 m ²	1032,26 ft ²	730 kg

COMPOSITION

Surface layer	Direct laminated paper, impregnated with melamine resin
Substrate	Moisture resistant High Density Fiberboard (HDF)
Backing	Direct laminated paper, impregnated with melamine resin. With attached Silent system underlay

TESTED VALUE

Abrasion resistance
Impact resistance
Thickness swelling
Fire resistance
Formaldehyde
Slipperiness
Density
Resistance to staining
Resistance to cigarette burns
Effect of a furniture leg
Effect of a castor chair
Thermal resistance

METHOD

EN13329
EN13329
EN13329
EN14041
EN14041
EN14041
EN323
EN438
EN438
EN424
EN425

TEST RESULTS

AC4 (IP≥4000)
Small ball : ≥ 12 N - Big ball : ≥ 750 mm
12% (requirement ≤ 18%)
Cfl-S1
E1
DS
900 kg/m³
5 (groups 1+2); 4 (group 3)
4
No damage (foot type 0)
No change in appearance or damage
0,10 m²K/W – Suitable for floor heating/
cooling. Detailed instructions on
www.berryalloc.com

CERTIFICATES/LABELS

- Sustainability of forests: PEFC certified (07-31-229)
- Labelling according to French VOC emission regulation: A+
- DOP : 170-DPLA18-1

WARRANTY

Lifetime Residential Warranty
5 Years of Commercial Warranty
Warranty conditions on www.berryalloc.com

