

## DESCRIPTION

|                             |                          |        |             |
|-----------------------------|--------------------------|--------|-------------|
| Total thickness             | EN ISO 24346<br>[EN 428] | mm     | 2.00        |
| Weight                      | EN ISO 23997<br>[EN 430] | g/sq.m | 2850        |
| Width of sheet              | EN ISO 24341<br>[EN 426] | cm     | 200         |
| Length of sheet             | EN ISO 24341<br>[EN 426] | lm     | 20          |
| Tile size                   | EN ISO 24342<br>[EN 427] | mm     | 608 x 608 * |
| Number of tiles per package | -                        | -      | 20          |

## CLASSIFICATION

|                              |                          |       |                          |
|------------------------------|--------------------------|-------|--------------------------|
| Norm / Product specification | -                        | -     | EN ISO 10581<br>(EN 649) |
| European classification      | EN ISO 10874<br>(EN 685) | class | 34 - 43                  |
| Fire rating                  | EN 13 501-1              | class | B <sub>fl</sub> -s1      |
| Static electrical propensity | EN 1815                  | kV    | < 2                      |
| Slip resistance              | DIN 51130 / BGR 181      | Class | R9                       |

## PERFORMANCE

|                                                           |                            |                 |                             |
|-----------------------------------------------------------|----------------------------|-----------------|-----------------------------|
| Wear resistance                                           | EN 660.2                   | mm <sup>3</sup> | ≤ 2.0                       |
| Wear Group                                                | NF 189                     | group           | T                           |
| Type Binder content                                       | EN ISO 10581               | type            | I                           |
| Dimensional stability                                     | EN ISO 23999<br>[EN 434]   | %               | sheet ≤ 0.40<br>tile ≤ 0.25 |
| Residual indentation                                      | EN ISO 24343-1<br>[EN 433] | mm              | ≈ 0.02                      |
| Castor chair test (type W)                                | ISO 4918<br>(EN 425)       | -               | OK                          |
| Thermal conductivity                                      | EN ISO 10456<br>(EN12524)  | W/(m.K)         | 0.25                        |
| Colour fastness                                           | EN 20 105 - B02            | degree          | ≥ 6                         |
| Surface treatment                                         | -                          | -               | Evercare™                   |
| Chemical products resistance                              | EN ISO 26987<br>[EN 423]   | class           | OK                          |
| Anti-bacterial activity<br>(E.coli – S. aureus – MRSA) ** | ISO 22196                  | -               | > 99 %<br>inhibits growth   |

## ENVIRONMENT / INDOOR AIR QUALITY

|                    |             |                    |             |
|--------------------|-------------|--------------------|-------------|
| TVOC after 28 days | ISO 16000-6 | µg/ m <sup>3</sup> | < 10        |
| Certification      | -           | -                  | Floorscore® |

## CE MARKING

|                                                                                    |          |   |                                                                                                                                                                                                                                                                   |
|------------------------------------------------------------------------------------|----------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | EN 14041 | - |    |
|                                                                                    |          | - |                                                                                                                                                                              |

\* Products available in tiles for a minimum quantity order of 500 sqm

\*\* The implementation of an effective cleaning method is the best defence against infection