

FOCUS OAK

TEMPORARY WOOD RANGE FOR PROJECTS PRODUCT DATASHEET 2022



Pure Oak TreS PL



Pure Oak TreS PN



Shade Oak Cotton
TreS PN



Shade Oak Beige
TreS PN



Shade Oak Cream
TreS PN

PRODUCT DATA	Material code	Dimensions LxWxH (mm)	Pattern	Surface treatment	Surface effect	Bevel (2 side)	Character	Latin name	DoP no.	Wear layer thk (mm)	Board/pack	m2/pack	m2/pallet	Net weight/m2 (kg)
Pure Oak TreS PL	8723923	2 281 x 194 x 13	3-strip	Proteco Lacquer	-	-	Calm	1	0020-0104	2,5	6	2,66	106,4	7,3
Pure Oak TreS PN	8723924	2 281 x 194 x 13	3-strip	Proteco Natura	-	-	Calm	1	0020-0104	2,5	6	2,66	106,4	7,3
Shade Oak Cotton TreS PN	8723926	2 281 x 194 x 13	3-strip	Proteco Natura	-	-	Calm	1	0020-0104	2,5	6	2,66	106,4	7,3
Shade Oak Cream TreS PN *	8723925	2 281 x 194 x 13	3-strip	Proteco Natura	-	-	Lively	1	0020-0104	2,5	6	2,66	106,4	7,3
Shade Oak Beige TreS PN	8723927	2 281 x 194 x 13	3-strip	Proteco Natura	Brushed	-	Lively	1	0190-0103	2,5	6	2,66	106,4	7,3

* PEFC certified

Due to the nature of the material this table shows typical values.

1: Quercus Robur & Quercus Petraea

TECHNICAL DATA (EN 13489)		13 mm
Reaction to fire	EN 14342 Table 1 (when applicable / EN 13501)	Dfl-s1
Emission of formaldehyde	EN 14342	E1
Brinell hardness (average value) Oak	(BHN) EN1534	3,7
Taber Abraser/Lacquer's wear resistance Proteco Lacquer Proteco Natura	EN 13696	4000 3500
<i>These typical values are not applicable for stained, brushed or hardwax oiled products.</i>		
Reduction of sound weighted index ΔL_w in dB with 2 mm Tarkofoam/flex II	EN ISO 10140-3 / EN ISO 717-2	≥ 17
Thermal insulation value (RT m ² K/W) board only with rag felt with 2 mm Tarkofoam/flex II	EN ISO 10456:2007	0,101 0,121 0,141
Thermal conductivity (W/m K)	EN 12664 / EN 14342:2013	0,104
Construction: softwood veneer and lamella core		3-layer

INSTALLATION	
Installation method	2-lock for floating or glue down
Installation instruction	Download from www.tarkett.com Contact your supplier for more details
Underfloor heating compatible Maximum floor surface temperature 27°C with self-regulating under-floor heat system	Yes
Start & Stop: Shorter lengths of planks included in approx. 1 pack per 20 m ²	

RECOMMENDED ACCESSORIES	
Installation	Tarkofoam II / Tarkoflex II Installation kit
Aesthetics	Skirting Transition moulding Pipe covers
Care & Maintenance	Tarkoclean Refresher
See more alternatives and the complete range of accessories @ www.tarkett.com	

MAINTENANCE
These Tarkett wooden floors have a Proteco surface treatment and therefore a strong protection against normal wear, abrasion, scratches and stains. Some floors will require more frequent maintenance for increased life span. Generally these products are light coloured floors and hardwax oiled floors, particularly with brushed surface and/or high-lighted details. Please always refer to maintenance guidance available on websites.
See maintenance instructions @ www.tarkett.com



2-LOCK



97%
RENEWABLE
RESOURCES



www.realwood.eu



Hanaskog 2022.03

The pictures only present the colour of the floor. For more details regarding grading and variations contact your sales contact. Although every care has been taken to reproduce images that reflect the finished product, the quality of monitor and printer and the nature of wood results in variations in the color and structure of individual planks. When sanding a wooden floor the appearance will change in colour, texture and surface effects.