

DECLARATION OF PERFORMANCE

No. 1/2024

1. Unique identification code of the product-type:

Multi layer (L2) solid wood panels / boards STP from aspen wood (POTL, EN13556) for the non-load-bearing area/use according EN 13986:2004+A1:2015; SWP/1 NS, SWP/2 NS and SWP/3 NS

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

Panel boards are delivered in packages with package labels indicating the package number and production date to ensure the tracking back to the production date

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Solid wood panels / boards for internal use as non-structural building components in humid conditions

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Ozoli AZ SIA, reg. no. 43201000440

Alūksnes novads, Jaunlaicenes pagasts, "Ozoli 1", LV-4336, Latvia

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

No authorized agent

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

EN 13986:2004+A1:2015

Meža un koksnes produktu pētniecības un attīstības institūts SIA, NB 2040 performed reaction to fire test and classification under system 3 and issued classification report no. K21/2024

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable


9. Declared performance:

Essential characteristics	Performance	Harmonised technical specification
Bonding quality, N mm ⁻²	$f_v > 1,2$ according to EN 13353	EN 13986:2004+A1:2015
Durability (Moisture resistance)	see bonding quality	
Density, kg m ⁻³	500	
Release of formaldehyde	E1	
Reaction to fire class	E	
Water vapour permeability / vapour resistance factor	70 (wet cup) / 200 (dry cup)	
Airborne sound insulation	NPD	
Sound absorption coefficients	0,10 (250-500 Hz) / 0,30 (1000-2000 Hz)	
Thermal conductivity, W m ⁻¹ K ⁻¹	0,13	
Biological durability	Durability class 5 according to EN 350-2	
Content of pentachlorophenol, ppm	< 5	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Andis Zariņš, Chairman of the Board



(signature)

Alūksne, 28.03.2024.

