

# WISA Spruce plywood, uncoated



<b>Program operator, publisher:</b>	Building Information Foundation RTS Malminkatu 16 A 00100 Helsinki <a href="http://epd.rts.fi">http://epd.rts.fi</a>
<b>Owner of the declaration:</b>	UPM Plywood Oy
<b>Name of the product:</b>	WISA Spruce plywood, uncoated
<b>Declaration number:</b>	RTS_21_19
<b>Registration number:</b>	RTS_21_19
<b>ECO Platform reference number:</b>	00000916
<b>Issue date:</b>	25.2.2019
<b>Valid to:</b>	29.10.2023
<b>Scope of the declaration</b>	This environmental product declaration covers the environmental impacts of WISA Spruce plywood, uncoated. The declaration has been prepared in accordance with EN 15804:2012+A1:2013 and ISO 14025 standards and the additional requirements stated in the RTS PCR (English version, 2.6.2016). This declaration covers the life cycle stages from cradle-to-gate
	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">               Laura Sariola              Secretary of certification group         </div> <div style="text-align: center;">               Markku Hedman              RTS General Director         </div> </div>
Verified according to the requirements of EN 15804+A1 (product group rules)	
Independent verification of the declaration and data, according to ISO14025:2010	
<div style="display: flex; justify-content: space-around;"> <input type="checkbox"/> Internal                 <input checked="" type="checkbox"/> External             </div>	
Third party verifier:  DI Hannu Karppi, Ramboll Finland Oy	

# General information

## Manufacturer and Contact Information

UPM Plywood Oy  
Niemenkatu 16  
15141 Lahti  
Production sites: Jyväskylä, Pello.  
www.wisaplywood.com  
Sanna Kontinen, sanna.kontinen@upm.com

## Conductor of Life Cycle Assessment (LCA) and Environmental Product Declaration (EPD)

ECOBIO Oy  
Runeberginkatu 4c B21  
00100 Helsinki  
+358 (0)20 756 9450  
www.ecobio.fi

## Product Category Rules

RTS PCR protocol: EPDs published by the Building Information Foundation RTS sr (2.6.2016)

EN 15804:2012: Sustainability of construction works – Environmental product declaration – Core rules of the product category of construction products

SFS-EN 16485:2014. Round and sawn timber. Environmental product declarations. Product category rules for wood and wood-based products for use in construction

## Date of publication and validity of EPD

EPD is published on 25.2.2019. EPD is valid for 5 years, 29.10.2018-29.10.2023.

Rakennustietosäätiö RTS  
Malminkatu 16 A  
00100 Helsinki  
<http://epd.rts.fi>

## Verification

The EPD is verified by an independent external party according to the EN 15804:2012 standard. The EPD is verified by Ramboll Finland Oy, DI Hannu Karppi according to the product category rules presented above. Pakkahuoneenaukio 2, FI-33101 Tampere, +358 40 5083608, [www.ramboll.fi](http://www.ramboll.fi).

# Product description

## Description of the product and its use

The products covered by this declaration are uncoated spruce plywood boards for building and construction. The boards are strong, stiff and lightweight and hence suitable for multiple different uses, e.g. roofing, flooring and wall sheeting. Related products are e.g:

WISA-Kate Plus  
WISA-Roof  
WISA-Spruce  
PELLOS  
Top Floor  
WISA-Spruce Special  
WISA-Wall Ergo  
WISA-Spruce  
Premium  
RAW Ergo Wall  
WISA-Sprucefloor  
WISA-Parquet Spruce  
WISA-Oil  
WISA-SpruceBT  
WISA-SpruceFR

The EPD is based on product-specific data from the manufacturing facilities located in Finland. The results presented for 1 m<sup>3</sup> of the final product are weighted based on the respective production volumes of each manufacturing facility.

The products are supplied from production in different thicknesses ranging from 5 mm to 50 mm. The plywood boards are designed, produced and CE marked according to EN 13986. For specific physical properties, we refer to the CE-declaration or Declaration of Performance on [www.wisaplywood.com](http://www.wisaplywood.com)

## Main product components and or materials

The uncoated plywood boards are made of spruce wood, glue and protective agent. The boards do not include Substances of very high concern (SVHC).

	Component/Substance	Amount	CAS-nr	Classification
Uncoated	Wood	92,5%	-	
	Phenol-formaldehyde resin	4,9 %		
	Hardener	3,8 %		
	Protective agent	< 1 %		
	Phenolic films	-		

# LCA calculation information

According to EN 15804, an EPD of construction products may not be comparable if they do not comply with this standard. EPD might not be comparable if different functional unit or reference thickness is used.

## Declared unit

This EPD describes the environmental effect of 1m<sup>3</sup> of plywood board throughout the life cycle.

The density of the plywood board is 480 kg/m<sup>3</sup>.

## System boundaries

Cradle-to-Gate with options;

- product stage (A1-A3),
- construction process stage (A4-A5),
- use stage (B1-B7),
- end-of-life stage (C1-C4).

## Cut-off rules

In the inventory of the input flows a 1 % cut-off rule has been applied. The 1 % cut-off rule is based on the assumption that these input flows do not have a major impact on the environmental impacts as a whole (EN 15805 6.3.5).

Machines and facilities (capital goods) required for and during production are excluded, as is transportation of employees.

## Reference service life (RSL)

As permanent component of building or infrastructure, plywood boards are primarily used in dry indoor or moderately humid conditions, such as in roofing, flooring and wall sheeting. According to research results and experience, glued timber products, such as plywood, will have around the same service life expectations than solid wood in dry and moderately humid conditions. The most important factors in evaluating service life of wooden materials in dry and moderately humid conditions are design, execution and maintenance. If installed properly and moisture exposure is low or moderate, the service life of the plywood board is 100 years at minimum. The spruce and birch plywood have the biological durability performance corresponding to Use class 2 for uncoated plywood according to EN 13986:2004+A1:2015.

## Year of study

Raw materials, transports and manufacturing data: 2016.


# LCA-software

GaBi 8, thinkstep AG

## Life cycle stages

Product stage			Construction process		Use stage							End-of-life				Benefits and loads beyond the system boundary
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	B6	B7	C1	C2	C3	C4	D
x	x	x	x	x	NR	NR	NR	NR	NR	NR	NR	x	x	x	x	ND
Raw material supply	Transports	Manufacturing	Transports	Installation	Use	Maintenance	Repair	Replacement	Refurbishment	Energy use	Water use	De-construction	Transports	Waste processing	Disposal	Reuse, Recovery, Recycling

 Mandatory modules

 Mandatory in accordance with the provisions of section 6.2.1 of the RTS EPD protocol

 Optional modules based on scenarios

NR = Not relevant, i.e. module not declared; all modules that are not declared within the EPD but where additional data are available. This data can also be used for building assessment scenarios.

ND = Not determined

### Product stage; A1-A3

#### A1; Raw-material supply

The raw material supply covers sourcing and production of all raw materials, fuels and energy used. The supply of packaging materials is also included in module A1.

The emission factors used for the electricity are based on country-specific electricity grid mixes, reflecting actual used electricity per manufacturing facility (Thinkstep database):

- FI: Electricity grid mix 200 g CO<sub>2</sub>/kWh



## Construction process stage; A4-A5

### A4; Transports

From the factories the plywood is transported to centralized warehouses across Europe. The transport distances are based on factory specific logistics from 2016.

Parameter	Unit
Vehicle type	Truck-trailer, Euro 6, 34-40 t
Load capacity	85 % (GaBi)
Distance	778 km
Bulk density	480 kg/m <sup>3</sup>

Parameter	Unit
Vehicle type	Large engine ship
Load capacity	65 % (GaBi)
Distance	1 499 km
Bulk density	480 kg/m <sup>3</sup>

### A5; Installation

At the construction site a 5 % wastage of the material is assumed. The wastage is sent the treatment as follows: 95 % to energy recovery and 5 % to material recovery

Parameter	Unit
Ancillary materials for installation	estimated to very small and hence neglected
Water use	0 m <sup>3</sup>
Other resource use	0 kg
Energy type and consumption	estimated to very small and hence neglected
Waste materials	5 % material loss
Output materials	material reuse and energy recovery

## **Use stage; B1-B7**

The use phase consists of the following modules:

B1: Use

B2: Maintenance

B3: Repair

B4: Replacement

B5: Refurbishment

B6: Operational energy use

B7: Operational water use

Once the product is installed, no actions or technical operations are required during the use phase until the demolition of the construction. No operational energy or water use is required by the product

## **End-of-life stage; C1-C4**

### **C1; De-construction**

The de-construction and/or demolition of the product is part of the demolition of the entire construction. The deconstruction is considered to be done by excavation.

### **C2; Transports**

Transport distance to waste processing is estimated to be 100 km by road.

### **C3; Waste processing**

The collected waste is sent either to energy recovery (95 %) or material recover (5 %).

### **C4; Disposal**

No generated waste is disposed to landfill.

## **Benefits and loads beyond the system boundary; D**

The environmental impacts of the benefits and loads beyond the system boundary are not assessed in the life cycle assessment for this environmental product declaration.



# LCA results

## Environmental impacts

Declared unit = 1m<sup>3</sup> of plywood board. The density of the plywood board is 480 kg/m<sup>3</sup>.

Impact category	unit	A1	A2	A3	A1-A3	A4	A5
Global warming	kg CO2 eq	-1 583	6.02	928	-649.18	37.70	43.60
Ozone depletion	kg CFC 11 eq	5.48E-06	2.00E-12	9.65E-12	5.48E-06	1.26E-11	8.99E-12
Acidification	kg SO2 eq	0.59	0.02	0.11	0.72	0.23	4.10E-03
Eutrophication	kg (PO4)3- eq	0.06	0.004	0.023	0.08	0.056	8.46E-04
Photochemical ozone creation	kg Ethene eq	0.11	0.001	0.006	0.12	0.024	3.36E-04
Depletion of abiotic resources – elements	kg Sb eq	4.30E-04	4.32E-07	9.92E-08	4.31E-04	2.72E-06	9.75E-08
Depletion of abiotic resources – fossil fuels	MJ	1 811	82.36	8.54	1 902	519	7.42

Impact category	unit	C1	C2	C3	C4	D
Global warming	kg CO2 eq	1.13	2.25	872	0	0
Ozone depletion	kg CFC 11 eq	2.47E-14	7.45E-13	1.8E-10	0	0
Acidification	kg SO2 eq	4.13E-03	1.99E-03	0.08	0	0
Eutrophication	kg (PO4)3- eq	8.78E-04	3.79E-04	0.017	0	0
Photochemical ozone creation	kg Ethene eq	3.84E-04	2.07E-05	6.71E-03	0	0
Depletion of abiotic resources - elements	kg Sb eq	3.84E-08	1.61E-07	1.95E-06	0	0
Depletion of abiotic resources – fossil fuels	MJ	15.40	30.70	148	0	0

## Resource use

Resource use	unit	A1	A2	A3	A1-A3	A4	A5
Use of renewable primary energy excluding renewable primary energy resources used as raw materials	MJ	10 465	4.15	1.26	10 470	26.10	1.32
Use of renewable primary energy resources used as raw materials	MJ	18 837	0	0	18 837	0	0
<b>Total use of renewable primary energy resources</b>	MJ	29 302	4.15	1.26	29 307	26.10	1.32
Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials	MJ	3 449	82.63	9.65	3 541	521	8.85
Use of non-renewable primary energy resources used as raw materials	MJ	0	0	0	0	0	0
<b>Total use of non-renewable primary energy resources</b>	MJ	3 449	82.63	9.65	3 541	521	8.85
Use of secondary material	kg	0	0	0	0	0	0
Use of renewable secondary fuels	MJ	0	0	0	0	0	0
Use of non-renewable secondary fuels	MJ	0	0	0	0	0	0
Net use of fresh water	m3	0.16	0.01	0.05	0.21	0.05	0.10

Resource use	unit	C1	C2	C3	C4	D
Use of renewable primary energy excluding renewable primary energy resources used as raw materials	MJ	0.07	1.54	26.40	0	0
Use of renewable primary energy resources used as raw materials	MJ	0	0	0	0	0
<b>Total use of renewable primary energy resources</b>	MJ	0.07	1.54	26.40	0	0
Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials	MJ	15.40	30.80	177.00	0	0
Use of non-renewable primary energy resources used as raw materials	MJ	0	0	0	0	0
<b>Total use of non-renewable primary energy resources</b>	MJ	15.40	30.80	177.00	0	0
Use of secondary material	kg	0	0	0	0	0
Use of renewable secondary fuels	MJ	0	0	0	0	0
Use of non-renewable secondary fuels	MJ	0	0	0	0	0
Net use of fresh water	m3	0.00	0.00	2.01	0	0

## Waste categories:

Waste categories	unit	A1	A2	A3	A1-A3	A4	A5
Hazardous waste disposed	kg	6.33E-07	4.34E-06	7.07E-07	5.68E-06	2.73E-05	5.17E-09
Non-hazardous waste disposed	kg	0.13	0.006	2.40	2.54	0.040	0.10
Radioactive waste disposed	kg	0.01	1.13E-04	4.48E-04	0.01	7.10E-04	5.67E-04

Waste categories	unit	C1	C2	C3	C4	D
Hazardous waste disposed	kg	1.93E-09	1.62E-06	1.03E-07	0	0
Non-hazardous waste disposed	kg	1.09E-04	2.35E-03	1.91	0	0
Radioactive waste disposed	kg	3.37E-06	4.25E-05	0.011	0	0

## Other output flows

Other output flows	unit	A1	A2	A3	A1-A3	A4	A5
Components for re-use	kg	0	0	0	0	0	0
Materials for recycling	kg	0	0	0	0	0	1.2
Materials for energy recovery	kg	0	0	0	0	0	22.8
Exported energy, Thermal	MJ	0	0	0	0	0	120
Exported energy, Electric	MJ	0	0	0	0	0	51,7

Other output flows	unit	C1	C2	C3	C4	D
Components for re-use	kg	0	0	0	0	0
Materials for recycling	kg	0	0	24	0	0
Materials for energy recovery	kg	0	0	456	0	0
Exported energy, Thermal	MJ	0	0	1 030	0	0
Exported energy, Electric	MJ	0	0	2 410	0	0

# Additional information

## Use

There is no harmful substance released to air, water or ground during the use of the product.

Regarding indoor air quality the plywood boards have a M1 emission classification granted by the Building Information Foundation RTS sr (Rakennustietosäätiö RTS sr). M1 stands for low emissions.

## End-of-life

- information on recycling including e.g. suitable procedures for recycling the entire product or selected parts and the potential environmental benefits gained*
- information on a suitable method of reuse of the product (or parts of the products) and procedures for disposal as waste at the end of its life cycle, and*
- information regarding disposal of the product or inherent materials, and any other information considered necessary to minimise the product's end-of-life impacts.*

# References

1. RTS. PCR protocol: EPDs published by the Building Information Foundation RTS sr (2016)
2. ISO 14025: Environmental labels and declarations - Type III environmental declarations - Principles and procedures (2006)
3. ISO 14040: Environmental management - Life Cycle Assessment - Principles and framework (2006)
4. ISO 14044: Environmental management - Life Cycle Assessment - Requirements and guidelines (2006)
5. EN 15804: Sustainability of construction works - Environmental product declaration - Core rules of the product category of construction products (2014)
6. SFS-EN 16485: Round and sawn timber. Environmental product declarations. Product category rules for wood and wood-based products for use in construction (2014)
7. LCA report: UPM Plywood Oy – Plywood boards. (2018)
8. Research report, 100 years' service life of wood in service class 1 and 2 – dry and moderately humid condition. VTT (2014).