



**C-TEC**<sup>TM</sup>  
BUILDING PRODUCT  
SPECIALISTS

## Product Information

**Peel  
Tec**



### TECHNICAL DATA

#### Physical and Chemical Characteristics

**100% Methyl Chloride FREE!**

<b>Contents :</b>	500 ml
<b>VOC-content :</b>	Approximately 98% w/w
<b>Colour :</b>	Transparent
<b>Scent :</b>	Characteristic
<b>Relative density at 20°C :</b>	1,25 g/ml
<b>Yield :</b>	1,5 g/sec
<b>Vapour pressure at 20°C :</b>	3 to 4 bar
<b>Coverage :</b>	Approximately 0,8 m <sup>2</sup>

#### Product Description

Revolutionary product to remove old layers of paint and lacquer on surfaces of stone, asphalt, metal and wood.

#### Product characteristics

Gel structure. Very effective.

The aerosol should be stored at room temperature before use.

Application temperature 5 – 30°C.

Spray pattern approximately 8 centimetre wide.

#### Application

Shake before use. Before use, test the compatibility of the surface. Apply generously and allow to take effect. The time to take effect depends on the quality and age of the paint or lacquer to be removed. Then, remove with a tool appropriate for this purpose. On stubborn deposits, you need to repeat the process.

**Shelf life:** See elsewhere on the packaging (exp.)

C-Tec N.I. Limited, Unit 6 Ashtree Enterprise Park,  
Newry, Co. Down, Northern Ireland, BT34 1BY.  
Tel: 028 3083 4892 Fax: 028 3026 4444  
Email: [info@ct1ltd.com](mailto:info@ct1ltd.com) Web: [www.ct1ltd.com](http://www.ct1ltd.com)

All information, including illustrations, is believed to be reliable. Users however, should independently evaluate the suitability of each product for their application. C-TEC makes no warranties of the accuracy of completeness of the information, and disclaims any liability regarding its use. C-TEC only obligations are those in the standard terms and conditions of sale of this product, and in no case will C-TEC be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of this product. (20180201)