



FAST FASTENING



## BETONGSKR R-LX HF 5,0X50 ZF BRK=100

### Betongskrue R-LX FAST

For direkte innfestning i betong. Skruen har Hi-Lo gjenger som gir en høy uttreksverdi. NB! Ved montering, bor alltid 10mm dypere enn skruelengden krever. Overflatebehandling: Zinkflakes, korrosjonsklasse C3. Boks.

### Kataloginfo

| Artikelnr              | Dimension d x L<br>mm | Borrdiameter<br>mm | Nyckelvidd<br>mm | Innehåll | Antal/fp |
|------------------------|-----------------------|--------------------|------------------|----------|----------|
| <a href="#">288301</a> | 5,0x50                | 5                  | 8                | 100      | 8        |
| <a href="#">288303</a> | 5,0x75                | 5                  | 8                | 100      | 8        |
| <a href="#">288305</a> | 6,0x50                | 6                  | 10               | 50       | 8        |
| <a href="#">288307</a> | 6,0x75                | 6                  | 10               | 50       | 8        |
| <a href="#">288309</a> | 6,0x100               | 6                  | 10               | 50       | 6        |
| <a href="#">288315</a> | 8,0x60                | 8                  | 13               | 25       | 8        |
| <a href="#">288317</a> | 8,0x75                | 8                  | 13               | 25       | 8        |
| <a href="#">288319</a> | 8,0x90                | 8                  | 13               | 25       | 6        |
| <a href="#">288321</a> | 8,0x100               | 8                  | 13               | 25       | 6        |
| <a href="#">288323</a> | 8,0x130               | 8                  | 13               | 25       | 6        |
| <a href="#">288329</a> | 10,0x65               | 10                 | 15               | 20       | 8        |
| <a href="#">288331</a> | 10,0x85               | 10                 | 15               | 20       | 6        |
| <a href="#">288333</a> | 10,0x100              | 10                 | 15               | 20       | 6        |
| <a href="#">288335</a> | 10,0x120              | 10                 | 15               | 20       | 6        |

### Teknisk data

| Skrue dimension<br>mm | Borrdiameter<br>mm | Min monteringsdjup<br>mm | Praktisk lastförmåga<br>(kN) |
|-----------------------|--------------------|--------------------------|------------------------------|
| Ø 6,0                 | 6                  | 40                       | 2,08                         |
| Ø 8,0                 | 8                  | 55                       | 5,00                         |
| Ø 10,0                | 10                 | 70                       | 9,00                         |

no: <http://no.fast-fastening.com/fast/lboxServlet?p=IXK090&AID=288301>

