



DECLARATION OF PERFORMANCE

DOP C4 4.8-0.30 ASPRC30



1. Unique identification code of the product-type:

SPC RIGID CLICK 4.8mm / 0.30 mm wear layer

2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

For use as floor covering in buildings (see EN 14041) according to the manufacturer's specifications.

3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

ASPECTA BVI, Argon 37, 4751XC Oud Gastel, Netherlands

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

--

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 3

6. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Name of the notified test laboratory, that has issued the certificate of conformity of the factory production control, inspection reports and calculation reports (if relevant).

Entwicklungs- und Prüflabor Holztechnologie GmbH
is authorized as a notified body 0766
certificate FLO-24-06-17-01

not applicable

Notified Body

certificate of constancy of performance

7. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not applicable

8. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	B _{fl} s1	EN 14041:2004+AC:2005+AC:2006
Content of Pentachlorophenol	NPD	EN 14041:2004+AC:2005+AC:2006
Formaldehyd Emissions	Class E1	EN 14041:2004+AC:2005+AC:2006
Slip resistance	DS	EN 14041:2004+AC:2005+AC:2006
Electrical behavior (dissipative)	NPD	EN 14041:2004+AC:2005+AC:2006
Electrical behavior (conductive)	NPD	EN 14041:2004+AC:2005+AC:2006
Electrical behavior (antistatic)	NPD	EN 14041:2004+AC:2005+AC:2006
Thermal conductivity [W/mK]	NPD	EN 14041:2004+AC:2005+AC:2006
Water-tightness	NPD	EN 14041:2004+AC:2005+AC:2006

9. The performance of the product identified in points 1 is in conformity with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3
Signed for and on behalf of the manufacturer by:

Graca Rocha , Sustainability & Quality Manager

(name and function)

Netherlands, June 2024

(place and date of issue)

(signature)