

Order number: 04 916 06 99

SCHELL COMFORT regulating angle valve

DIN regulating angle valve with COMFORT handle
With self-sealing connection thread (ASAG easy), test mark: DVGW certified

Scope of delivery:

- long push rod and push rosette Ø 54 mm
- pull-resistant SCHELL brass cone compression connection with length compensation

Field of application / Technical data:

flow class A

Details:

- Material: brass conform German drinking water regulation
- Test Mark: P-IX 212/IA
- Surface: chrome
- Weight: 0.14 kg/pc.
- Packaging unit: 100
- Dimension: DN 10 G 3/8 ext. thread x DN 10 G 3/8 ext. thread

Versions:

Dimension: DN 15 G 1/2 ext. thread x DN 10 G 3/8 ext. thread Order No.: [04 917 06 99](#)

With self-sealing connection thread (ASAG easy), test mark: DVGW certified, chrome, PU 100, W: 0.15 kg/pc.

Dimension: DN 10 G 3/8 ext. thread x DN 10 G 3/8 ext. thread Order No.: [05 098 06 99](#)

With self-sealing connection thread (ASAG easy) with test mark: KIWA, chrome, PU 100, W: 0.14 kg/pc.

Dimension: DN 10 G 3/8 ext. thread x DN 10 G 3/8 ext. thread Order No.: [05 254 06 99](#)

With self-sealing connection thread (ASAG easy), chrome, PU 100, W: 0.14 kg/pc.

Dimension: DN 15 G 1/2 ext. thread x DN 10 G 3/8 ext. thread Order No.: [05 252 06 99](#)

With self-sealing connection thread (ASAG easy), chrome, PU 100, W: 0.15 kg/pc.

