

### 1. General description

Versatile fluid for lubrication cleaning, de-blocking, corrosion protection, water displacement and much more. A quick and valuable help in and around the house.

### 2. Features

- General Corrosion protection.
- Temporary conservation of metal parts during storage.
- Protects metals and alloys.
- Displaces and seals out water and moisture.
- Safe on all metal surfaces, does not stain.
- Safe on most rubbers, plastics and coatings. Test on sensitive or stressed materials before use.
- Convenient 360° (including inverted position) spray valve for aerosols.
- High purity CO<sub>2</sub> propellant, giving an active product content of 95%.
- Loosens metal parts seized by dirt, corrosion or dried-up grease.
- Penetrates quickly.

### 3. Applications

- Surface treatment.
- Seized and corroded parts.
- To remove moisture from ignition systems.
- A modern versatile aid for hundreds of repair jobs in all working environments: automotive, home, leisure,...

### 4. Directions

- Apply a thin even film.
- Use extension tube for more precise application.
- Allow a few minutes for good penetration.
- Repeat if necessary.
- To remove residues or excess product, use one of the CRC cleaners.
- Do not use on energized equipment.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

### 5. Typical product data (without propellant)

Appearance	Liquid.
Color	Amber.
Odor	Salicylate.
Density	0.82 g/cm <sup>3</sup> (@ 20°C).
Flash Point	78 °C (Closed Cup)
Auto Ignition temperature	> 200 °C
Density active product	0.88 g/cm <sup>3</sup> (@ 20°C).





# Technical Data Sheet

---

5-56

---

Typical coat weight

1 --> 2  $\mu\text{m}$

## Remarks

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

**Version** CRC\_RED-5\_56\_CONS-20180809

**Date** 22/08/2018