





RC30 ESSENTIALS RIGID CLICK LVT













TECHNICAL DATA SHEET

PHYSICAL PROPERTIES & PACKAGING (RIGID CLICK FLOORING - 4.8 / 0.30 MM)		
Collection	ESSENTIALS PLANK	ESSENTIALS TILE XL
Use	Commercial & Residential	Commercial & Residential
Size	225 mm x 1210 mm (8.86" x 47.64")	304.8 mm x 609.6 mm (12" x 47.64")
Thickness - Overall	4.8mm	4.8mm
Product Construction	4.0 mm Rigid Core (including 0.30 mm Wear Layer and 0.8 mm IXPE Acoustic Underlay)	4.0 mm Rigid Core (including 0.30 mm Wear Layer and 0.8 mm IXPE Acoustic Underlay)
Wear Layer - Thickness	0.30mm	0.30mm
Edge Detail	4 sides Micro Bevel	4 sides Micro Bevel
Finish	Duraspect™ Extreme Surface Protectant	Duraspect™ Extreme Surface Protectant
Patented Click System	Droplock-100 (I4F)	Droplock-100 (I4F)
Mass per Unit Area	8225 g/m ²	8225 g/m ²
Pieces/Carton	8 pieces	12 pieces
Coverage/Pallet	2.18m ²	2.23m ²
Coverage/Carton	56 Cartons (121, 97m ²)	54 cartons (120.40m ²)
Coverage/Container	20 Pallets (2439.36 m ²)	20 Pallets (2408.05m ²)
Warranty ⁽¹⁾	Material: 20 years (100%) Labour: 10 years (Pro rata)	Material: 20 years (100%) Labour: 10 years (Pro rata)

EUROPEAN / INTERNATIONAL STANDARDS - CE CERTIFICATION / TESTING			
Description	Standard	Symbol	Results
CE Certification	EN 14041		Refer to Standards Below
Reaction to Fire	EN 13501-1 EN ISO 9239-1 EN ISO 11925-2		Bfl - s1 Classification
Formaldehyde Emission	EN 717-1		Class E1
Slip Resistance	EN 13893		Class DS



RC30 ESSENTIALS RIGID CLICK LVT

TECHNICAL DATA SHEET

EUROPEAN / INTERNATIONAL STANDARDS – MANUFACTURING & USAGE (EN 16511)			
Description	Standard	Symbol	Results
Classification (Level of Use)	EN 16511 EN ISO 10874		Commercial - General (Class 32) Refer to Standards Below
Wear Resistance IP,	ISO 24338 Procedure A		≥4,000 cycles
Impact Resistance (Big Ball)	EN 13329:2006, A1:2008, Annex F		No Visible Damage
Micro-Scratch Resistance [Class]	EN 16094, Method A	N/A	MSR-A2
Castor Chair Resistance	EN ISO 4918		After 25,000 cycles: No Disturbance to the Surface; No Delamination, Cracks, or Disruptions
Effect of Furniture Leg	EN ISO 16581 (Tested with foot type 0)		No Visible Damage
Residual Indentation	EN ISO 24343-1		≤0.15mm
Resistance to Staining [Grade, per Group]	EN 438-2 (Group 1 & 3 - Only 10 Minutes)		Groups 1, 2 & 3: Grade 5
Locking Strength	ISO 24334		Long Side ≥ 1.0kN/m Short Side ≥ 1.5kN/m
Dimensional Stability and Curling under influence of Temperature	EN ISO 23999		≤0.15 % ≤ 2mm
Colour Fastness to Light	ISO 105-B02, Method 3		≥Grade 6
Thickness (t)	EN 17539		$\Delta t^{avg} \leq 0.50\text{mm}$ (Versus Nominal) $t^{max} - t^{min} \leq 0.50\text{mm}$
Length (l)			$l \leq 1500\text{mm}: \Delta l \leq 0.5\text{mm}$ $l > 1500\text{mm}: \Delta l \leq 0.3\text{mm/m}$ (Versus Nominal)
Width (w)	EN 17539		$\Delta w^{avg} \leq 0.10\text{mm}$ (Versus Nominal) $w^{max} - w^{min} \leq 0.20\text{mm}$
Squareness (q)			$q^{max} \leq 0.20\text{mm}$
Straightness (s)			$s^{max} \leq 0.30\text{mm/m}$
Flatness (f)	EN 17539	N/A	Maximum Single Values: $f_{w,concave} \leq 0.15\%$, $f_{w,convex} \leq 0.20\%$ $f_{l,concave} \leq 0.50\%$, $f_{l,convex} \leq 1.00\%$
Openings (o)	EN 17539	N/A	Measured from the Surface Between Vertical, Contacting Edges: $o^{avg} \leq 0.15\text{mm}$, $o^{max} \leq 0.20\text{mm}$
Height Difference (h)	EN 17539	N/A	$h^{avg} \leq 0.10\text{mm}$ $h^{max} \leq 0.15\text{mm}$

RC30 ESSENTIALS RIGID CLICK LVT

TECHNICAL DATA SHEET

EUROPEAN / INTERNATIONAL STANDARDS - AUXILIARY PERFORMANCE & SAFETY			
Description	Standard	Symbol	Results
Content of PCP (Pentachlorophenol)	EN 12673:1999		Not detected
Static Electrical Propensity	EN 1815		Antistatic Floor Coverings: ≤2,0kV (Absolute Value)
Thermal Resistance Thermal Conductivity	EN 12664		$R_{23} = 0.048$ (m ² · K)/W $\lambda_{23} = 0.102$ W/m · K
Slip Resistance (Wet)	DIN EN 16165 : 2023 Annex B	N/A	Grade R10
Slip Resistance (UK)	BS 7976-2:2002+A1 2013	N/A	Low Slip Potential
Impact Sound Insulation ⁽²⁾	EN ISO 10140-3 ISO 717-2 EN ISO 140-8		$\Delta L_W = 18$ dB
A-weighted walking sound pressure level	EN 16205:2013		$L_{n,walk} A = 80$ dB(A)
Product-Content Safety	REACH SVHC	N/A	Not detected
Heavy Metals	EN 71-3:2019+A1:2021	N/A	Not detected

Footnotes

1) Warranty: Please see full terms and conditions of our warranties at www.aspecta flooring.com

2) Impact Sound Insulation (EN ISO 10140-3, ISO 717-2, EN ISO 140-8): ΔL_W = Weighted Reduction of Impact Sound Pressure Level

The manufacturing facility is ISO 9001 (Quality Management System) and ISO 14001 (Environmental Management System) certified.

Disclaimer: This document represents the current state of knowledge at the time of its publication and instantly supersedes all previous editions. It may be replaced, supplemented or amended at any time and without special notice. Please be sure to check the validity, relevance and content for topicality before issuing a guarantee claim at www.aspecta flooring.com

