

## Roll-on-wall Cover Plus

### Product description

**Material**                      ROLL-ON-WALL COVER PLUS is a covering, heavy-duty glass veil.

**Use**                                Once applied to the wall, ROLL-ON-WALL COVER PLUS hides medium-sized fibre glass structures and irregular surfaces at once, smoothing out wall surfaces. It is especially advisable for high traffic areas and suitable for contract, as it allows avoiding filling old wall surfaces. Thus, renovation works can be carried out very time efficiently.


- Properties**
- Covers irregular surfaces (medium-sized fibre glass structures)
  - Bridges cracks
  - Quick to a smooth wall:
    - no filling
    - no sanding
    - dust free
    - no noise
    - up to 75 % faster\*
  - ideal as a wall liner

- Certificates**
- complies with CE DIN EN 15102
  - flame retardant in accordance with DIN EN 13501-1 (B.-s2, d0)
  - Standard 100 by Oeko Tex®
  - contains no allergeneous substances
  - A (VOC)

Roll size and packaging	Article	Roll size	Weight approx.	Packing unit	Rolls per pallet
	662-15	1,00 x 15,00 m	550 g/m <sup>2</sup>	6 Rolls	24 Rolls

\*Compared to the classical plaster filling technique.

Version: 12/2021



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)




## Roll-on-wall Cover Plus

### Instructions of use

- First step** Please check product prior to hanging. Irregularities in material are characteristic for this product. They do not entitle to claims. A control of the material and equal batch numbers is required. Claims after usage will not be accepted.
- Wall surface** The wall surface must be dry and evenly absorbent. If necessary, treat prior to hanging.
- Hanging** Use the glass fibre adhesive LECOLLE Xtra Strong observing manufacturer's instructions.
- Cut wallpaper length to according height incl. 5 - 10 cm extra material. Front outside. Apply glue to the wall per length evenly with a lambskin roller. Apply the wallpaper length to the wall smoothing out air bubbles with a rubber roller. Overlap and double cut or butt join following length. Trim excess. Excessive adhesive has to be removed with a damp sponge immediately.
- Painting** Once dry, the wallcovering must be wallpapered. Use a wall liner prior to painting with dispersion, latex or acrylic paint according to DIN EN 13300. Please observe manufacturer's instructions. For further recommendations contact your local distributor.
- Note** The statements above are general recommendations. We exclude any claims based on work conditions and wall constitutions on which we do not have any influence. In case of doubt, please test.

Version: 12/2021



\*Information sur le niveau d'émission de substances volatiles dans l'air intérieur, présentant un risque de toxicité par inhalation, sur une échelle de classe allant de A+ (très faibles émissions) à C (fortes émissions)

