



LK PE-X Universal X16 utbytesrør RiR



NRF nr.	Dim. rør	Lengde	Vekt (kg)
836 49 44	X16	75 m	7,6

RØREGENSKAPER

Betegnelse	Rørdim. (mm)	Materiale	Rørsortiment, utførelse				Tryk-klasse	Temperaturområde			Standard
			Uten varerør	RiR	RiR Ekstra	Isolering		Maks kontinuerlig	Maks momentan	Laveste tillatte	
LK Gulvarmerør	8x1,0 12x2,0	PE-Xa	X				PN6	70 °C	95 °C	-20 °C	EN ISO 15875 (DIN16892/3)
LK Gulvarmerør	16x2,0 20x2,0	PE-RT	X				PN6	60 °C	70 °C	-20 °C	EN ISO 22391 (DIN16833/4)
LK Varmerør	25x2,3 32x2,9	PE-Xa		X			PN6	70 °C	95 °C	-20 °C	EN ISO 15875 (DIN16892/3)
LK Universalrør PE-X	16x2,0 20x2,5 25x3,5	PE-Xa	X	X	X		PN10	70 °C	95 °C	-20 °C	EN ISO 15875 (DIN16892/3)
LK Universalrør PAL	16x2,0 20x2,5 25x3,5 32x3,0 40x3,5 50x4,0 63x4,5 75x7,5	PE-RT/ Al/ PE-RT	X X X X X X X X	X X X X X X X X	X X X X X X X X	X X X X X X X X	PN10	70 °C	95 °C	-20 °C	EN ISO 15875 (DIN16892/3)

