

Robust™ Fiberpuss - Grå

Batch number see side sack print

Declaration of performance

Labelling of declaration of performance and clear identification code of the product type

110330-01-EN998-1-GP

Intended use

Filling mortar, for fixing and bonding thermal insulation panels and for mesh reinforced plastering on insulation and cement-based surfaces. For outdoor and indoor applications.

Manufacturer

Steinhardt AS • Postboks 8627 Ranheim • 7452 Trondheim, Norway

System for assessment and verification of constancy of performance

System 4

Harmonised standard

EN 998-1 :2010

Declared performance

Essential characteristics	Performance
Reaction to fire	A2
Water absorption	W2
Water vapour diffusion resistance factor μ	15/35 (table value)
Tensile strength	$\geq 0,08 \text{ N/mm}^2$ at fractional pattern A, B or C
Thermal conductivity $\lambda_{10,\text{dry},\text{mat}}$	$\leq 0,61 \text{ W/(mK)}$ for P=50% $\leq 0,66 \text{ W/(mK)}$ for P=90% (table values according to EN 1745)
Durability	NPD
Hazardous substances	NPD

The performance of the product conforms with the declared performance. The manufacturer is solely responsible for compiling this declaration of performance which is consistent with the regulation (EU) No. 305/2011.

Signed for the manufacturer and on behalf of the manufacturer of:



Stian Schevig, Daglig leder, Steinhardt AS.

Date of issue. 01.06.2016.