

SPIT GRIP S slaganker Elforsinket uten krave



Bruksområde: montasje i betong. Ventilasjon, rør, kabler, mm.

Hvor kan den brukes	Hva kan den bære (belastning)	Hvordan skal den monteres																				
	Maks. anbefalt belastning: <table><tr><td>3,40 kN</td><td>3,70 kN</td><td>5,80 kN</td><td>10,40 kN</td><td>11,80 kN</td></tr><tr><td>M6 x 30</td><td>M8</td><td>M10</td><td>M12</td><td>M16</td></tr></table> Maks. anbefalt belastning: Skjær <table><tr><td>2,40 kN</td><td>4,10 kN</td><td>6,20 kN</td><td>6,40 kN</td><td>20,60 kN</td></tr><tr><td>M6</td><td>M8</td><td>M10</td><td>M12</td><td>M16</td></tr></table>	3,40 kN	3,70 kN	5,80 kN	10,40 kN	11,80 kN	M6 x 30	M8	M10	M12	M16	2,40 kN	4,10 kN	6,20 kN	6,40 kN	20,60 kN	M6	M8	M10	M12	M16	
3,40 kN	3,70 kN	5,80 kN	10,40 kN	11,80 kN																		
M6 x 30	M8	M10	M12	M16																		
2,40 kN	4,10 kN	6,20 kN	6,40 kN	20,60 kN																		
M6	M8	M10	M12	M16																		

Anbefalt maks. belastningsverdier: i betong 20 mPa


(1 kN ~ 100 kg)

Dim.	Bor diameter do	Boredybde mm ho	Uttrekk N rec - kN	Skjær V rec - kN*	Tiltrekk Nm
M6	8	32	3,40	2,40	5
M8	10	33	3,70	4,10	10
M10	12	43	5,80	6,20	22
M12	15	54	10,40	6,40	36
M16	20	70	11,80	20,60	80

*) Ved boltekkvalitet 8.8

Viktig!


For CE godkjent montasje skal det brukes original slagdor, som med 4 merker markerer korrekt montering.



Sortiment

Best.nr. Anker	NOBB nr.	Best.nr. Slagdor	Dimensjon mm	Antall
050788	30254411		M6 6 x 25	100
062040	30254429	050922	M6 8 x 30	100
062050	30254437	050923	M8 10 x 30	100
062060	30254445	050924	M10 10 x 40	100
062070	30254452	050925	M12 15 x 50	50
062081	30254460	050926	M16 20 x 65	20

M6 8 x 30



De angitte belastningsverdiene er veiledende og må ikke brukes som dokumentasjon. For dokumentasjon skal SPIT Fixing Design Guide brukes, kontakt evt. vår tekniske avdeling for ytterligere veiledning.