




DK

Varenr. 189758

Passer til låsekasse 2014,2016 og 4249. Kan anvendes på døre op til 44 mm tykkelse.

1. Pak alle komponenterne ud af posen.
2. Den udvendige del ⁽¹⁾ med rød og grøn markering monteres. Drej pinden ⁽³⁾ så det viser grønt.
3. Indvendig del monteres ⁽²⁾ og pinden ⁽³⁾ tilpasses hvis nødvendigt.
4. Knækskrue ⁽⁴⁾ klippes til i rette længde. Mål dem når de sidder i de nedfræsedede huller.
Ved dørtykkelse 40 mm skal knækskruen kortes til ca. 39 mm.
5. Knækskrue ⁽⁴⁾ føres gennem rosetten fra indvendig side og gevindbøsningerne ⁽⁵⁾ monteres på modsatte side af døren.
6. Skruerne spændes med en skruetrækker. Overspænd ikke.
7. Clickrosetter ⁽⁶⁾ sættes udover den indvendige roset.
8. Monter vridergreb ⁽⁷⁾ på indvendig del, spænd pinolskrue ⁽⁸⁾ fast
9. VIGTIG: Skruerne efterspændes efter behov.
10. Ved behov for afmontering af clickrosetten - HUSK: Beskyttelse ind mod dørens overflade for at undgå skader.

UK

Item no. 189758

Can be used for mortise lock 2014,2016 and 4249. Can be used on doors up till 44 mm thickness.

1. Unpack all the parts from the poly bag.
2. The outer part ⁽¹⁾ with red and green indicator shall be mounted on the door. Turn the spindle ⁽³⁾ so the indicator is green.
3. The inner part ⁽²⁾ shall be mounted on the door and the spindle ⁽³⁾ shall be cut at correct length if necessary.
4. The cut able screws ⁽⁴⁾ shall be cut in the correct length. Measure the screws when they are fixed in the holes on the inner rose. If the door thickness is 40 mm the cut able screws ⁽⁴⁾ shall be cut at 39 mm length.
5. The cut able screws ⁽⁴⁾ goes throw the inner rose from the inside of the door and the nuts ⁽⁵⁾ shall be fixed on the opposite side of the door.
6. The screws shall be tightened with a manual screwdriver. Do not tighten too hard.
7. The click roses ⁽⁶⁾ is to be put on the inner rose.
8. Fix the turn ⁽⁷⁾ on the spindle on the inside of the door. Tighten the stop screw ⁽⁸⁾ with the allen key.
9. NOTICE: The screws shall be retightened again when needed.
10. If you need to take of the click rose - NOTICE: Protect the surface of the door to avoid damages.