

TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF swell stopp plus	
Profil		The patented EGGER installation system <i>JUST clic!</i> stands for quick and simple installation process without glue. Patented as <i>JUST clic!</i> EP 1 441 087 and EP 1 462 587	
Guarantee domestic area		according to Egger Guarantee	
Guarantee comercial area		according to Egger Guarantee	
Antistatic properties according EN1815		yes, < 2 kV	
Class of use	31		
European Norm EN13329			
Format	CLASSIC		
Dimension mm (length x width)	1292 x 192		
Complete thickness	7	9	
Thickness of <i>silenzio@ special cellulose</i>		2	
Bevel	-		
Profil	<i>JUST clic!</i>		
Pallet	Packaging		
Paket information	One-way-pallet		
	Piece	10	7
	m2	2,48	1,74
	kg	15,39	11,00
Pallet information			
	Piece	520	420
	m2	128,99	104,19
	kg	815,00	676,00
Classification and general requirements			
abrasion resistance according EN13329	AC3 (IP ≥ 2000)		
impact resistance according EN13329	IC1		
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4		
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact		
Effect of a castor chair according EN425	No change in appearance or damage		
Castor chairs according EN12529	Type W		
Thickness swelling according EN13329	≤ 18 %		
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm		
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4		
Static indentation by constant pressure according EN13329	< 0,01		
Surface soundness according EN13329	≥ 1,0 N/mm2		
Thermal resistance according to EN 12667	0,07 m² K/W	0,12 m² K/W	
Impact Sound Reduction according to EN ISO 10140 -3	-	18 dB	
Room Sound Reduction IHD W 431	-	30% (1)	

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm EN13329		
Format	CLASSIC	
Dimension mm (length x width)	1291 x 193	
Complete thickness	8	10
Thickness of silenizio® special cellulose	2	
Bevel	-	WV2
	Packaging	
Pallet	One-way-pallet	
Paket information		
	Piece	8
	m2	1,99
	kg	13,86
	Piece	7
	m2	1,74
	kg	12,38
Pallet information		
	Piece	480
	m2	119,40
	kg	850,00
	Piece	392
	m2	97,67
	kg	703,59
Classification and general requirements		
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Surface soundness according EN13329	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,07 m² K/W	0,12 m² K/W
Impact Sound Reduction according to EN ISO 10140 -3	-	17 dB
Room Sound Reduction IHD W 431	-	38% ⁽¹⁾

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



TECHNICAL DATASHEET		
EGGER LAMINATE FLOORING		
Coreboard		HDF Aqua Plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm EN13329		
Format	CLASSIC	
Dimension mm (length x width)	1291 x 193	
Complete thickness	8	10
Thickness of silenzio® special cellulose	2	
Bevel	WV4	WV4
	Packaging	
Pallet	One-way-pallet	
Paket information		
	Piece	7
	m2	1,74
	kg	13,80
Pallet information		
	Piece	392,00
	m2	97,44
	kg	782,94
Classification and general requirements		
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 5 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Surface soundness according EN13329	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,06 m² K/W	0,12 m² K/W
Impact Sound Reduction according to EN ISO 10140 -3	-	17 dB
Room Sound Reduction IHD W 431	-	34% (1)

* reference flooring construction: 7 mm laminate flooring on 3 mm PE-Foam and 0,2 mm PE-Film
The determined room sound improvement gives the percentage reduction of the loudness feeling relating to the reference.



TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm EN13329		
Format	LARGE	
Dimension mm (length x width)	1291 x 246	
Complete thickness	8	
Thickness of silenizio® special cellulose		
Bevel	WV4	
	Packaging	
Pallet	One-way-pallet	
Paket information		
	Piece	8
	m2	2,54
	kg	18,00
Pallet information		
	Piece	360
	m2	114,30
	kg	822,00
Classification and general requirements		
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Surface soundness according EN13329	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,08 m² K/W	



TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF Aqua Plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use		32
European Norm EN13329		
Format		KINGSIZE
Dimension mm (length x width)		1291 x 327
Complete thickness		8
Thickness of silenizio® special cellulose		
Bevel		WV4+1
Pallet		Packaging One-way-pallet
Paket information		
	Piece	6
	m2	2,53
	kg	17,84
Pallet information		
	Piece	240
	m2	101,20
	kg	727,00
Classification and general requirements		
abrasion resistance according EN13329		AC4 (IP ≥ 4000)
impact resistance according EN13329		IC2
resistance to staining EN438		group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425		No change in appearance or damage
Castor chairs according EN12529		Type W
Thickness swelling according EN13329		≤ 5%
tolerance of top layer according EN13329		length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329		blue wool scale ≥ level 6 grey wool scale ≥ level 4
Static indentation by constant pressure according EN13329		< 0,01
Surface soundness according EN13329		≥ 1,0 N/mm2
Thermal resistance according to EN 12667		0,06 m² K/W



TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm EN13329		
Format	KINGSIZE	
Dimension mm (length x width)	1291 x 327	
Complete thickness	8	
Thickness of silenizio® special cellulose		
Bevel	-	WV2
Pallet	Packaging	
Paket information	One-way-pallet	
	Piece	6
	m2	2,53
	kg	17,84
Pallet information		
	Piece	240
	m2	101,20
	kg	727,00
	Classification and general requirements	
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Surface soundness according EN13329	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,07 m² K/W	



TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use	32	
European Norm EN13329		
Format	LONG	
Dimension mm (length x width)	2052 x 248	
Complete thickness	9	
Thickness of silenizio® special cellulose		
Bevel	WV4	
Pallet	Packaging One-way-pallet	
Paket information		
	Piece	5
	m2	2,54
	kg	22,12
Pallet information		
	Piece	180
	m2	91,60
	kg	824,00
Classification and general requirements		
abrasion resistance according EN13329	AC4 (IP ≥ 4000)	
impact resistance according EN13329	IC2	
resistance to staining EN438	group 1 + 2: level 5 group 3: level 4	
Effect of furniture leg according EN424	No damage shall be visible, when tested with foot Type 0 artefact	
Effect of a castor chair according EN425	No change in appearance or damage	
Castor chairs according EN12529	Type W	
Thickness swelling according EN13329	≤ 18 %	
tolerance of top layer according EN13329	length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm	
Light fastness according EN13329	blue wool scale ≥ level 6 grey wool scale ≥ level 4	
Static indentation by constant pressure according EN13329	< 0,01	
Surface soundness according EN13329	≥ 1,0 N/mm2	
Thermal resistance according to EN 12667	0,08 m² K/W	



TECHNICAL DATASHEET

EGGER LAMINATE FLOORING

Coreboard		HDF swell stopp plus
Profil		The patented UNI <i>fit!</i> installation system stands for a quick and simple installation process without glue. Produced under the licence of Flooring Industries™.
Guarantee domestic area		according to Egger Guarantee
Guarantee comercial area		according to Egger Guarantee
Antistatic properties according EN1815		yes, < 2 kV
Class of use		33
European Norm EN13329		
Format		CLASSIC
Dimension mm (length x width)		1291 x 193
Complete thickness		11
Thickness of silenizio® special cellulose		
Bevel		WV4
		Packaging
Pallet		One-way-pallet
Paket information		
	Piece	6
	m2	1,49
	kg	14,69
Pallet information		
	Piece	312
	m2	77,74
	kg	778,00
		Classification and general requirements
abrasion resistance according EN13329		AC5 (IP ≥ 6000)
impact resistance according EN13329		IC3
resistance to staining EN438		group 1 + 2: level 5 group 3: level 4
Effect of furniture leg according EN424		No damage shall be visible, when tested with foot Type 0 artefact
Effect of a castor chair according EN425		No change in appearance or damage
Castor chairs according EN12529		Type W
Thickness swelling according EN13329		≤ 18 %
tolerance of top layer according EN13329		length ± 0,2 mm width ± 0,1 mm thickness ± 0,5 mm
Light fastness according EN13329		blue wool scale ≥ level 6 grey wool scale ≥ level 4
Static indentation by constant pressure according EN13329		< 0,01
Surface soundness according EN13329		≥ 1,0 N/mm2
Thermal resistance according to EN 12667		0,12 m² K/W

