



## DECLARATION OF PERFORMANCE

No. 5/4

1. **Birch Plywood Type FSF with the thickness 9-40 mm (FSF 9-40)**
2. Batch no.: see package.
3. For internal use in humid conditions (uncoated) and for external use (coated and with sealed edges) as structural components –  
EN 13986 : 2004 (4.2, 4.3)
4. Manufacturer: **JSC „SVEZA Ust-Izhora“**  
ul. Fanernaya 5, Pontonny, Saint Petersburg, 196643, RUSSIA

5. Non-applicable

6. System of assessment and verification of consistency of performance of the construction product as set out in Annex V: EN 13986:2004 System 2+

7. The notified body:

- 1075 -

The Bremen Institute for Materials Testing (MPA Bremen)  
Paul-Feller-Str. 1, 28199 Bremen, Germany

has performed the certification in accordance with EN 13986, System 2+ and issued the certificate of conformity of the factory production control:

**1075-CPD-Z291-4/15**

8. Non-applicable

9. Declared performance:

<i>Essential characteristics</i>	<i>Performance</i>	<i>Harmonized technical specification</i>
Bending strength	F40/25	EN 636 : 2012, Table 1
Modulus of elasticity	E70/40	EN 636 : 2012, Table 2
Bonding quality	Class 3	EN 636 : 2012, EN 314-2:1993
Formaldehyde release	E1	EN 636 : 2012, Table 3
Reaction to fire	D-s2, d0	EN 13986:2004, Table 8

10. The performance of the product is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer.

Signed for and on behalf of the manufacturer by:

Saint Petersburg, January 29th, 2015



Svyatoslav G. Sarson  
Director of Branch «Ust-Izhora»  
of JSC «SVEZA»