

# SWISSTEC Sourcing Ltd.

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,  
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-078

Item No: 502016269











**Description:**

CBS CSK FLAT HD TX25 HALF THRD SST A2 PASSIVATED WAX 5x60

Material: A2

Certificate No.: E-30-20560-15

Report No.: 1015-CPR-30-10585/11

	Nominal diameter	Inner thread diameter	Total length	Head diameter	Thread length	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre) $(N/mm^2)$	Head pull-through parameter $(N/mm^2)$	Yield moment $(Nmm)$	Tensile capacity $(kN)$
Description	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)	(N/mm <sup>2</sup> )	(N/mm <sup>2</sup> )	(Nmm)	(kN)
										
5x60	4.7 - 5.0	2.95 - 3.15	58.5 - 60.0	9.64 - 10.0	34.5 - 37.5	1.61	16.42 / 12.99	22.53	4066	5.36
Characteristic density of wood $\rho_k$ (kg/m <sup>3</sup> )						450	390	450	-	
Durability (i.e. corrosion protection)						Stainless steel A2 (Service Class 3 acc. To EN 1995-1-1)				

**The manufacturer declares for:**

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 18 Apr 2019



Hieu Trong Nguyen