

K 950 S | 10 kg class drilling and breaking hammer

Article: 4933449400



- 20 J blow energy for Hard hitting performance.
- Variolock (12 positions) for selecting the most appropriate chisel angle.
- 6 m cable.
- 1700 watt motor - best in class with plenty in reserve for the toughest applications.
- DIGITRONIC® - fullwave electronics for precise power adjustment to application.
- 3 handles - all with AVS (Anti-Vibration-System) and soft grip for comfortable and less tiring use.
- All metal gearcase - optimum seating of the gears for enhanced service life.

K 950 S	
Article Number	4933449400
Blow energy (EPTA)(J)	20
Full load hammer action (bpm)	975 - 1950
Full load speed (soft hammer) (rpm)	125 - 250
Max. drilling core bit (mm)	150
Max. drilling solid bit (mm)	50
Max. drilling tunnel bit (mm)	80
No load speed (rpm)	125 - 250
Power input (W)	1700
Sound power level (dB(A))	11
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	100
Sound pressure level uncertainty (dB(A))	3
Supplied in	Kitbox
Vibration chiseling (m/s ²)	11
Vibration chiselling uncertainty (m/s ²)	2
Vibration drilling (m/s ²)	12.5
Vibration drilling into concrete [m/s ²]	11
Vibration drilling into concrete uncertainty [m/s ²]	2
Weight (kg)	11.8