

EAN: 6414150101632  
 NRF: 4203771  
[static.oras.com/9210FZ-104](http://static.oras.com/9210FZ-104)



Electra 92 series is giving you a whole new modern design with its rounded square body and spout. Giving you new fresh and updated design.

Design compliments the new trends of the modern bathroom with its more squared design.

#### Key Features

Aerator with Eco flow limitation for ECO building installation  
 Newest Sensor technology for better detection and operation comfort  
 Bluetooth technology for easy adjustment to personalize settings  
 Antiscalding protection  
 Temperature measurement  
 Battery and power cable

- Public, GreenBuilding, Housing
- Berøringsfri, Batteridrevet, Separat omformer, Bluetooth®, Blyfri
- Benkemontert
- Forkrommet
- Fast tut
- PCA® strålesamler med konstant vannmengde uavhengig av trykk, Justerbar vannstråle
- Temperaturreguleringshendel
- Justerbar varmtvannsbegrenser (ettermonterbar)
- Manuell blandeventil, Tilbakeslagsventil, Smussfilter
- Advanced PSD sensor, Signallys, Indikator for lav spenning
- Fleksible slanger
- 3S Installasjon

## Teknisk data

### Flow attributter

Vannmengde ved 300 kPa (med vannmengdebegrenser) **0.057 l/s**

### Tekniske egenskaper

Varmtvannsforsyning **max. +70°C**  
 Arbeidstrykk **100 - 1000 kPa**  
 Tilkoblingsstørrelse **G3/8**  
 Prosjeksjon **117 mm**  
 Tilbakeslagssikring (EN1717) **EB**  
 Materiale **Composite**

### Program instillinger

Etterrenningstid **3 s (1-20 s)**  
 Automatisk spyling **off (off/1-120 h)**  
 Automatisk spyling periode **30 s (1-1800 s)**  
 Funksjonstid **2 min (1 - 1800 s)**

### Elektroniske attributter

Elektrisk tilkobling **9 V**  
 Batteri **AA 1.5 V Lithium x 2**  
 Bluetooth version **5.x (D060576)**

### Bestemmelser

EU Directive **C € Radio Equipment Directive 2014/53/EU , Low Voltage Directive 2014/35/EU , EMC Directive 2014/30/EU , RoHS Directive 2011/65/EU**

EN Standard **EN 15091, ETSI EN 301 489-1 V1.9.2 , ETSI EN 300 328 v2.2.2 , EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011+AC:2012 , EN 60335-1:2012+A11+A13+A14+A15:2021, Part 19.11.4**

Støyklasse **I (ISO 3822)**

Tetthetsklasse **IP 55**



