## **PRODUCT OVERVIEW & USPS GBH 18V-28 C**

SP!

#### **Corded power with 18 Volt freedom**

3.4J of impact energy (0.2J more than corded equivalents & 36V predecessor) 3.4

HEAVY

DUTY

BRUSHLESS

Brushless motor

#### Smart hammer – Perfect tool control USP! (user interface & connectivity)

- Real-time tool status notifications (Temperature, Battery, etc.) via user interface & smart device
- Individual adjustments with Bluetooth CoMo via Bosch Toolbox app
- 3 different working modes (Auto, Favorite, Soft) to ensure the right performance setting for any job



#### **LED Worklight**

For working in dark areas





8.0 Ah

Pro CORE 18V

#### HEALTH

#### **Outstanding PROtection features**

**KickBack Control** Vibration Control

VIBRATION KICKBACH

#### HEALTH **Dustless Drilling**

- Compatible to existing GDE 18V-16
- Easy attachable and integrated on tool



#### SIMPLIFICATION

#### **Tool Hook**

Used to hang up the tool during jobs, reducing interruptions for more efficient and convenient work



NEW!



BOSCH

# GBH 18V-28 C Professional

### Solo, L-Boxx

**Impressive performance** Brushless motor striking mechanism with 3.4J impact energy

#### Health and simplification

2 Increased user health protection thanks to KickBack Control, Vibration Control and GDE 18V-16 compatibility

Perfect control and the right setting for every job

3 Three different work modes (Auto, Favorite, Soft) available via the user interface

| Marketing & Logistics       |                    | Scope of supply | Part no.   |
|-----------------------------|--------------------|-----------------|------------|
| SKU                         | 0611920001         | Baretool        | 3611J20000 |
| EAN code                    | 4059952611648      | L-Boxx 238      | 1600A012G2 |
| Tool dimension (LxWxH)      | 363 x 103 x 249 mm | L-Boxx Inlay    | 608285074J |
| Packaging dimension (LxWxH) | 442 x 357 x 253 mm |                 |            |
| Weight (gross/net) est.     | 6.63 kg/3.3 kg     |                 |            |
|                             |                    |                 |            |

All the power, no cord: the cordless rotary hammer for full throttle hammer drilling



Technical information

| lechnical information           |         |                               |
|---------------------------------|---------|-------------------------------|
| Voltage                         | [V]     | 18                            |
| Max. impact energy              | [J]     | 3.4                           |
| No-load speed                   | [rpm]   | 0 - 950                       |
| Impact Rate                     | [1/min] | 0 - 4220                      |
| Weight w/o battery              | [kg]    | 3.3                           |
| Max. drilling diameter concrete | [mm]    | 28                            |
| Compatible dust extraction      |         | GDE 18V<br>GDE 16 p<br>GDE 68 |
|                                 |         |                               |

|                        | Target groups                                     | Applications   |
|------------------------|---|--|
| 8                      |   | Hammer drilling in concrete;                               |
| 3.4                    | Foundation & Structure<br>(Masonry & Restoration) | Medium to heavy duty<br>anchoring (main drilling           |
| ) – 950                |   | diameters of 8-14mm)                                       |
| ) – 4220               | HVAC / Plumber                                    | Hammer drilling in concrete;<br>Installation of washbasins |
| 3.3                    |   | requiring 14mm diameter<br>Installation of cable racks     |
| 28                     | Electrician                                       | and carrier systems  |
| GDE 18V-16,            | Licencian   | Chiseling tasks for correction/<br>adaption work           |
| GDE 16 plus,<br>GDE 68 | Rough Carpenter/<br>Framer                        | Drilling concrete attached to<br>metal plate               |

